

No. 654,402.


Patented July 24, 1900.

H. N. KING.

FASTENER FOR ATTACHING MAIL BOXES TO POSTS.

(Application filed Mar. 13, 1900.)

(No Model.)



WITNESSES.

O. P. Breyer
M. Hickey

INVENTOR.

Henry N. King
By Newell S. Wright

His Attorney

UNITED STATES PATENT OFFICE.

HENRY N. KING, OF ADRIAN, MICHIGAN.

FASTENER FOR ATTACHING MAIL-BOXES TO POSTS.

SPECIFICATION forming part of Letters Patent No. 654,402, dated July 24, 1900.

Application filed March 13, 1900. Serial No. 8,435. (No model.)

To all whom it may concern:

Be it known that I, HENRY N. KING, a citizen of the United States, residing at Adrian, county of Lenawee, State of Michigan, have
5 invented certain new and useful Improvements in Fasteners for Attaching Mail-Boxes to Posts; and I declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the
10 art to which it appertains to make and use the same, reference being had to the accompanying drawings, which form a part of this specification.

My invention has for its object to provide
15 a fastener for attaching mail-boxes to posts; and it consists of the structure, combination, and arrangement of devices hereinafter described and claimed and illustrated in the accompanying drawings, in which—

20 Figure 1 is a view in side elevation. Fig. 2 is a view in rear elevation. Fig. 3 is a view in cross-section through the fastening device. Fig. 4 is a view in vertical section there-through. Fig. 5 is a detail view in perspective
25 of the clamp-holder. Fig. 6 is a detail view in perspective of the clamp. Figs. 7 and 8 illustrate different modifications in the construction of the clamp *f* to engage the square and the round post.

30 More particularly my invention is designed to provide a fastener for the purpose above mentioned, whereby a mail-box may be firmly secured to a post in a very simple, superior, and economical manner.

35 In carrying out my invention a mail-box of any desired construction is indicated at *a*, and a post, which may also be of any desired construction, is indicated at *b*. The particular post herewith shown is formed of two corresponding parts riveted together, the body
40 or central portion of the post being essentially diamond-shaped in cross-section and having flanges through which the parts are riveted together, as indicated at *c*.

45 To the mail-box I secure a clamp-holder *d*, (indicated in detail in Fig. 5,) the holder being provided with an attaching-plate, (indicated by the numeral 1,) which may be riveted or otherwise secured to the box, as indicated at
50 *e*. The clamp-holder is also provided with rearwardly-projecting walls, (indicated by the numerals 2 and 3.) Said walls are connect-

ed at their upper and lower extremities with webs, (indicated by the numeral 4,) said webs recessed or shaped to fit the adjacent side of
55 the post.

Inasmuch as I have shown in the drawings herewith a post having the body thereof essentially of diamond shape in cross-section the webs 4 4 are shown provided with corresponding V-shaped slots 5 5 to receive the adjacent body portion of the post. I do not, however, limit myself to any particular shape
60 of the post nor to any particular shape of said webs 4 4 and their recesses 5 5, inasmuch as 65 it is obvious that if a round post were employed said recesses would be of round form, or if a square post were employed said recesses would be made square.

The plate 1, with the walls 2 3 and end
70 webs or flanges 4 4, form a chamber or housing in which is engaged a clamp *f*, this clamp, as shown in Fig. 6, being formed with three sides, (indicated by the numerals 6, 7, and 8,) the side walls 7 and 8 being provided with
75 inwardly-projecting flanges 9 9. The shape of this clamping device may vary, however, if desired, the same being open at its extremities and engaged within the clamp-holder by means of a bolt or screw *g*, having
80 a threaded engagement therewith, the bolt being passed through the mail-box from the interior thereof and through the attaching portion 1 of the clamp-holder and so engaging the clamp. The clamp is removable
85 from the clamp-holder when the bolt or screw *g* is disengaged therefrom. To secure the device to the post, the clamp is first removed from the clamp-holder and slipped upon the post. The clamp is then engaged in the
90 clamp-holder and the screw *g* is engaged with the clamp, thereby tightening the flanges 9 9 upon the adjacent portion of the post and binding the post between said flanges and the end flanges 4 4 of the holding device. 95

In a post constructed as shown the clamp is forced downward upon the post below the upper rivets *c c*, and when tightened in place by the screw it will be obvious that the device cannot be slipped off from the post, as
100 the clamping-flanges 9 9 not only bind the post against the end flanges 4 4 of the holder when the screw is set, but the projecting heads of the rivets *c c* effectually prevent

the device being slipped off from the post until the screw is loosened, access to the screw of course being controlled by the lock upon the mail-box.

5 In Fig. 7 I have shown the clamp *f*, instead of being three-sided, formed in the shape of a band or four-sided clamp to be slipped over the end of the post, in which case, of course, the webs 4 will be recessed of corre-
10 sponding form.

In Fig. 6, where a round post is shown, the clamp *f* may be of circular form to be also slipped over the post, and in which case the webs 4 would be recessed of corresponding
15 form.

What I claim as my invention is—

1. The combination with a mail-box, of a clamp-holder rigidly attached to the mail-box on the outside thereof, a clamping device to
20 engage a post having an adjustable engagement with the clamp-holder, and a bolt passed through the side of the mail-box from within the box to adjust and secure the clamping device with the clamp-holder.

25 2. The combination with a mail-box, of an adjustable clamping device to engage a post, a clamp-holder open on its rear side secured to the box on the outside thereof to receive the clamping device, and a tightening device
30 passed through the box from within to secure and adjust the clamping device with the clamp-holder and bind the post against adjacent portions of the clamp-holder.

3. A fastener for attaching mail-boxes to
35 posts provided with a clamping device con-

structed with clamping-flanges to engage the post, a clamp-holder to receive the clamping device constructed with end webs or flanges to receive the adjacent portion of the post, and means to engage the clamping device
40 with the clamp-holder.

4. A fastener for attaching mail-boxes to posts provided with a clamping device open at its extremities to be slipped over the end
45 of the post, a clamp-holder to receive the clamping device and the adjacent portion of the post, and means to engage the clamping device with the clamp-holder.

5. A fastener for attaching mail-boxes to posts provided with a clamp open at its ex-
50 tremities to engage a post, a clamp-holder secured to the box provided with side walls and end webs to receive the clamping device, and means to secure the clamping device within the clamp-holder.

6. A fastener for attaching mail-boxes to posts provided with a clamping device to en-
55 gage the post, a clamp-holder to receive the clamping device, and means to engage the clamping device with the clamp-holder, said
60 clamp-holder provided with end webs or flanges recessed to correspond to the form of the post.

In testimony whereof I sign this specification in the presence of two witnesses.

HENRY N. KING.

Witnesses:

IRA LONG,
JOHN GAHAGAN.