
No. 655,002.

Patented July 31, 1900.

## G. H. ORCUTT. CLOTHES DRIER.

(Application filed Sept. 16, 1899.)

(No Model.)



Witnesses. Harry M. Rugg. M. G. Regan. Inventor. G.H.Orcutt, By Ottomorys. Southgate Southgate,

## United States Patent Office.

GUY H. ORCUTT, OF WORCESTER, MASSACHUSETTS.

## CLOTHES-DRIER.

SPECIFICATION forming part of Letters Patent No. 655,002, dated July 31, 1900.

Application filed September 16, 1899. Serial No. 730,676. (No model.)

To all whom it may concern:

Be it known that I, GUY H. ORCUTT, a citizen of the United States, residing at Worcester, in the county of Worcester and State of Massachusetts, have invented a new and useful Clothes-Drier, of which the following is a specification.

My invention relates to that class of clothes-driers which are provided with bars or rods pivotally connected to a base or center piece to extend radially at different angles therefrom; and the object of my present invention is to provide a strong, simple, and efficient clothes-drier of the class which can be detachably hung upon a door-casing, window-casing, or similar support without marring or defacing the same and which can be compactly folded into small compass when not in use.

To these ends a clothes-drier constructed according to my invention consists of the parts and combinations of parts, as hereinafter described, and more particularly pointed out in the claim at the end of this specification.

The accompanying drawing is a perspective view taken from the rear side of a clothesdrier constructed according to my invention.

A clothes-drier constructed according to my present invention comprises a base-piece, preferably of metal, a plurality of arms pivotally mounted on the base-piece, and extending up from the rear side of the base-piece is a supporting-arm having an overhanging

upper end provided with teeth or projections for supporting the device from a door-casing, window-casing, or similar support. The supporting-arm is long enough to bring the pivoted bars within easy reach of the person using

40 the drier, and the supporting-arm is preferably hinged or jointed near its lower end, so that the same can be folded down over the pivoted bars to allow the device to be compactly folded together when not in use.

Referring to the drawing and in detail, 10 designates a substantially-semicircular casting which forms the base-piece of a clothesdrier constructed according to my invention. Pivotally mounted on rivets or screws 11, extending up from the base-piece 10, are wooden arms or rods 12, which extend radially from said base-piece and may be swung or turned to any desired position in the ordinary manner. Extending up from the rear side of the base-piece 10, preferably from substantially

the middle thereof, is a supporting-arm 13. The supporting-arm 13 is provided at its upper end with an overhanging portion 14, having inclined teeth 15, which are sharpened, so as to seat themselves in the top of a door or 60 window casing or similar support from which the device is hung. The supporting-arm 13 is pivoted or hinged at 16 near its lower end, so that when the device is not in use the supporting-arm may be folded down over the 65 wooden bars or arms 12, so that the clothesdrier may be compactly folded and put away when not in use.

In order to prevent the clothes-drier from scratching or marring the face of the door- 70 casing or window-casing from which the same is supported, the base-piece 10 is preferably provided with a backing-strip, of rubber or similar material, as 17, the rubber strip 17 not only serving as a cushion to prevent the 75 clothes-drier from marring the paint of the window-casing or door-casing from which the same is hung, but also having a tendency to prevent the clothes-drier from swinging or oscillating sidewise with respect to its sup-80 porting-hook 14.

I am aware that many changes may be made in the construction of my clothes-drier by those who are skilled in the art without departing from the scope of my invention as 85 expressed in the claims. I do not wish, therefore, to be limited to the form which I have herein shown and described; but

What I do claim, and desire to secure by Letters Patent of the United States, is—

In a clothes-drier, the combination of a base-piece or casting 10, a plurality of rods or bars 12 extending radially therefrom and pivotally mounted on rivets 11 secured in the base-piece 10, a supporting-arm 13 extending 95 up from the rear side of the base-piece or casting 10, and having a hooked upper end for hanging the clothes-drier from a window-casing, a door-casing, or similar support without marring the face thereof, said supporting-arm being hinged or jointed as at 16 to fold down over the bars 12 when not in use, substantially as described.

In testimony whereof I have hereunto set my hand in the presence of two subscribing 105 witnesses.

GUY H. ORCUTT.

Witnesses:

LOUIS W. SOUTHGATE, PHILIP W. SOUTHGATE.