

No. 657,217.

Patented Sept. 4, 1900.


W. HEEREN.

SIGN.



(Application filed July 27, 1897.)

(No Model.)


*Fig. 1.*



*Fig. 2.*



*Fig. 4.*



WITNESSES:

*J. P. Appleman.*  
*A. M. Wilson*

*Fig. 3.*

INVENTOR

*William Heeren.*  
BY  
*Henry C. Evert.*  
ATTORNEY.

# UNITED STATES PATENT OFFICE.

WILLIAM HEEREN, OF PITTSBURG, PENNSYLVANIA.

## SIGN.

SPECIFICATION forming part of Letters Patent No. 657,217, dated September 4, 1900.

Application filed July 27, 1897. Serial No. 646,065. (No model.)

*To all whom it may concern:*

Be it known that I, WILLIAM HEEREN, a citizen of the United States of America, residing at Pittsburg, in the county of Allegheny and State of Pennsylvania, have invented certain new and useful Improvements in Signs, of which the following is a specification, reference being had therein to the accompanying drawings.

o This invention relates to certain new and useful improvements in signs, and has for its object to construct a sign of pliable materials to permit its being bent into any shape desired.

15 The invention further aims to construct a sign which will be strong, durable, effectual in its appearance, and comparatively inexpensive to manufacture; and the invention further aims to produce a sign which will be weatherproof.

20 With the above and other objects in view the invention finally consists in the novel construction, combination, and arrangement of parts to be hereinafter more specifically described, and particularly pointed out in the claim.

In describing the invention in detail reference is had to the accompanying drawings, forming a part of this specification, and where- 30 in like figures of reference indicate similar parts throughout the several views, in which—

Figure 1 is a front view. Fig. 2 is a longitudinal sectional view on line X X of Fig. 1. Fig. 3 is a back view showing parts cut away. 35 Fig. 4 is a vertical sectional view on line Y Y of Fig. 3.

Referring to the drawings, 1 designates the body of the sign, composed of celluloid, and 2 the sign letter, character, or the like.

40 3 designates lugs or projections.

4 designates a backing of pliable material, preferably lead, which also serves as a backing of the sign.

5 designates a sheet of rubber.

45 In constructing the sign the letters, characters, or the like having a coating of adhesive material on the back are arranged in the desired design. A sheet of celluloid is placed

on the design, the letters adhering to the celluloid. Over the celluloid is placed a thin 50 sheet of rubber, and a sheet of lead forming the backing is placed over the rubber sheet. The sign, as above built up, is placed in a frame of metal corresponding to shape and size of the sign and placed upon a highly- 55 polished heated surface, and when force is applied to the backing the celluloid, having been made soft and pliable by the action of the heat, will be pressed flush with the face of the sign-letters by the metallic backing 4. 60 The action of the heat upon the sheet of rubber cements the celluloid and pliable plunger or the backing firmly together. Furthermore, by one action, as above described, a finished polished article is made. 65

In large signs lugs 3 are used to fasten the letter to the backing; but I do not claim the lugs as a novel feature of my invention.

It will be noted that various changes may be made in the details of construction with- 70 out departing from the general spirit of my invention.

Having fully described my invention, what I claim as new, and desire to secure by Letters Patent, is— 75

The herein-described method for manufacturing signs which consists in first providing a metallic plate with a suitable open design and coating one of its faces with an adhesive material then placing the same on a heated 80 block, second applying to the coated face thereof a celluloid wafer, third applying to the back face of the celluloid wafer a thin sheet of rubber, fourth applying to the sheet of rubber a suitable backing of a flexible metallic plate and fifth in compressing the said 85 parts together to force a portion of said celluloid into the open design to form the finished sign, substantially as and for the purpose set forth. 90

In testimony whereof I affix my signature in presence of two witnesses.

WILLIAM HEEREN.

Witnesses:

W. H. TIMMERMAN,  
THOS. M. BOYD, Jr.