


No. 658,613.

Patented Sept. 25, 1900.

J. A. BERONIO.  
BARREL OPENER.

(Application filed Mar. 13, 1900.)

(No Model.)





# UNITED STATES PATENT OFFICE.

JOSEPH A. BERONIO, OF MEMPHIS, TENNESSEE.

## BARREL-OPENER.

SPECIFICATION forming part of Letters Patent No. 658,613, dated September 25, 1900.

Application filed March 13, 1900. Serial No. 8,509. No model.)

*To all whom it may concern:*

Be it known that I, JOSEPH A. BERONIO, a citizen of the United States, and a resident of Memphis, in the county of Shelby and State of Tennessee, have invented a new and Improved Barrel-Opener, of which the following is a full, clear, and exact description.

The purpose of this invention is to provide a device for removing the top hoop of barrels and which may be used with equal facility whether the head is in the barrel or not.

This specification is the disclosure of one form of the invention, while the claims define the actual scope thereof.

Reference is to be had to the accompanying drawings, forming a part of this specification, in which similar characters of reference indicate corresponding parts in all the views.

Figure 1 is a perspective view showing the invention in use. Fig. 2 is a sectional view showing the invention in use in connection with a barrel the head of which has been removed. Fig. 3 is a rear elevation with the handle in section, and Fig. 4 is a sectional side elevation showing an arrangement of parts different from that shown in Figs. 1 and 2.

The instrument comprises a hand-lever or handle *a*, to one end of which is pivoted a hook, comprising a shank *b* and a transversely-disposed plate *b'*, the edge of which is turned edgewise to form the bill of the hook, such hook serving to engage the hoops of the barrel, as illustrated. Pivoted to the hand-lever *a* directly adjacent to the hook is a link *c*, the free end of which terminates in an enlargement *c'*, formed with two openings *c<sup>2</sup>* and *c<sup>3</sup>* therein. To this head is pivotally connected by a pin *d'* lugs *d<sup>2</sup>*, fastened on and forming part of the foot *d*. This foot is in the form of a plate with a slight transverse bend therein, as best shown in Fig. 2. The upper end of the plate terminates in a ledge *d<sup>3</sup>*, which is directly adjacent to a return-flange *d<sup>4</sup>*, and the lower end of which terminates in spurs *d<sup>5</sup>*. The foot is pivotally mounted on the link *c*; but in operation it is intended to be fastened thereto by means of a cotter or like pin *e*, which is capable of being projected into either one of the openings *c<sup>2</sup>* and *c<sup>3</sup>*, and thus hold the foot *d* in either one of two positions. When the pin *e* is placed in

the opening *c<sup>2</sup>*, the foot *d* is held with the link *c* approximately perpendicular thereto, as in Fig. 1, and when the pin is placed in the opening *c<sup>3</sup>* the foot is held approximately in the plane of the link *c*, as shown in Figs. 2 and 3.

In using the device to open a barrel the head and hoops of which are in place the foot *d* is secured with respect to the link *c* in the position shown in Fig. 1, whereupon the foot has its spurs *d<sup>5</sup>* rested on the head of the barrel and the ledge *d<sup>3</sup>* engaged with the staves. The hook comprising the shank *b* and the flanged plate *b'* is now engaged with the staves, and by throwing down the free end of the hand-lever *a* the hoops may be drawn from the barrel. Should it be desired to remove the hoops of a barrel, the head of which has been removed, the foot is secured in the position shown in Figs. 2 and 3 and the returned flange *d<sup>4</sup>* engaged with the upper ends of the staves, thus permitting the spurs *d<sup>5</sup>* to engage against the inner sides of the staves. Then by engaging the hook with the hoops of the barrel and drawing down on the lever the hoops may be withdrawn. It will also be observed that by reversing the parts *c* and *b* and swinging the handle to the opposite position from that shown in Fig. 1 then by placing the foot in the position shown in Fig. 1 the foot may be engaged with the chamfer of the staves and the hook engaged with the hoop. Then by throwing the lever upward the hoop may be removed. This use of the device is very convenient when working with large barrels or hogsheads and is illustrated in Fig. 4.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

1. The combination of a hand-lever, a hook mounted on one end thereof, a link pivotally mounted on the lever adjacent to the hook, and a foot carried adjustably on the link.

2. A barrel-opener, having a hand-lever, a hook mounted thereon, a link pivotally carried on the hand-lever adjacent to the hook, and a foot carried by the link and capable of being thrown in either one of two positions for the purpose specified.

3. A barrel-opener, comprising a hand-

lever, a hook mounted at one end thereof, a link pivotally mounted on the lever adjacent to the hook, a foot pivotally mounted on the link, and means for securing the foot fast on  
5 the link in the desired position.

4. A barrel-opener, comprising a hand-lever, a hook carried thereon, and a foot connected with the lever, the foot having a projecting ledge at one end and a returned flange  
10 adjacent thereto.

5. A barrel-opener, having a hand-lever, means thereon for engaging the hoops of a barrel, and a foot carried by the hand-lever and having a projected ledge at one end and  
15 a returned flange adjacent thereto.

6. A barrel-opener, comprising a hand-lever, means carried thereby to engage the hoops, and a foot carried by the hand-lever and capable of being thrown into either one of two positions, thus facilitating the use of  
20 the barrel-opener in connection with a barrel with or without a head.

In testimony whereof I have signed my name to this specification in the presence of two subscribing witnesses.

JOSEPH A. BERONIO.

Witnesses:

ANTONIO S. BAEBORO,  
TOM V. VIGUS.