

No. 670,945.

Patented Apr. 2, 1901.

J. L. ASH.

VAPORIZING DEVICE FOR GAS ENGINES.

(Application filed Nov. 4, 1899.)

(No Model.)





Fig. 1.



Witnesses.

H. Remison.

C. W. Adams.

Fig. 2.

Inventor.

J. L. Ash.

Frederickson & Co.
Attys.

UNITED STATES PATENT OFFICE.

JACOB LAGRANGE ASH, OF LANSING, MICHIGAN.

VAPORIZING DEVICE FOR GAS-ENGINES.

SPECIFICATION forming part of Letters Patent No. 670,945, dated April 2, 1901.

Application filed November 4, 1899. Serial No. 735,811. (No model.)

To all whom it may concern:

Be it known that I, JACOB LAGRANGE ASH, of the city of Lansing, in the county of Ingham, in the State of Michigan, have invented certain new and useful Improvements in Gas-Engines, of which the following is a specification.

My invention relates to improvements in gas-engines; and the object of the invention is to devise an improved means for insuring a perfect mixture of gasolene and air entering the explosion-chamber; and it consists, essentially, of a mixing-chamber formed in the body of the intake-valve and having the air-pipe leading from the base of the engine into the valve-body directly below the valve proper, a branch of the air-pipe extending up to the mixing-chamber, and a suitable reservoir for gasolene being provided at the top of the mixing-chamber, from which the gasolene is delivered in a small stream at the top of the chamber, and the parts being otherwise constructed and arranged in detail, as hereinafter more particularly explained.

Figure 1 is a perspective view of portion of a gasolene-engine to which my invention relates. Fig. 2 is a vertical section through the major portion of Fig. 1, parallel with the cylinder.

In the drawings like letters of reference indicate corresponding parts in each figure.

A is the cylinder of the gasolene-engine, and B the valve casing or body.

C is the passage-way above the valve, leading into the explosion-chamber at the end of the cylinder.

D is the valve, having a seat at *b* and provided with a stem *c*, extending through a spider *c'* in the orifice *C'*. The valve D is held on its seat by the spiral spring *d*, extending between the spider *c'* and the collar *d'* on the end of the valve-stem *c*.

E is the mixing-chamber, connected by the passage-way *e* to the space *D'*, immediately below the valve D.

F is the pipe for the admission of air, which is connected by a branch *F'* to the valve-chamber and a bent extension *F²* to the mixing-chamber intermediate of its length.

G is the drain-pipe for the mixing-chamber, which is designed to carry back to the tank all surplus gasolene.

H is a small gasolene-reservoir which is kept supplied with gasolene by a pump, the reservoir being connected to the mixing-chamber by a valve *h*, which is intended to deliver a small stream of gasolene at the top of the mixing-chamber, allowing it to fall down through the mixing-chamber to the bottom. At the time of suction in the engine part of the air will pass around through the bent portion *F²* of the pipe, and thence pass directly across the falling stream of gasolene from the reservoir H, which it vaporizes and carries with it enough gasolene to form a proper mixture. When the valve is opened by suction, this mixture passes through the passage-way C into the interior of the engine, where the explosion takes place.

I find in practice that the air passing through the mixing-chamber in the manner hereinbefore described and carrying with it gasolene serves to thoroughly vaporize it and forms a proper mixture suitable for the most efficient working of the engine.

What I claim as my invention is—

1. In combination, a cylinder, a casing, a passage leading to the cylinder, a valve controlling the same, a gasolene-supply, a mixing-chamber, air-passage leading directly across the mixing-chamber and a second air-passage leading through the casing and intersecting the passage from the mixing-chamber below the valve, substantially as described.

2. In combination, a cylinder, a casing, a passage leading to the cylinder, a valve controlling the same, a gasolene-supply, a mixing-chamber, air-passage leading directly across the mixing-chamber and a second air-passage leading through the casing and intersecting the passage from the mixing-chamber below the valve and a return-pipe leading from the mixing-chamber to the gasolene-supply, substantially as described.

JACOB LAGRANGE ASH.

Witnesses:

O. J. CLARK,
FRANK HINER.