

J. F. BUSCHMANN.

DEVICE FOR DECORATING CHRISTMAS TREES.

(Application filed Aug. 11, 1900.)





Witnesses Gelwood Bell F. W. Sterre Shuf. Buschmann Inventor By his Attorney Latelle

UNITED STATES PATENT OFFICE.

JOHN FRED BUSCHMANN, OF HATTIESBURG, MISSISSIPPI.

DEVICE FOR DECORATING CHRISTMAS TREES.

SPECIFICATION forming part of Letters Patent No. 674,956, dated May 28, 1901.

Application filed August 11, 1900. Serial No. 26,543. (No model.)

To all whom it may concern:

Beitknown that I, JOHN FRED BUSCHMANN, a citizen of the United States, residing at Hattiesburg, in the county of Perry and State 5 of Mississippi, have invented certain new and useful Improvements in Devices for Decorating Christmas Trees, of which the following is a full and complete specification, such as will enable those skilled in the art to which it ro appertains to make and use the same.

This invention relates to devices for decorating Christmas trees by connecting therewith or suspending therefrom toys, candles, fruits, and various other articles; and the ob-15 ject thereof is to provide an improved device of this class which is simple in construction and operation and comparatively inexpensive and which may be used for the purpose specified and for other and similar purposes; 20 and with this and other objects in view the described and claimed.

The invention is fully disclosed in the following specification, of which the accompa-25 nying drawings form a part, in which the separate parts of my improvement are designated by the same reference characters in each of the views, and in which-

Figure 1 is a view showing the construction 30 and operation of my improved device; Fig. 2, a bottom plan view of a detail thereof; Fig. 3, a cross-section of a candle-holder which I employ, and Figs. 4 and 5 are plan views of blanks from which the candle-holder is made.

In the drawings forming part of this specification I have shown at A a support which in the drawings represents a limb of a Christmas tree, and in the practice of my invention, as shown at the right of Fig. 1, I provide a 40 hanger B, preferably composed of wire and provided at its lower end with a hook b, with which is detachably connected a supplemental hanger C, having at its upper end a hook C² and provided at its lower end with a metal 45 disk D, loosely connected therewith and concavo-convex in form and provided around its perimeter with a plurality of spring-fingers d, which are lance-shaped in form and each of which is preferably provided near its end 50 with an inwardly-directed prong d^2 .

The disk D, with its spring-fingers d, is in-

tended to grasp and hold an orange E orany similar fruit, and it will be apparent that any other ornamental or gift device may be suspended in the same manner.

The upper portion of the hanger B is provided with a hook b^3 , from which projects an upwardly-directed extension b^4 , which, as shown in the drawings, supports a toy ship F, or the upwardly-directed extension b^4 of 60 the hanger B may be used to support a candle or any other device or toy.

It will be observed that the supplemental hanger C is detachably connected with the hanger B, and by means of the hook b³ the 65 hanger B may be suspended from a limb or any other article, and the fruit or other device connected with the supplemental hanger serves to hold the toy ship, candle, or other article in an upright position.

I have also shown at the left of Fig. 1 another invention consists in the device hereinafter | form of my invention in which I employ a hanger g, preferably composed of wire and provided near its upper end with a hook g^2 , by which it may be suspended from the limb 75 A or a branch thereof, and the hanger g is extended above the hook g^2 and connected with a candle-holder g^3 . The lower end of the hanger g is provided with a hook or open ring g^4 , and detachably connected therewith 80 is one of the disks D, which is also provided with fingers d and prongs d^2 , the same as hereinbefore described, and by means of which an orange or other fruit E may be suspended from the hanger g. The candle-holder 85 g^3 is composed of two blanks h and k, (shown in Figs. 4 and 5, respectively,) and the disk h constitutes the bottom of the candle-holder and is provided around its perimeter with Vshaped notches or recesses h2 and at the cen- 90 ter thereof with a rectangular depressed portion h^3 , the opposite sides of which are provided with pin-holes h^4 , and the blank k is oblong in form and provided with a central rectangular portion the ends of which are en- 95 larged, as shown at k^2 , by means of side pieces having beveled corners formed on said ends.

In forming the candle-holder the enlarged ends h^2 of the blank k are bent upwardly, as shown in Fig. 3, and the central portion there- 100 of is set into the depressed portion h^3 of the blank h, and pins k^3 are passed through the

pin-holes h^4 , so as to hold said parts together, and the perimeter of the blank h is bent upwardly, as shown at h^5 in Figs. 1 and 3. The blank k is also provided centrally thereof 5 with a prong k^6 , which is cut therefrom or formed integrally therewith and bent upwardly to form a prong which enters the lower end of the candle when the latter is placed in the holder. This device makes an effective 10 candle-holder which may be used for the purpose of decorating a Christmas tree or for other and similar purposes, and said device is simple in construction and operation and perfectly adapted to accomplish the result for 15 which it is intended, and it will be apparent that changes in and modifications of the construction described may be made without departing from the spirit of my invention or

Having fully described my invention, I

sacrificing its advantages.

claim as new and desire to secure by Letters Patent—

A device of the class described, comprising a main hanger b adapted to be suspended from a limb or other support, and provided 25 with an upwardly-directed extension adapted to support a candle or other article, the lower end of said hanger being provided with a detachable supplemental hanger c, and a disk d loosely connected therewith, and provided 30 with spring-fingers having inwardly-directed prongs, substantially as shown and described.

In testimony that I claim the foregoing as my invention I have signed my name in pres-

ence of the subscribing witnesses.

JOHN FRED BUSCHMANN.

Witnesses: W. C. BENNETT, T. E. BATSON.