


## A. L. MARINER. EYEGLASS CASE.


(Application filed May 3, 1901.)


(No Model.)











## United States Patent Office.

ABBOTT L. MARINER, OF MEDFORD, MASSACHUSETTS, ASSIGNOR TO LOUIS E. KIRSTEIN AND ABRAHAM ASHER, OF BOSTON, MASSACHUSETTS.

## EYEGLASS-CASE.

SPECIFICATION forming part of Letters Patent No. 677,785, dated July 2, 1901.

Application filed May 3, 1901. Serial No. 58,562. (No model.)

To all whom it may concern:

Be it known that I, Abbott L. Mariner, a citizen of the United States, residing at Medford, in the county of Middlesex and State of Massachusetts, have invented certain new and useful Improvements in Eyeglass-Cases, of which the following is a specification.

My invention relates to improvements in cases adapted to contain spectacles and eye10 glasses. These cases are ordinarily made of sheet metal covered on the exterior with leather and lined on the inside with velvet.

My present improvement relates to the spring-hinge by which the cover or flap of the case is secured to the body part. It is well known that by reason of the velvet lining and outside leather cover ordinary forms of hinge are not readily adaptable for use on eyeglass-cases; and the object of my invention is to provide a form of hinge which is free from exposed or projecting parts, which is capable of being neatly covered, and which shall act to hold the cover of the case both in the open and closed position.

In the accompanying drawings I have shown at Figure 1 in perspective an eyeglass or spectacle case of a well-known form or shape to which my present improvement is applied. At | Figs. 2 and 3 I have shown sections through 30 a hinged portion of the case represented by the dotted line 2 2 of Fig. 1, showing the relation of the parts when the cover is fully open or fully closed, and at Fig. 3 their relation when the cover is in an intermediate position. 35 At Figs. 4 and 5 I have shown transverse sections of the case and cover on the dotted lines 44 and 55, respectively, of Fig. 1, and at Figs. 6 and 7 I have shown in perspective and enlarged certain details of my improved hinge-40 joint, as will be hereinafter more fully de-

The cover A and the case B are provided at their meeting edges with tubular portions ab, preferably made integral with them and equal in diameter and bore. The said portions together form a tube adapted to receive a spiral spring C and hinge members D E. These hinge members (shown in detail and enlarged at Figs. 6 and 7) consist of pins preferably made of metal and approximately fitting the interior of the tube ab. I have shown and

prefer to employ two pairs of hinged members arranged as indicated at Figs. 2 and 3 that is to say, with a pair of hinged members at each end of the tube and the spiral spring 55 centrally disposed. The hinged members D E are respectively provided at their abutting ends with a wedge or double taper d and a corresponding double taper slot e to receive the same. One member of each hinge is 60 placed in that part of the tube attached to the cover and the other member in that part of the tube attached to the case, and each member of the hinge is prevented from turning in the tube, preferably by means of a fin or pro- 65 jection F, adapted to enter and interlock with a cut-away portion of the tube. This construction is illustrated at Figs. 4 and 5, where the pin D is shown in the first-named figure with its fin entering a recess in that part B of 70 the tube formed upon the case, while in Fig. 5 the pin E is shown with its projection entering a slot in the wall of the tube a, attached to the cover.

It will be understood that the spring C is 75 at all times under compression, its function being by reason of its resilience to crowd the two members of the hinge together longitudinally.

The operation of the device is as follows: 80 Assuming the article to be in the condition shown in Fig. 1, with the cover in the open position, the endwise thrust of the spring C forces the parts D and E together longitudinally, and the wedge-and-slot formation of 85 their ends holds the cover against turning unless sufficient pressure be applied to counteract the spring-pressure. If now it is desired to close the case, this is done by the hand in the ordinary manner, and while it is 90 being closed the parts of the hinge pass from the relation shown in Fig. 2 to that of Fig. 3, the wedge no longer lying in the slot, but by reason of its rotation, due to the closing of the case, having ridden up out of the slot and 95 bearing upon the extreme end of the walls thereof and at right angles to its former position. If now the movement of the case be continued in closing, the further rotation of the hinged members attached to the cover 100 will cause them to again assume a position where the wedge is free to enter the slot under the spring-pressure, this being the closed position shown in Fig. 4. It will further be understood that ordinarily the two members of the hinge come together, both in the open and closed position of the lid, with a slight snap, which has been found desirable in articles of this character.

I claim—

1. The improved case herein described, to comprising a tray having a cover hinged thereto, the adjacent portions of the tray and cover being provided with recesses containing hinge members having their abutting ends respectively provided with a wedge and a tapered slot and a spring arranged to force the said ends together.

2. In a case of the character described, the combination of a cover A and tray B, respectively provided with tubular portions a, b, and a coiled spring C, and hinge members 20 D, E, located in said tubular portions, the said members being provided with fins F, adapted to enter slots in said tubular portions, whereby the hinge members are prevented from turning in the tubular portions 25 when the cover is opened or closed.

In testimony whereof I have hereunto subscribed my name this 27th day of April, 1901.

ABBOTT L. MARINER.

Witnesses:

CHAS. C. KURTZ, ALEX. P. BROWNE.