

No. 688,052.

Patented Dec. 3, 1901.

H. D. ALLEN.
DESK LOCK.

(Application filed June 17, 1901.)

(No Model.)

Fig. 1




Fig. 2




Fig. 3





Fig. 4



Witnesses.
J. H. Thompson.
Lillian D. Kelley.

Howard D. Allen.
Inventor.
By *at* Seymour & Carey

UNITED STATES PATENT OFFICE.

HOWARD D. ALLEN, OF TERRYVILLE, CONNECTICUT, ASSIGNOR TO EAGLE LOCK CO., OF TERRYVILLE, CONNECTICUT, A CORPORATION.

DESK-LOCK.

SPECIFICATION forming part of Letters Patent No. 688,052, dated December 3, 1901.

Application filed June 17, 1901. Serial No. 64,776. (No model.)

To all whom it may concern:

Be it known that I, HOWARD D. ALLEN, of Terryville, in the county of Litchfield and State of Connecticut, have invented a new and
5 useful Improvement in Desk-Locks; and I do hereby declare the following, when taken in connection with the accompanying drawings and the numerals of reference marked thereon, to be a full, clear, and exact description of
10 the same, and which said drawings constitute part of this specification, and represent, in—

Figure 1, a view in front elevation of a lock constructed in accordance with my invention; Fig. 2, a view showing the application of the
15 lock to a desk, which is shown in section; Fig. 3, a broken view, in vertical section, showing the application of the detachable cylinder or key-guide to the lock-case; Fig. 4, a detached view, in side elevation, showing the de-
20 tachable cylinder or key-guide and its retaining-nut.

My invention relates to an improvement in that class of desk-locks provided with detachable cylinders or key-guides, the object being to produce a lock of this character which
25 shall at once be extremely simple and durable in construction and convenient to apply without marring the desk.

With these ends in view my invention consists in a desk-lock having certain details of construction, as will be hereinafter described, and pointed out in the claims.

In carrying out my invention I provide the lock with a detachable cylinder or key-guide
35 comprising a circular head 2, a hub 3, a shank 4, and a threaded stem 5, which forms its inner end, the said head, hub, shank, and threaded stem being formed with a longitudinally-arranged key-slot 6 and the said head
40 being provided with an annular cap 7. The said shank 4 corresponds in length to the thickness of the lock-case 8 and its cover 9, the said cover being formed with a circular opening 10 and the case with a corresponding
45 opening 11, registering with the opening 10. A nut 12, formed with a slot 13, is adapted to be applied to the threaded stem 5.

In applying my improved lock the desk 14 is provided with a mortise 15 for the reception of the lock and with two registering holes
50 16 and 17 for the reception of the hub 3 of

the cylinder or key-guide and the nut 12. After the lock has been introduced into the mortise 15 the cylinder or key-guide is inserted through the hole 16 and pushed inward
55 until its head 2 rests against the outer surface of the case, at which time the hub 3 will occupy the hole 16 and the shank 4 extend through the lock-case with the threaded stem
60 5 projecting into the hole 17. The nut 12 is now inserted into the hole 17 and applied to and screwed over the stem forming the inner end of the cylinder or key-guide until it is
65 brought to a bearing upon the outer face or back of the lock-case, as shown in Fig. 3. When the lock is thus assembled, the shoulder between the hub and shank will preferably bear against the cover of the case, while the
70 inner end of the nut will bear against the shoulder between the shank and threaded stem. To remove the lock, it is only necessary to apply a screw-driver to the nut and remove it from the threaded stem of the cylinder or key-guide, which may then be pulled
75 away from the lock-case, after which the same may be lifted out of its mortise.

My improved desk-lock, having a detachable key-guide or cylinder, is extremely simple and durable in construction and every way easy and convenient to apply and remove.
80

It is apparent that in carrying out my invention some changes may be made from the construction herein shown and described, and I would therefore have it understood that I do not limit myself to the precise details
85 shown, but hold myself at liberty to make such changes and alterations as fairly fall within the spirit and scope of my invention.

Having fully described my invention, what I claim as new, and desire to secure by Letters
90 Patent, is—

1. In a desk-lock, the combination with the lock-case, of a detachable cylinder or key-guide extending from front to back through the case with which it engages to prevent it
95 from longitudinal movement inward, and retaining means applied and attached to the inner end of the said cylinder or key-guide and bearing against the outer face or back of the case, whereby the said cylinder or key-
100 guide is held against longitudinal movement outward.

2. In a desk-lock, the combination with the lock proper, of a cylinder or key-guide comprising a head, a hub, a shank, and a threaded stem adapted to be passed through the case, 5 and a nut for application to the projecting threaded stem, whereby the cylinder or key-guide is held in place.

3. In a desk-lock, the combination with the case and cover thereof, the said parts being 10 formed with corresponding openings, of a cylinder or key-guide comprising a circular head, a hub, a shank, and a threaded stem, the shank of said cylinder or head being adapted to pass through the said openings, at 15 which time the hub and head will be on one

side of the lock-case and the threaded stem on the other side thereof, and a nut adapted to be applied to the said threaded stem for holding the cylinder in place in one direction while it is held in place in the opposite direc- 20 tion by the shoulder formed between the said hub and stem.

In testimony whereof I have signed this specification in the presence of two subscribing witnesses.

HOWARD D. ALLEN.

Witnesses:

R. J. PLUMB,
OTIS B. HOUGH.