


No. 688,365.

Patented Dec. 10, 1901.

H. D. THATCHER.
PAPER PAIL.

(Application filed Feb. 11, 1901.)

(No Model.)



Witnesses
Frank L. Ourand.
Albert Hopkins

Inventor
Hervey D. Thatcher
by Sturtevant & Greeley
Attorneys

UNITED STATES PATENT OFFICE.

HERVEY DEXTER THATCHER, OF POTSDAM, NEW YORK.

PAPER PAIL.

SPECIFICATION forming part of Letters Patent No. 688,365, dated December 10, 1901.

Application filed February 11, 1901. Serial No. 46,820. (No model.)

To all whom it may concern:

Be it known that I, HERVEY DEXTER THATCHER, a citizen of the United States, residing at Potsdam, in the county of St. Lawrence, State of New York, have invented certain new and useful Improvements in Paper Pails, of which the following is a description, reference being had to the accompanying drawings and to the letters of reference marked thereon.

My invention relates to improvements in paper pails of the kind for which I have heretofore been granted Patents No. 553,794, of January 28, 1896, and No. 619,099, of February 7, 1899, these pails being preferably made of paper or pasteboard and designed for holding butter, milk, lard, oysters, &c., and in general consisting of a pail in shape of the frustum of a cone, the bottom being formed by two circular disks the one smaller than the other, so that when forced downward the outer one will crimp at the rim of the inner disk, thereby giving a larger surface to be attached by adhesive material to the wall of the cylinder, being held in place by the wedging action of the cone and the adhesive character of the wax or other adhesive composition used.

The object of the present invention is to provide certain improvements in the manner of reinforcing the pail at its upper edge and in the manner of securing the top thereof in position.

The invention consists, primarily, of a pail of conical shape having at its upper end a reinforcing hoop or band which extends beyond the upper edge of the body of the pail, whereby said upper edge of the pail-body forms a rest or ledge for the top or cover, said reinforcing band or hoop being provided with ears or fasteners at the lower edge adapted to be bent under to engage the lower edge of the reinforcing band or hoop and at the upper end provided with portions adapted to be bent down to engage the band or hoop of the pail and also to hold the cover from displacement vertically, and also, if desirable, one of the prongs may be perforated for the reception of a bail.

Secondly, the invention consists in an ear for pails constructed as hereinafter set forth.

Finally, the invention consists in the mat-

ters hereinafter described and referred to in the appended claims.

In the accompanying drawings, which illustrate the invention, Figure 1 represents a perspective view of the receptacle; Fig. 2, a vertical section. Fig. 3 is a view of the blank which forms the reinforcing hoop or band, and Fig. 4 is a plan view of the blank from which the ear is made.

In the drawings, A represents the body of the pail, which is constructed in the manner described in connection with my former patent, No. 619,099, above referred to.

B represents the reinforcing strip or band, which is shown in Fig. 3 as formed of a narrow strip of material cut out in the shape shown in order that when its edges are secured together it will be in the shape of a narrow frustum of a cone, and this reinforcing strip or band B is secured upon the upper edge of the body of the pail A, with its upper edge projecting beyond the upper edge of the pail-body, so that the latter forms a ledge for the reception of the cover C.

D represents the ear or bail-blank, which, as shown in Fig. 4, is substantially triangular in shape, pointed at its lower end, and with its upper end split or die-cut to form four prongs, the outer of which prongs are lettered *a* and the inner ones *b* and *c*, respectively, the one, *c*, being perforated for the reception of a bail, if desired. This ear is applied by bending over the lower portion, as at *d*, to engage the lower edge of the reinforcing band or hoop B. The prongs *a* are then bent down to engage the upper edge of the reinforcing band or hoop, thus holding the ear in position. If desired, the other prongs *b* and *c* may be bent down to hold the cover in place, or only the prong *b* may be bent down for such purpose and the prong *c* be perforated to receive the end of the bail, as shown.

The reinforcing strip or band is secured to the body of the pail in any suitable manner, preferably by adhesive material; but it will be understood that it might be secured by the prongs on the ear, and the pail is made waterproof and grease-proof in any suitable manner.

Various minor modifications and changes in the details of construction of the device may be made without departing from the spirit of my invention.

Having thus described my invention, what I claim, and desire to secure by Letters Patent, is—

1. As an improved article of manufacture,
5 a paper vessel or pail consisting of a body, a reinforcing strip or band secured at the upper end thereof, its upper edge projecting above the upper edge of the pail or vessel, which thus forms a ledge or seat for a cover,
10 and an ear having prongs secured to the upper and lower edges of the reinforcing band or strip; substantially as described.

2. As an improved article of manufacture,
15 a paper vessel or pail consisting of a body, a reinforcing strip or band secured at the upper end thereof, its upper edge projecting above the upper edge of the pail or vessel, which thus forms a ledge or seat for a cover, and an ear having prongs engaging the upper
20 and lower edges of the reinforcing band or

strip and prongs engaging the cover to prevent displacement thereof; substantially as described.

3. The combination with a pail and a reinforcing band or strip, ears or fasteners split 25 or die-cut at the upper end, so as to furnish one or more prongs, whereby it may be attached to the band, one or more prongs adapted to be turned down to hold the cover in place, and one or more prongs to engage the 30 band at its lower extremity, whereby the ear may be held in place; substantially as described.

In testimony whereof I affix my signature in presence of two witnesses.

HERVEY DEXTER THATCHER.

Witnesses:

WM. NORMAN BARNHART,
JESSE CARLYLE FRENCH.