

No. 694,739.


Patented Mar. 4, 1902.

M. S. GOLDMAN.

CUFF HOLDER.

(Application filed Aug. 7, 1901.)

(No Model.)



WITNESSES.

J. R. Keller.
E. C. Potter.

INVENTOR.

By M. S. Goldman
A. C. Everitt
attys

UNITED STATES PATENT OFFICE.

MATTHEW S. GOLDMAN, OF PITTSBURG, PENNSYLVANIA.

CUFF-HOLDER.

SPECIFICATION forming part of Letters Patent No. 694,739, dated March 4, 1902.

Application filed August 7, 1901. Serial No. 71,225. (No model.)

To all whom it may concern:

Be it known that I, MATTHEW S. GOLDMAN, a citizen of the United States of America, residing at Pittsburg, in the county of Allegheny and State of Pennsylvania, have invented certain new and useful Improvements in Cuff-Holders, of which the following is a specification, reference being had therein to the accompanying drawings.

10 This invention relates to certain new and useful improvements in cuff-holders, and has for its object the provision of novel means whereby a cuff may be securely retained in any desired position.

15 The present invention aims to construct a cuff-holder that may be conveniently attached to the inner face of the sleeve; furthermore, to provide novel means that will allow a free and easy adjustment of the cuff to any desired position.

20 Another object of the present invention is to construct a cuff-holder of the above-described character that will be extremely simple in construction, strong, durable, and comparatively inexpensive to manufacture.

25 With the above and other objects in view the invention consists in the novel combination and arrangement of parts to be hereinafter more fully described, and specifically pointed out in the claims.

30 In describing the invention in detail reference is had to the accompanying drawings, forming a part of this specification, and wherein like numerals of reference indicate corresponding parts throughout the several views, in which—

35 Figure 1 is a vertical sectional view of a portion of a sleeve having my improved cuff-holder and cuff attached thereto. Fig. 2 is a perspective view of the cuff-holder. Fig. 3 is a longitudinal sectional view thereof. Fig. 4 is a perspective view of a modified form of my cuff-holder.

40 In these drawings the reference-numeral 1 indicates the coat-sleeve.

2 indicates the cuff.

3 indicates the guide, having openings 4 formed therein at each end thereof, forming suitable fastening means to attach the same to the inner face of the coat-sleeve.

50 The reference-numeral 5 indicates a sleeve which may be composed of metal, hard rub-

ber, fiber, or the like and is slidably arranged on the guide 3, this sleeve carrying a clamp 6. The said clamp is bent over upon itself 55 and carries a forwardly-extending tongue 7, the latter being slightly downwardly inclined.

In this form of construction the sleeve 5 is frictionally held on the guide 3, being fitted sufficiently tight thereon to be retained 60 against ordinary strain in any position to which it may be placed.

In the modification shown in Fig. 4 the numeral 8 indicates a loop formed of a corrugated wire, which may be employed in lieu of 65 the guide 3. The clamp 6, when this corrugated-wire loop is employed, is provided with grips 6' to engage the corrugated wire and hold the clamp thereon, the said clamp being held in the position to which it has been 70 moved by the corrugations in the wire.

The operation of my improved cuff-holder is as follows: The guide being attached to the interior face of the sleeve, as shown in Fig. 1, the end of the cuff is inserted in the clamp 6 75 and will be securely retained therein, the sleeve 5 sliding upon the guide 3, which will permit the cuff to be adjusted to any desired position. In the modified form the corrugations will form a suitable stop, which will 80 likewise serve to rigidly retain the cuff in a manner that an accidental displacement of the same will be impossible.

The many advantages obtained by the use of my improved cuff-holder will be readily 85 apparent from the foregoing description, taken in connection with the accompanying drawings.

It will be noted that various changes may be made in the details of construction without departing from the general spirit of my invention.

Having fully described my invention, what I claim as new, and desire to secure by Letters Patent, is— 95

1. In a cuff-holder adapted for attachment to the inner face of the coat-sleeve, and comprising a flat guide having its ends secured to the inner face of the coat-sleeve, a sleeve 100 slidably mounted on said guide and frictionally held in the position to which it has been moved, and a clamp carried by said sleeve for engagement with the cuff, said clamp having a portion thereof held within the sleeve

and the remaining portion bent over upon itself with the free end bent downwardly, substantially as described.

2. In a cuff-holder adapted for attachment
5 to the inner face of a coat-sleeve, a guide having its ends rigidly fastened to the inner face of the sleeve, and a clamp slidably mounted on said guide for engagement with the cuff,
10 the said clamp having a portion thereof engaging the slide and the remaining portion

doubled over upon itself and extended forwardly with its free end bent downwardly, substantially as described.

In testimony whereof I affix my signature in the presence of two witnesses.

MATTHEW S. GOLDMAN.

Witnesses:

JOHN NOLAND,
E. E. POTTER.