
J. B. RUSSEL. CARPET STRETCHER.

(Application filed Dec. 2, 1901.)




Jas.a. Martin H. J. Thomas

J. B. Russell H. Batel Attorney

J. B. RUSSEL. CARPET STRETCHER.

(Application filed Dec. 2, 1901.)

2 Sheets—Sheet 2.



WITNESSES

United States Patent Office.

JACOB B. RUSSEL, OF DELRAY, MICHIGAN.

CARPET-STRETCHER.

SPECIFICATION forming part of Letters Patent No. 695,495, dated March 18, 1902.

Application filed December 2, 1901. Serial No. 84,338. (No model.)

To all whom it may concern:

Be it known that I, JACOB B. RUSSEL, a citizen of the United States, residing at Delray, in the county of Wayne and State of 5 Michigan, have invented certain new and useful Improvements in Carpet-Stretchers; and I do declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which to it appertains to make and use the same, reference being had to the accompanying drawings, and to the letters of reference marked thereon, which form a part of this specification.

This invention has relation to improve-15 ments in carpet-stretchers; and it consists in the novel construction, combination, and arrangement of parts of which it is composed, all as will be hereinafter more fully explained, and particularly pointed out in the appended 20 claim.

The annexed drawings, to which reference is made, fully illustrate my invention, in which—

Figure 1 represents a side view of my im-25 proved carpet-stretcher. Fig. 2 is a plan view of the same. Fig. 3 is a vertical longitudinal sectional view. Fig. 4 is a transverse sectional view of the roller, and Fig. 5 is a detail view of the hand-lever.

Referring by letter to the accompanying drawings, A designates the carpet-stretcher, which comprises the roller a and a fulcrumed bar b, a frame c, a pawl d, and a hand-lever e. The roller a is provided with spurs f and 35 at each end with journals g, which have their bearing in the eyes h h on the inner end of the frame c, while the outer end of said frame has an eye i, through which passes the lower end of the bar b. This bar b is provided at 40 its lower end with a spur j, while the upper end serves as a handle for a purpose presently explained. Upon the lower portion of this bar b and arranged above the eye i of the frame is secured a collar k, to which the end l of the 45 pawl d is pivoted, while the opposite end of said pawl engages the ratchet-teeth m, that are centrally arranged upon the toothed roller. This roller in addition to the ratchetteeth has openings n, which are in line with 50 said teeth and alternate therewith, said openings being designed to receive one end of a detachable hand-lever e, whereby the roller is revolved.

The frame c is provided with a cross-bar o, that extends from one side of the frame 55 to the opposite side thereof and in front of the teeth upon the roller, the same serving to keep the carpet from the spurs and preventing it from following the roller. A guide loop or staple p is secured to the top of the 60 frame, through which the pawl freely passes, and held in position to properly engage the teeth on face of the toothed roller.

Having thus described the various parts of which my invention is composed, I will now 65

proceed and explain its operation.

In operating my device the roller is placed near the washboard of the house, and the teeth of said roller grasp the carpet, after which the spur j in the lower end of the bar 70 b is forced into the floor, and while the operator holds the handle-bar b with one of his hands he inserts the end of the lever in one of the openings n and forces the lever forward, thus revolving the roller, which by its 75 teeth draws the carpet and stretches it to be tacked to the floor, and at the same time the pawl engages one of the ratchet-teeth and prevents the roller turning backward and releasing its grip upon the carpet. It will thus 80 be seen that in using my device one person can readily and easily operate it, and it is simple in construction, quickly operated, and at the same time inexpensive to manufacture.

What I claim, and desire to secure by Let-

ters Patent, is—

The within-described carpet-stretcher, comprising the toothed roller a provided with the ratchet-teeth m and openings n arranged 90 midway between the opposite ends thereof, a frame c to which the roller is pivoted, a crossbar o having a guide p, secured to the frame, a pawl d and hand-lever b and e, said pawl being pivoted at one end to the lever b and 95 its free end passing through the guide p engaging the teeth m, the whole constructed and arranged as shown and described.

In testimony whereof I affix my signature in presence of two witnesses.

JACOB B. RUSSEL.

Witnesses: C. L. Coulson, JOHN R. BYER.