


No. 699,295.

Patented May 6, 1902.

T. F. DUNN.
NECKTIE.

(Application filed Jan. 10, 1902.)

(No Model.)



WITNESSES:

A. H. Conney.
A. K. Hood.

INVENTOR:
Thomas F. Dunn,
By his Atty.
Henry Williams.

UNITED STATES PATENT OFFICE.

THOMAS F. DUNN, OF BOSTON, MASSACHUSETTS.

NECKTIE.

SPECIFICATION forming part of Letters Patent No. 699,295, dated May 6, 1902.

Application filed January 10, 1902. Serial No. 89,186. (No model.)

To all whom it may concern:

Be it known that I, THOMAS F. DUNN, a citizen of the United States, residing in Boston, in the county of Suffolk and State of Massachusetts, have invented a new and useful Improvement in Neckties, of which the following is a specification.

This invention relates to that class of neckties which extend around the neck and hang down in front, and especially to the style of necktie commonly termed a "four-in-hand;" and the invention relates specifically to a combination, with a four-in-hand tie, of a detachable band of the character and construction below described.

With many persons tying a four-in-hand is somewhat difficult and occupies considerable time to learn and practice. Moreover, the process of tying necessitates twisting, folding, and wrinkling the material, especially when the knot is drawn tight and comparatively small, as is somewhat the mode at present, a small knot being practically necessary when a high turned-down collar is worn. The wrinkling of the tie necessitates frequent ironing, and the constant tying causes the article soon to become worn, and when the color is delicate daily handling in tying and untying quickly soils it. It is also found in practice that in case the fabric of which the tie is constructed has distinct figures—such as a flower, for example—it is difficult to so arrange the tie that the figure will appear centrally in the cross-fold. This difficulty practically prevents the working or stamping upon four-in-hand ties of monograms, society, and other symbols, &c. It is also apparent that an ornamental scarf-pin if worn must be removed every time the knot is untied.

In this improvement I provide an attachable and detachable band so constructed that the ends of the four-in-hand tie may be allowed to hang freely down from the throat without tying or knotting or even folding, and the band is applied in such a manner that it cannot fall or slip, said band presenting the general appearance of the cross-fold in a four-in-hand tie.

The nature of my invention is fully described in detail below and illustrated in the accompanying drawings, in which—

Figure 1 is a front view of my four-in-hand

tie in position for use. Fig. 2 is a front view of the band removed and spread apart. Fig. 3 is a rear view of the same. Fig. 4 is a top view of the band removed and closed. Fig. 5 is a section taken on line X, Fig. 3.

Similar letters of reference indicate corresponding parts.

A represents an ordinary four-in-hand tie or scarf.

My attachable and detachable band comprises a base B, of starched or stiffened fabric or other flexible or elastic material, an outer covering C, corresponding to a greater or less degree with the fabric of the tie itself, said portion C overlapping the rear side of the base A at C', and a cheap lining D, applied to the rear or inner surface of the band. The side edges of the band are flaring, so that the top of the band is wider than the bottom, and secured to the rear or inner side next said edges are strips of metal E and F, each of which is secured in position by its upper and lower ends overlapping at *e* the upper and lower edges of the band and its central portions being provided with a pointed projection *e'*, which extends through the band and clenches on the inner side. The projections *e'* and lips *e* are not, however, in sight, as they are not only on the inner surface of the band, but on the rear side thereof behind the tie when the band has been placed in position. The strip of metal E is formed with the substantially rectangular extension or plate H, provided with a plurality of vertical slots H', said plate or extension being formed at its upper and lower edges with serrations or teeth J J'. The strip F is centrally provided with the rearwardly extending or overlapping catch F'. The teeth J J' project inward at such a downward angle that the clasp of the band presses them into the body of the tie, preventing the band from sliding downward, but allowing it to be slid upward.

The band is applied by springing it around the two depending portions of the tie and catching the hook F' into one of the slots H', as in Figs. 1 and 4. The band is then pushed up into its proper position and is prevented from slipping down by the serrations or teeth J J'.

A symbol is shown in the drawings in order to illustrate the fact that any symbol or pin

once properly placed or set on the band always remains in its position, which is usually a central one.

5 The taper of the band may be varied as desired, and as many slots H' can be provided as are deemed necessary, so that the band may present the appearance of a smaller or larger knot, as is desired by the wearer.

10 It is evident that by the use of this band wrinkling is prevented, so that the shape and fresh appearance of the tie are retained for a considerable time, and as there is no knotting to shorten the tie when in use less material is required to make it. Different bands hav-
15 ing different monograms or symbols, such as are used by college students and in political campaigns, may be applied to the same tie.

Having thus fully described my invention, what I claim, and desire to secure by Letters
20 Patent, is—

1. In combination with a necktie of the character described, an attachable and detachable band adapted to be applied to the tie at the point where the knot is usually pro-
25 duced, laterally and when open, and to be secured around and encircle said tie by clasp- ing the opposite ends of said band together, and to be removed from said tie by unclasp- ing said ends, opening out the band and with-
30 drawing it laterally from the tie; and means for engaging the band with the tie by the act of clasping said ends whereby it may be pre- vented from dropping out of such position, substantially as described.

35 2. In combination with a necktie of the character described, an attachable and de-

tachable band adapted to be applied to the tie at the point where the knot is usually pro- duced, laterally and when open, and to be secured around and encircle said tie by clasp- 40 ing the opposite ends of said band together and to be removed from the tie by unclasp- ing said ends, opening out the band and with- drawing it laterally from the tie; metallic strips secured to the opposite ends of the band 45 substantially parallel with said ends; clasp- ing devices extending outward from said strips for engagement with each other when the band is closed; and means for engaging the band by the act of clasping its ends 50 whereby it is prevented from dropping out of its position around the tie, substantially as set forth.

3. In combination with a necktie of the character described, the band comprising a 55 base of relatively stiff material and a cover- ing of ornamental material; the strips E, F secured to the opposite edges of the band; the slotted extension H, H' provided with the teeth J, J' and extending from the strip E 60 beyond the edge of the band; and the hook F' extending from the strip F and adapted to engage the extension H by means of one of its slots H', substantially as described.

In testimony whereof I have signed my 65 name to this specification in the presence of two subscribing witnesses.

THOMAS F. DUNN.

Witnesses:

HENRY W. WILLIAMS,
A. N. BONNEY.