

No. 703,211.

Patented June 24, 1902.

D. F. MORGAN.  
HAND PROTECTOR.

(Application filed Apr. 14, 1902.)

(No Model.)

Fig. 1.




Fig. 2.





Fig. 3.



WITNESSES:

David C. Walter,  
Harvey Scribner.

INVENTOR.

Daniel F. Morgan  
By Owen Owen  
His attorneys.



# UNITED STATES PATENT OFFICE.

DANIEL F. MORGAN, OF TOLEDO, OHIO.

## HAND-PROTECTOR.

SPECIFICATION forming part of Letters Patent No. 703,211, dated June 24, 1902.

Application filed April 14, 1902. Serial No. 102,841. (No model.)

*To all whom it may concern:*

Be it known that I, DANIEL F. MORGAN, a citizen of the United States, residing at Toledo, in the county of Lucas, and in the State of Ohio, have invented certain new and useful Improvements in Hand-Protectors; and I do declare the following to be a full, clear, and exact description of the said invention, such as will enable others skilled in the art to which it appertains to make and use the same, reference being had to the accompanying drawings, and to the letters of reference marked thereon, which form a part of this specification.

My invention relates to improvements in that class of protectors for the hands as is used in warm or mild weather by motormen and other workmen whose employment exposes the palm portion of the hand and thumb to violent or hard usage, or may be worn over a glove or mitten in cold weather and which may also be used as a pad or glove by ball-players; and it consists of a single piece of leather or other suitable material having slits and holes cut therein for the insertion of the hand, thumb, and fingers.

My invention relates more particularly, however, to the peculiar formation of the blank thereof and the novel arrangement and cutting of the slits and holes therein, as will be hereinafter more fully set forth and specifically claimed.

The object of my invention is to provide a protection for the hands, and more particularly the palm portion thereof and that portion of the thumb exposed to hard usage, that will be absolutely devoid of seams and welts and not equipped with the usual straps and buckles for securing the same to the hand, which have heretofore been found necessary in that class of handwear, and that will be strong, durable, and easy and cheap of manufacture.

A further object of my invention is to provide a hand-protector that is admirably adapted to be used as a base-ball pad and which may also be used as a protector of the knuckles in bag-punching by reversing the mode of wearing the said pad, so as to have the main portion thereof cover the knuckles and the strap or band extend around the fore part of the wrist.

While the essential features of my invention are necessarily susceptible of modification, the preferred embodiment thereof is illustrated in the accompanying drawings, in which—

Figure I is a front perspective view of a hand with my protector thereon. Fig. II is a back perspective view of the same, and Fig. III is a plan view of the blank thereof.

In the drawings, A represents the blank of my improved protector, the sides of which taper slightly inwardly in their downward course, thus making the lower portion thereof of less diameter than the upper or wrist portion. The upper and lower portions of the blank are preferably formed with the slightly-convex edges 1 and 2. Near the upper edge of the blank A and in a line parallel therewith is provided the transverse and upwardly-curved slit or elongated slot *a*, which terminates on either side at points near the angles formed by the upper and side edges of the said blank, thus forming the strap or band *b* for retaining the same on the hand. If it is desired, the slit *a* may be shorter than the one shown in the drawings and may then be extended by the wearer as he may see fit to properly adjust the protector to his hand. To one side of the said blank and near the upper edge thereof is provided the vertically-disposed curved slit *c* for the insertion of the thumb, the said slit extending upwardly and inwardly and forms the tongue *c'* for the protection of the palm portion of the thumb.

Near the lower edge of my protector I provide the openings or apertures *d*, of various sizes, which are four in number and arranged in a slightly outwardly-curved line. I prefer these openings or apertures *d* when the protector is to be worn on the bare hand or over a glove; but if it is desired to wear the same over a mitten, as is often done by motormen or other persons exposed to the cold, the divisions between the said openings may be cut away on the dotted lines *x x*, thereby providing the blank with an elongated and slightly-curved slot to receive the hand with the mitten thereon, and also aids in forming the strap *e*, that extends over the knuckles.

In using my said protector the hand is inserted through the slit *a*, the thumb in the slit *c* and the fingers in the openings or aper-



tures *d* or the elongated slot, as the case may be, in such manner as to bring the straps *b* and *e* over the back of the hand. The peculiar cutting of the slit *a* and the slit *c* and their  
 5 correlative position to each other form the short strap or band *f*, which fits snugly around the heel of the thumb and prevents the downwardly-slipping tendency of the protector. It will therefore be readily seen that my in-  
 10 vention may be used to protect the hands of motormen, linemen, &c., or as a base-ball mit or pad, and, if desired, it may be padded to suit the purpose to which it is applied, or by reversing the mode of wearing the same it  
 15 may be used as a pad or protector of the knuckles in bag-punching.

Having thus described my invention, what I claim as new, and desire to protect by Letters Patent, is—

20 1. A hand-covering, comprising a single piece, and having near its upper edge a slit extending transversely thereof, near its inner and upper edges a slit at an angle to said transverse slit, and provided with a series of  
 25 apertures near its lower edge, substantially as described.

2. An article of manufacture comprising a single piece of leather or other material, said piece having an outwardly-curved transverse  
 30 slit near its upper edge and an outwardly-curved vertical slit near one end of said transverse slit and forming a tongue, and being provided with a series of openings of various

sizes near its lower edge, substantially as described.

35 3. A hand-covering comprising a single piece and being provided at its lower portion with a series of openings for the insertion of the fingers, and a slit in its upper outer portion for the insertion of the thumb, and hav-  
 40 ing its upper portion cut to form a strap in a single piece and integral with the said hand-covering at each end, substantially as described.

4. A protector for the palm portion of the  
 45 hand comprising a single piece of material having its lower and upper portions cut to form openings for the insertion of the hand, said cut portions forming straps, and having a slit near its inner and upper edges for the  
 50 insertion of the thumb, substantially as described.

5. A hand-covering comprising a single rectangular piece of leather or other material conforming to the shape of the palm portion  
 55 of the hand, said piece having the slots *a* and *c* cut therein and the openings *d* in its lower portion, one of said slots being cut to form the integral strap *b*.

In testimony whereof I have signed my  
 60 name to this specification in the presence of two subscribing witnesses.

DANIEL F. MORGAN.

Witnesses:

A. H. COLDHAM,  
 HARVEY SCRIBNER.