
S. T. NAKASHJIAN. CURTAIN FIXTURE.

(Application filed Apr. 12, 1901.)

(No Model.)



Witnesse., E.N. Barker. W. B. Nourse.

Inventor.,
Stephen T. Nakashjian

Sy St. H. Barker, Atty.

INITED - STATES - PATENT : OFFICE.

STEPHEN T. NAKASHJIAN, OF WORCESTER, MASSACHUSETTS.

CURTAIN-FIXTURE.

SPECIFICATION forming part of Letters Patent No. 704,205, dated July 8, 1902.

Application filed April 12, 1901. Serial No. 55,594. (No model.)

To all whom it may concern:

Beitknown that I, STEPHENT. NAKASHJIAN, of the city and county of Worcester and State of Massachusetts, have invented certain new 5 and useful Improvements in Curtain-Fixtures; and I do hereby declare that the following is a full, clear, and exact description thereof, reference being had to the accompanying drawings, forming a part of this speci-

to fication, and in which—

Figure 1 represents a front view of part of the upper portion of a window with my invention applied thereto, a curtain and its roller being also shown by dotted lines in said 15 figure. Figs. 2 and 3 are front views of the two parts of the fixture shown on the left and right hand sides, respectively, of the windowcasing shown in Fig. 1. Fig. 4 is a side view of the part shown in Fig. 2 looking in the di-20 rection of arrow a, and Fig. 5 is a side view of the part shown in Fig. 3 looking in the direction of arrow b.

The object of my invention is to provide a curtain-fixture whose brackets may be ad-25 justed to fit the curtains to different widths of windows, that may be manufactured cheaply,

and which may be easily applied.

Said invention consists in combining with each of said brackets two horizontal base-30 plates, one at each side of each bracket, extending at right angles therefrom in opposite directions and having longitudinal slots formed therein to receive set-screws for holding said brackets in place after adjustment, 35 as will be hereinafter more fully set forth.

To enable others to better understand the nature and purpose of my said invention, I will now proceed to describe it more in de-

tail.

In the drawings, A represents the windowcasing, and B B' the curtain-fixture, which may be attached to said window-casing by means of the screws C. The part B' of the fixture has a bracket c, provided with socket c'45 to receive the plain end of the shade-roller D, (see dotted lines,) and the part B has a bracket d, provided with a notch d' in its upper edge to receive the spring end of said shade-roller. Said socket c' projects laterally from the outer 50 end of the bracket c and is formed integral therewith by compression of the sheet metal between suitable dies. Each of said parts B |

and B' is provided with two horizontal baseplates e e, extending at right angles therefrom in opposite directions from said brack- 55 ets c and d, and in each plate is formed a longitudinal slot f, extending nearly the whole length thereof, the purpose of said slots being to receive the holding-screws C, which are passed through the same into the window- 60 casing or other support to hold the devices in place. By this construction it is obvious that the brackets may be securely fastened in position to said window-casing and also may be easily adjusted laterally by simply loosening 65 the screws, so as to permit them to be moved to one side, as desired, and then refastened after adjustment by tightening said screws up again.

The parts BB' are each made of a single 70 piece of sheet metal bent and compressed into the desired shapes, as is shown in Figs. 1 to

5, inclusive.

The essential feature of my invention consists in providing the brackets c d with the 75 right-angle oppositely-projecting base-plates e e, each having longitudinal slots to receive the set-screws C to admit of the lateral adjustment of the brackets and of fastening them after adjustment.

I am aware that adjustable fixtures are not new, and therefore limit my invention to substantially the construction described.

Having described said invention, what I claim as new, and desire to secure by Letters 85

Patent, is—

A curtain-fixture, comprising in combination the shade-roller, the supporting parts B B' at each end thereof and means for fastening said parts in position, the parts B B', each 90 consisting of a single piece of sheet metal cut, bent and compressed to form the brackets c, d provided respectively with the socket c' and notch d' at their outer ends, and of the horizontal longitudinally-slotted base-plates e e, 95 e e, one at each side of each bracket and projecting at right angles in opposite directions from the inner ends thereof, substantially as and for the purpose set forth.

STEPHEN T. NAKASHJIAN.

Witnesses:

A. A. BARKER, W. B. Nourse.