

No. 704,644.

C. E. HULTQUIST.  
CUFF HOLDER.

Patented July 15, 1902.

(Application filed Aug. 13, 1901.)

(No Model.)

Fig. 1.




Fig. 2.




Fig. 3.





Fig. 4.



Witnesses:

Frank Blanchard  
Mary Daly

Inventor:

Carl E. Hultquist.  
By L. L. Worriam,  
Attorney.



# UNITED STATES PATENT OFFICE.

CARL E. HULTQUIST, OF ROCKFORD, ILLINOIS.

## CUFF-HOLDER.

SPECIFICATION forming part of Letters Patent No. 704,644, dated July 15, 1902.

Application filed August 13, 1901. Serial No. 71,921. (No model.)

*To all whom it may concern:*

Be it known that I, CARL E. HULTQUIST, a citizen of the United States of America, residing at Rockford, in the county of Winnebago and State of Illinois, have invented certain new and useful Improvements in Cuff-Holders, of which the following is a specification.

The objects of my invention are, first, the production of a cuff-holder that will not abrade or wear the placket-facing of a shirt-sleeve, and, second, that will not become accidentally detached from a cuff with which it has been connected; and it consists of certain new and useful features of construction and combinations of parts especially devised to those ends, all as hereinafter fully described, and specifically pointed out in the claim.

Referring to the accompanying drawings, which form a part of this specification, Figure 1 is an isometrical view of a cuff-holder embodying my invention. Fig. 2 is a view showing the same operatively connecting a cuff with the placket-facing of a shirt-sleeve. Fig. 3 is a section at the line 3 3 in Fig. 2 of parts there shown. Fig. 4 is also a section at the line 4 4 in Fig. 2 of parts there shown.

Like letters of reference indicate corresponding parts throughout the several views.

A is the connecting-bar of the cuff-holder, which terminates at one end in a pintle A', integral therewith, and is provided at its remaining end with a T-shaped stud A<sup>2</sup>, projecting transversely therefrom, and a prolonged end shank A<sup>3</sup>, substantially parallel with the head of the T-shaped stud A<sup>2</sup>.

B B' are a pair of jaws pivoted together by means of the pintle A' on the connecting-bar A, passing through openings B<sup>2</sup> B<sup>3</sup> in the ears B<sup>4</sup> B<sup>5</sup> thereon.

C is a roller, preferably of rubber or other yielding substance, mounted on a pintle C' on the inside of the jaw B', supported by the ears C<sup>2</sup>, projecting therefrom.

D represents any suitable spring devices normally holding the jaw B into engagement with the roller C, mounted on the inside of

the jaw B'. Obviously a coiled spring or any other suitable form of spring might be substituted for the bent springs D, here shown as being integral with the jaws B B', without departing from the spirit and scope of my invention. I therefore do not intend by describing the springs D to thereby limit myself to a spring or springs of any particular form or construction.

The jaw B may have transverse serrations B<sup>6</sup> therein, if desired.

Fig. 2 shows the jaws B B' of the cuff-holder operatively applied to the placket-facing E of the shirt-sleeve E'. By grasping the upper end of the cuff E<sup>2</sup> between the thumb and fingers of the hand such cuff and its holder may be slid up or down, as desired, the roller C permitting the jaws B B' to travel back and forth along the facing E and lengthwise thereof without abrading or wearing the same to an injurious extent. The T-shaped stud A<sup>2</sup> and shank A<sup>3</sup> render it practically impossible for the connecting-bar A to become accidentally detached from the buttonholes E<sup>3</sup> E<sup>4</sup> in the cuff E<sup>2</sup>. If, however, either the top A<sup>4</sup> of the T-shaped stud A<sup>2</sup> or the shank A<sup>3</sup> were wanting, the cuff would be liable to become detached from the holder, or the buttonholes E<sup>3</sup> E<sup>4</sup> therein would slip over the point now occupied by the shank A<sup>3</sup> and permit the connecting-bar A to slide up and down therethrough.

What I claim as new, and desire to secure by Letters Patent, is—

In a cuff-holder, in combination, a pair of jaws pivoted together by a pintle, a roller, of rubber or other yielding material, mounted on the inside of one of said jaws and at right angles to said pintle, substantially as and for the purpose specified.

In testimony whereof I have signed my name to this specification in the presence of two subscribing witnesses.

CARL E. HULTQUIST.

Witnesses:

ERIC H. KJELLGREN,  
L. L. MORRISON.