No. 706,929.


B. N. GRIMSHAW. DISPLAY RACK.

(Application filed Feb. 6, 1902.)

Patented Aug. 12, 1902.

(No Model.)

2 Sheets—Sheet I.



B.N. Grimshaw

Witnesses

No. 706,929.


Patented Aug. 12, 1902.


B. N. GRIMSHAW. DISPLAY RACK.

(Application filed Feb. 6, 1902.)

(No Model.)

2 Sheets—Sheet 2.





Inventor

B.N. Grimshow,

By Allviceson te

Uttorneys

United States Patent Office.

BENJAMIN N. GRIMSHAW, OF PITTSFIELD, ILLINOIS.

DISPLAY-RACK.

SPECIFICATION forming part of Letters Patent No. 706,929, dated August 12, 1902.

Application filed February 6, 1902. Serial No. 92,834. (No model.)

To all whom it may concern:

Beit known that I, BENJAMIN N. GRIMSHAW, a citizen of the United States, residing at Pittsfield, in the county of Pike and State of Illinois, have invented certain new and useful Improvements in Display-Racks; and I do declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same.

The invention relates to display-racks, and more particularly to a device for displaying wall-paper in roll and also wall-paper bound

in book form.

The object of the invention is to provide a device of this character which shall be simple of construction, durable in use, comparatively inexpensive of production, and one which in use may be adjusted to various positions, whereby different shadows and lights may be thrown upon the paper and the prospective purchaser be given a better opportunity to make a selection.

With this and other objects in view the invention consists of certain novel features of construction, combination, and arrangement of parts, which will be hereinafter more fully described, and particularly pointed out in the

appended claims.

In the accompanying drawings, Figure 1 is a perspective view of my improved displayrack, showing the two shelves adjusted and one supporting the end of a roll of paper and the other supporting a book of samples. Fig. 2 is a longitudinal vertical sectional view through the same parts, the shelves being lowered in a position out of use. Fig. 3 is a detail perspective view of the combined bookholder and hinge.

Referring to the drawings, 1 denotes the supporting standard or pedestal, provided with a base 2 of suitable construction.

3 denotes a head in the form of a tray or receptacle swiveled to the upper end of the post

45 or pedestal and having side pieces 4.

of the tray or receptacle and connected to the upper edges of the side pieces thereof by hinges 6. One or more rolls of paper are adapted to be placed in the tray or receptacle 3 and the end unwound from the roll and spread upon the shelf 5 for display.

7 denotes a shelf hinged at 8 to the tray and consisting of two parts 9 and 10. The parts 9 and 10 are connected together by com- 55 bined book-supports and hinges 11, consisting of a U-shaped frame 12, into which the back of the book is adapted to be placed, the horizontal fixed portion 13, which is secured to the lower cross-piece of the section 9 of the 60 shelf, and the horizontally-disposed portion 14, which is hinged to the upper end of the vertical part 15 of the book-support and is provided at its outer end with a downwardly and inwardly curved stop 16, which when 65 the parts are in the position shown in Fig. 1 abuts against the part 15 of the support and holds the section 10 at an angle to the section 9, as shown in Fig. 1; but when the shelf 7 is lowered to the position shown in Fig. 2 70 the parts thereof are allowed to swing into alinement, and thus be out of the way and permit of compact storage or transportation. As many of these combined book-supports and hinges may be employed as may be de- 75 sired.

In displaying the bound samples the back of the book is placed in the support and opened, one cover resting upon the section 9 of the shelf, while the other cover rests upon 80 the section 10 of the shelf. The sample leaves of the book may now be turned in either direction and will be supported in such position as to be readily inspected by the prospective purchaser.

I will now describe the means for swinging

estal 1 and retaining the shelves in their adjusted position. These means comprise arms 17, which are the one pivoted to the section 90 9 of the shelf 7 and the other pivoted to the shelf 5. The inner ends of these arms are preferably bent or curved and are pivoted to friction-shoes 18, the inner faces of which are curved to partially surround the pedestal or 95 standard 1. Chains or cords 19 are connected at one end to lugs 20, cast on said chains, and extend up and over guide-pulleys 21, secured to the bottom of the tray or receptacle 3, and afford means for elevating said shoes, 100

and consequently swinging outwardly the shelves, which after having been swung outwardly will remain in their adjusted positions, as the weight of each will be imparted to its

friction-shoe through the medium of the arms 17, and thus frictionally hold said shaft to the post or pedestal 1. The shelves may be lowered by grasping the arms 17 at their lower

5 ends and pulling them downwardly.

From the foregoing description, taken in connection with the accompanying drawings, the construction, mode of operation, and advantages of the invention will be readily unco derstood without requiring an extended ex-

planation.

Various changes in the form, proportion, and details of construction may be made within the scope of the invention without de-15 parting from the spirit or sacrificing any of the advantages thereof.

Having thus described my invention, what I claim, and desire to secure by Letters Pat-

ent; is--

20 1. A display-rack comprising a post or pedestal, a head supported by the upper end of the post or pedestal, and a shelf consisting of two parts arranged at angles to each other, one part being pivoted to the head, and a 25 book-back-receiving frame for connecting the adjacent ends of the parts of the shelf together, substantially as set forth.

2. A display-rack comprising a post or pedestal, a head supported by the upper end of

the post or pedestal, and a shelf consisting of 30 two parts arranged at angles to each other, one part being pivoted to the head, a bookback-receiving frame for connecting the adjacent ends of the parts of the shelf together, and means for adjusting the shelf at various 35 angles with respect to the post or pedestal, substantially as set forth.

3. A display-rack comprising a post or pedestal, a head supported at the upper end of the post or pedestal, a shelf consisting of two 40 parts, one part hinged to the head, and combined book-supports and hinges, each consisting of a U-shaped frame having a lateral extension adapted to be secured to the inner part of the shelf, and a hinge extension adapt- 45 ed to be secured to the outer part of the shelf and provided with a stop adapted to abut

against the U-shaped frame and support the outer part of the shelf at an angle to the inner part, substantially as set forth.

In testimony whereof I have hereunto set my hand in presence of two subscribing witnesses.

BENJAMIN N. GRIMSHAW.

Witnesses:

A. H. COCHRAN, F. D. HELLER.