

No. 712,184.

Patented Oct. 28, 1902.


L. C. FELD.

NURSING BOTTLE HOLDER FOR BABY CARRIAGES.

(Application filed Mar. 27, 1902.)

(No Model.)

2 Sheets—Sheet 1.



WITNESSES

G. A. Stewart
F. L. Keller

INVENTOR

Louis C. Feld.

BY

Edgar Tate & Co
ATTORNEYS

ATTORNEYS

No. 712,184.

Patented Oct. 28, 1902.


L. C. FELD.

NURSING BOTTLE HOLDER FOR BABY CARRIAGES.

(Application filed Mar. 27, 1902.)

(No Model.)

2 Sheets—Sheet 2.



WITNESSES

F. A. Stewart
J. H. Keller

INVENTOR

Louis C. Feld.

BY

Edgar Tate & Co
ATTORNEYS

ATTORNEYS

UNITED STATES PATENT OFFICE.

LOUIS C. FELD, OF BROOKLYN, NEW YORK.

NURSING-BOTTLE HOLDER FOR BABY-CARRIAGES.

SPECIFICATION forming part of Letters Patent No. 712,184, dated October 28, 1902.

Application filed March 27, 1902. Serial No. 100,172. (No model.)

To all whom it may concern:

Be it known that I, LOUIS C. FELD, a citizen of the United States, residing at Brooklyn, in the county of Kings and State of New York, have invented certain new and useful Improvements in Nursing-Bottle Holders for Baby-Carriages, of which the following is a full and complete specification, such as will enable those skilled in the art to which it ap-
10 pertains to make and use the same.

The object of this invention is to provide an improved device for connecting a nursing-bottle with a baby-carriage and for holding the same in proper position for use; and with
15 this and other objects in view the invention consists in a device or devices of the class specified constructed as hereinafter described and claimed.

The invention is fully disclosed in the following specification, of which the accompanying drawings form a part, in which the separate parts of my improvement are designated by the same reference characters in each of the views, and in which—

25 Figure 1 is a perspective view of a baby-carriage provided with my improvement, and Fig. 2 a perspective view of the operative parts of the device which I employ on an enlarged scale.

30 In the drawings forming part of this specification I have shown an ordinary baby-carriage, the body a of which is provided with side portions a^2 , which are preferably in the form of rolls or scrolls, and the front or dash-
35 board portion of which is also preferably provided with a similar roll or scroll a^3 ; but the baby-carriage and the body portion thereof may be of any preferred form and construction.

40 In the practice of my invention I provide a device or devices of the class specified comprising two upright spring-arm portions b , which in the form of construction shown are provided at their lower ends with spring-
45 hooks b^3 , adapted to engage and rest upon the sides a^2 of the body of the carriage, and a forward spring-arm portion c , provided with a similar spring-hook c^2 , adapted to engage the top portion of the dashboard of the body of
50 the baby-carriage, and the side arms b are curved inwardly and downwardly at their upper ends to form downwardly-directed sup-

plemental arms b^3 , and said side arms may be composed of a single wire, as shown in Fig. 1, or of double wires, as shown in Fig. 2, 55 and connected with the lower ends of the supplemental arms b^3 is a cross-head d , and the supplemental arms b^3 are passed through said cross-head and held therein by set-screws d^2 or in any other desired manner. 60

The front spring-arm c is provided with a supplemental member 2^c , which is rigidly connected at one end with a block e , through which the main part c of said arm passes, and the main part c of said supplemental arm is 65 provided at its rear end with a loop or ring c^3 , through which the supplemental part 2^c loosely passes, and the supplemental part 2^c of said arm is rigidly secured to the cross-head d . 70

The bottle-holder proper comprises an oblong or elliptical loop-shaped portion f , with the bottom portion of which is connected an arm g , which is free to turn thereon at g^2 , and this arm is loosely connected at g^3 with a ring 75 g^4 , with the upper side of which is loosely connected an arm g^5 , composed of two parts, which are bent around the top portion of the member f at g^6 and carried backwardly and formed into a loop g^7 , through which the main 80 part of the arm g^5 passes, and rigidly connected with the loop-shaped or elliptical member f , centrally of the top portion thereof, is a rod or other device h , which passes upwardly through the cross-head d and may be ver- 85 tically adjusted therein by means of a set-screw or similar device h^2 .

The elliptical or loop-shaped portion or member f of the bottle-holder is designed to receive or hold the body portion of the bot- 90 tle, as shown in Fig. 1, while the ring or supplemental part g^4 is designed to receive and hold the neck of the bottle, and in Fig. 1 of the drawings I have shown a bottle thus supported, and the form and dimensions of the 95 various parts of the device and the adjustable features thereof are such that the bottle may be suspended in proper relative position for use at all times.

The supplemental part g^4 of the bottle- 100 holder and the parts connected therewith are adapted to be folded upwardly, as shown in dotted lines in Fig. 2, and the entire device may be detached from the body of the baby-

carriage and connected therewith whenever desired, and by means of the construction of the forwardly-directed spring-arm *c* and the supplemental part 2° thereof the latter may
5 be adjusted longitudinally, while the construction of the members *b*³ and the cross-head *d* and the connections thereof are such that said members will turn in said cross-head and may be disconnected therefrom
10 whenever desired, and the entire device may be thus compactly folded together or the parts thereof may be separated and compactly stored whenever desired.

Having fully described my invention, what
15 I claim as new, and desire to secure by Letters Patent, is—

In a device of the class described, a loop-shaped or elliptical member, a ring supported in front thereof and adapted to connect there-
20 with so as to swing vertically, an upwardly-directed member connected with the loop-

shaped or elliptical member, a support with which said upwardly-directed member is adjustably connected, and means for connecting said support with the body of the baby- 25 carriage, and holding the same thereover, consisting of spring side arms adapted to engage the sides of the body of the carriage, and a forwardly-directed spring-arm, adapted to engage the front of the body of the carriage, 30 the latter arm being composed of two parts, one of which is adjustable upon the other, substantially as shown and described.

In testimony that I claim the foregoing as my invention I have signed my name, in pres- 35 ence of the subscribing witnesses, this 24th day of March, 1902.

LOUIS C. FELD.

Witnesses:

F. A. STEWART,
F. F. TELLER.