

W. S. RHODES & W. J. TRUMP. COMBINED SIDESTICK AND QUOIN. APPLICATION FILED MAR. 8, 1902.

NO MODEL.





Jos. a Ryan Amostr Harr William S. Rhodes
William J. Trump

BY

Muma

United States Patent Office.

WILLIAM SAMUEL RHODES AND WILLIAM JACKSON TRUMP, OF LINCOLN, NEBRASKA.

COMBINED SIDESTICK AND QUOIN.

SPECIFICATION forming part of Letters Patent No. 722,753, dated March 17, 1903. Application filed March 8, 1902. Serial No. 97,308. (No model.)

To all whom it may concern:

Be it known that we, WILLIAM SAMUEL RHODES and WILLIAM JACKSON TRUMP, citizens of the United States, residing at Lincoln, 5 in the county of Lancaster and State of Nebraska, have made certain new and useful Improvements in a Combined Sidestick and Quoin, of which the following is a specification.

It is the object of our invention to provide an improvement in that class of printers' furniture employed for locking up forms and which comprise a sidestick or foot-stick and quoins or wedges that are adjustable thereon.

We have devised an improved construction, arrangement, and combination of parts, whereby certain advantages are attained, as hereinafter set forth.

In the accompanying drawings, Figure 1 is 20 mainly a plan view of our invention, portions of the quoins being broken away and a portion of a chase and form being indicated in dotted lines. Fig. 2 is a perspective view of our improved sidestick. Fig. 3 is a cross-

25 section on the line 3 3 of Fig. 1.

The sidestick A, which may be also a footstick, has the usual straight edge and on the opposite side two reversed inclines a a and at a central point two lateral projections B, 30 which are parallel and arranged at right angles to the longitudinal axis. These projections B are in the nature of short flat bars or plates formed integrally with the body of the sidestick A and provided with an open slot 35 2, having parallel sides and extending outward from the sidestick proper. The said projections are separated, as required, to receive between them a collar C, (see Fig. 1,) which is formed integrally with two cylin-40 drical and alined screws C'. These screws are threaded in opposite directions and are rigidly connected with the collar C, being preferably constructed integrally therewith. The quoins or wedges D, which are adapted 45 to work on the reversed inclines a of the sidestick A, are provided at their inner and wider ends with threaded sockets adapted to receive the said screws C'. As seen in side view, the quoins D have practically the form 50 of right-angled triangles, their outer sides being parallel to the same plane, while their inner ones are parallel to the inclines of the side-

stick. It is apparent that when the parts are in the position shown in Fig. 1 if the collar C be rotated the quoins D will be forced far- 55 ther apart or brought nearer each other, as the case may be, and that thereby the device will be adjusted as required for locking up the form X in the chase Y. For the purpose of rotating the collar C and screw C' the 60 former is provided with a series of peripheral sockets adapted to receive a suitable lever Z.

(Indicated by dotted lines.)

It will be noted that the collar C is of such length as to fit easily between the guides B, 65 so that there is no movement of the adjusting devices C and C' longitudinally, while it is free to be removed or inserted by reason of the slots 2 being open at their outer ends. Thus the parts B not only serve to hold the ad- 70 justing device in due position both as to longitudinal and lateral movement, but they enable the quoin attachment as a whole to be readily applied and detached. The parts A, C, C', and D may therefore be readily put together or 75 taken apart, and larger or smaller quoins may be readily substituted should occasion require—as, for example, when the form is unusually small. Our device thus constitutes an improved means for locking up forms quickly 80 and securely.

Having thus described our invention, what we claim as new, and desire to secure by Let-

ters Patent, is—

The improved article of printers' furniture 85 herein described consisting of the sidestick having its inner side provided with reversed inclines and provided at the inner ends of said inclines with the projecting lugs provided in their free ends with the longitudinal 90 slots formed between the upper and lower edges of the said lugs, the adjusting-shaft projecting at its ends through said slots and provided at its middle with the collar fitting and operating between said lugs, and the 95 quoins having inclined faces operating along those of the sidesticks and engaged by the ends of the screw-shaft.

> WILLIAM SAMUEL RHODES. WILLIAM JACKSON TRUMP.

Witnesses:

CLAUDE S. WILSON, W. K. WILLIAMS.