
### S. SHICK.

## FURNITURE DRAWER.

APPLICATION FILED OCT. 30, 1902.

NO MODEL



# United States Patent Office.

# STEWARD SHICK, OF CLEARFIELD, PENNSYLVANIA.

#### FURNITURE-DRAWER.

SPECIFICATION forming part of Letters Patent No. 723,050, dated March 17, 1903.

Application filed October 30, 1902. Serial No. 129,426. (No model.)

To all whom it may concern:

Be it known that I, STEWARD SHICK, a citizen of the United States, residing at Clearfield, in the county of Clearfield and State of 5 Pennsylvania, have invented certain new and useful Improvements in Furniture-Drawers; and I do declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to 10 which it appertains to make and use the same.

The invention relates to secret drawers for furniture, such as desks, bureaus, cabinets, or, in fact, any article of furniture with which

a drawer may be employed.

The object of the invention is to provide a drawer of this character which shall be simple of construction, durable in use, comparatively inexpensive of production, and adapted to contain valuables designed to be hidden 20 or concealed from view, and thus furnish a safe repository.

With these and other objects in view the invention consists of certain novel features of construction, combination, and arrangement 25 of parts, as will be more fully described, and | particularly pointed out in the appended

claim.

In the accompanying drawings, Figure 1 is a vertical sectional view through a piece of 30 furniture and a bank of drawers, one of which is constructed in accordance with my invention. Fig. 2 is a longitudinal vertical sectional view through my improved drawer. Fig. 3 is a cross-sectional view therethrough. 35 Fig. 4 is a rear view of the drawer, portions being broken away to more clearly illustrate the spring-catch.

In the drawings, 1 denotes a piece of furniture, and 2 my improved drawer. The 40 drawer is composed of the front piece 3, the end pieces 4, the back piece 5, and the bottom 6. The bottom 6 is supported upon ledges 7 of the end pieces, a distance from the lower edges of said end pieces, and has 45 its forward edge projecting into a groove 8, formed in the rear face of the front piece.

9 denotes drawer-slides secured to the innersides of the end pieces at their lower edges.

10 denotes a supplemental drawer, which is 50 adapted to engage said slides and be supported under the bottom 6 of the drawer proper and is provided with a back piece 11, which in design and finish corresponds to the back piece 5.

A spring-catch 12 is secured at one end to |

the lower edge of the back piece 11 and lies throughout its entire length in a groove 13, whereby the same is concealed from view except when the drawer is inverted. The free end of the catch projects upwardly through a 60 hole 14, formed in the back piece 11, and engages a keeper-socket 15, formed in the lower

edge of the back piece 5.

From the foregoing description, taken in connection with the accompanying drawings, 65 the construction, operation, and advantages of the invention will be readily understood without requiring an extended explanation. It is evident that valuables placed within the supplemental drawer are concealed from view 70 when the drawer proper is withdrawn from the piece of furniture, and no evidence of the supplemental drawer will appear unless the drawer proper is inverted or turned upside down.

Various changes in the form, proportion, and the minor details of construction may be resorted to without departing from the principle or sacrificing any of the advantages of this invention.

Having thus described my invention, what I claim as new, and desire to secure by Letters Patent, is—

The combination with a drawer proper, the front and ends of which project below the 85 bottom of the drawer and the back of which has its lower edge in a plane above the plane of the lower edges of the front and ends of the drawer, said back having a keeper-socket, of a supplemental drawer opening from the 90 rear and provided with a back piece, which fits between the end pieces and is flush with the back piece of the drawer proper and formed along its lower edge with a longitudinal groove intersected by a vertical aper- 95 ture which is adapted, when the supplemental drawer is closed, to aline with the keepersocket, and an angular spring-catch, one end of which is fastened in the groove and the other end of which projects through the ap- 100 erture and is adapted to engage the keepersocket when the supplemental drawer is in

closed position, substantially as described. In testimony whereof I have hereunto set my hand in presence of two subscribing wit- 105 nesses.

STEWARD SHICK.

Witnesses:

BENJ. G. COWL, J. A. WILLSON.