
A. HART.

BRUSH.

APPLICATION FILED OCT. 31, 1902.

NO MODEL.



United States Patent Office.

ALBERT HART, OF PHILADELPHIA, PENNSYLVANIA, ASSIGNOR OF ONE-HALF TO SMITH, KLINE & FRENCH COMPANY, A CORPORATION OF PENNSYLVANIA.

BRUSH.

SPECIFICATION forming part of Letters Patent No. 723,462, dated March 24, 1903.

Application filed October 31, 1902. Serial No. 129,574. (No model.)

To all whom it may concern:

Be it known that I, Albert Hart, a subject of the King of Great Britain, (but having declared my intention of becoming a citizen of the United States,) residing in the city and county of Philadelphia and State of Pennsylvania, have invented certain new and useful Improvements in Brushes, of which the following is a specification, reference being had to the accompanying drawings.

My invention relates to a brush, of which the brushing material consists of a mass of rubber sponge with two brushing-surfaces on opposite sides, removably united to a handle

15 by means of a containing-band.

In the accompanying drawings, Figure 1 is a view of a brush illustrating my invention. Fig. 2 is a plan view of the mass of rubber sponge removed from the handle. Fig. 3 is a similar view of the containing-band with a portion of the handle, and Fig. 4 is a detailed view showing the locking device of said band.

The body of the brush is formed of a single mass of rubber sponge A of the desired shape, 25 which is preferably that shown, having two opposite brushing-surfaces a a somewhat flattened and having a rounded edge b of regular contour—as, for instance, the elliptical shape indicated in the drawings. The other 30 portion of the brush consists of a handle D, having attached to it or preferably formed integrally with it a two-part containing-band dd', whose periphery is substantially similar to but smaller than the edge contour of the 35 mass of rubber sponge. The handle D, with its band d d', may conveniently be made of aluminium. The two parts of the band are hinged together at e and the other ends are provided with a securing device, (shown in 40 Fig. 4,) whereby they may be held together in such manner as to be locked by the elasticity of the contained mass of sponge. This locking device is formed by means of notches g g',

located near the ends of the parts d d', portions of said notches being undercut, so as to form a pair of corresponding dovetailed catches f f', which engage snugly with one another. The total length of the notches as compared with the length of the dovetailed portions is such that the catches may be

moved longitudinally apart to a distance which permits their disengagement from one another by lateral movement.

In use the parts dd' are opened, the rubber sponge is inserted within their embrace, and 55 they are then closed and locked by means of the catches f f' in such way as to leave a brushing-surface exposed upon either side of the band. By reason of the peculiar consistency and structure of the rubber sponge 60 when thus confined it will not be displaced by ordinary usage, being held in position by its own elasticity, and it also firmly locks the catches in engagement, so as to prevent the containing-band from opening. It can, how- 65 ever, at any time be taken out and replaced by pushing the catches longitudinally apart and then separating them laterally to permit the opening of the band.

The stability of the rubber sponge within 70 its containing-band is increased by making a slight variation at one or more points between the configuration of the rubber sponge and that of the closed band. Thus it will be observed in the drawings that although in 75 general outline the two correspond, yet the elongated sides of the rubber sponge are continuously rounded, while the corresponding sides of the band are flattened, thus producing an increased pressure at these two opposite points.

The brush thus produced has two brushing-surfaces of equal utility. It is light and durable. Its cleanliness is obvious, as it consists of separable parts, each of which can be 85 thoroughly and readily cleaned. Whenever the rubber sponge has been worn out, it may be replaced by another inserted in the same handle.

Having thus described my invention, I 90 claim—

1. A brush-handle provided with a holder in the form of a divided band; the meeting ends of which are overlapped one upon the other, and provided upon their overlapped 95 faces with interlocking undercut projections.

2. A brush comprising a handle, a bandlike holder comprising a rigid section and a hinged section; the free ends of the hinged section and the adjacent end of the fixed sec-

tion being overlapped and there provided with interlocking undercut catches, and a brush-body formed of a mass of elastic material compressed within the holder, and holding it locked by the expansive force of the material.

In witness whereof I have hereunto signed !

my name in the presence of two subscribing witnesses.

ALBERT HART.

Witnesses:

JAMES H. BELL, M. KATIE TRUMBORE.