

No. 736,458.

PATENTED AUG. 18, 1903.

T. L. & T. J. STURTEVANT.

PITMAN.

APPLICATION FILED MAY 28, 1903.

NO MODEL.

Fig. 1.




Fig. 2.





Fig. 3.



Witnesses.
Robert E. Pratt,
Attest.

Inventors.
Thomas L. Sturtevant
Thomas J. Sturtevant
by *Wm. L. Laver* *Att'y.*

UNITED STATES PATENT OFFICE.

THOMAS L. STURTEVANT, OF QUINCY, AND THOMAS J. STURTEVANT, OF
WELLESLEY, MASSACHUSETTS.

PITMAN.

SPECIFICATION forming part of Letters Patent No. 736,458, dated August 18, 1903.

Application filed May 28, 1903. Serial No. 159,144. (No model.)

To all whom it may concern:

Be it known that we, THOMAS L. STURTEVANT, residing at Quincy, and THOMAS J. STURTEVANT, residing at Wellesley, in the
5 county of Norfolk and State of Massachusetts, citizens of the United States, have invented certain new and useful Improvements in Pitmen, of which the following is a specification, reference being had therein to the accompa-
10 nying drawings.

This invention relates to pitmen and pitmen connections of such construction that they may be attached to a crank or detached therefrom in such a manner that the parts
15 may be readily assembled or dismounted the construction of the parts being such that wear on the pitmen-head bearing parts may be readily compensated for, and, furthermore, such that free and independent rocking
20 movements of the pitmen-head on the crank-pin during the stroke of the crank will not be interfered with.

In the accompanying drawings, Figures 1 and 2 are central sectional views at right angles to each other, illustrating the improved
25 pitmen in assembled condition and in operative relation to a crank-pin; and Fig. 3 is a view showing the several parts disconnected from each other.

Referring to the drawings, 12 denotes the body portions of the pitmen, which are of a wide beam-shaped form and are provided with segmental or forked portions or heads 13,
30 adapted to bear against opposite sides of a crank-pin, as 14, carried by any suitable crank-arm or web, and the body portions of the pitmen are provided, adjacent to said segmental bearing portions 13, with apertures or openings
35 16 for the reception of lugs or parts 17 of a strap 18 of proper size to embrace or encircle the segmental portions 13 of the pitmen in the assembled condition of the parts, the said strap being preferably formed in two parts secured together by screws or screw-bolts 19 or other fastening devices passing through said lugs 17
40 and clamping the pitmen-head 13 upon the crank-pin 14. An open strap formed in one piece may, however, be employed, if desired, and in such case the strap will be of elastic
45 metal, as brass, adapted to be opened sufficiently to be sprung over the crank-pin. The segmental bearing portions 13 of the pitmen are preferably of less than a semicircle in ex-

tent, so that they do not collectively completely surround the crank-pin 14, but clearances are
55 left between said segmental portions 13, so as to provide not only for adjustment of the parts to compensate for wear by tightening the screw-bolts 19, but also to allow sufficient room for independent rocking movements of
60 the pitmen upon the crank-pin during the strokes of the crank.

It will be understood that the construction above described provides pitmen and pitmen connections the parts of which can be readily
65 assembled or dismounted, in which independent movements of the pitmen-heads are not interfered with, and in which wear can readily be compensated for by tightening the screw bolt or bolts holding the encircling strap to-
70 gether.

Having thus described our invention, we claim and desire to secure by Letters Patent—

1. The combination with two pitmen each of which is provided with a segmental bearing portion and with an opening adjacent thereto, of a strap encircling the said segmental bearing portions of said pitmen and extending into the openings adjacent thereto, and means for securing the said strap to-
75 gether. 80

2. The combination with two pitmen each of which is provided with a segmental bearing portion of less than a semicircle in extent, and with an opening adjacent to said segmental bearing portion, of a strap encircling the said segmental bearing portions of said pitmen and extending into said openings, and a screw or bolt for securing the said strap to-
85 gether. 90

3. The combination with two pitmen each of which is provided with a segmental bearing portion of less than a semicircle in extent, and with an opening adjacent to said bearing portion, of a two-part strap encircling the said
95 segmental bearing portions of said pitmen and extending into said openings, and screws or bolts for securing the two parts of said strap together.

In testimony whereof we affix our signatures
100 in presence of two witnesses.

THOMAS L. STURTEVANT.

THOMAS J. STURTEVANT.

Witnesses:

HENRY CALVER,

J. D. KLINGE.