

No. 738,063.

PATENTED SEPT. 1, 1903.

R. C. POOL.

BUCKLE.

APPLICATION FILED AUG. 7, 1902.

NO MODEL.

Fig. 1.




Fig. 2.




Fig. 3.





Fig. 4.



Witnesses

C. H. Walters.
J. W. Moore.

Inventor

Robert C. Pool

James H. Bevan

Attorney

UNITED STATES PATENT OFFICE.

ROBERT C. POOL, OF LINDALE, TEXAS.

BUCKLE.

SPECIFICATION forming part of Letters Patent No. 738,063, dated September 1, 1903.

Application filed August 7, 1902. Serial No. 118,764. (No model.)

To all whom it may concern:

Be it known that I, ROBERT C. POOL, a citizen of the United States, residing at Lindale, in the county of Smith and State of Texas, have invented certain new and useful Improvements in Buckles; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same.

This invention relates to improvements in buckles; and the object is to provide a simple and convenient construction of buckle which may be quickly and readily attached to or detached from the straps and which will permit of the ready and rapid adjustment of the straps and at the same time will positively hold the same in their adjusted positions.

With the above object in view the invention consists in the novel features of construction hereinafter fully described, particularly pointed out in the claims, and clearly illustrated by the accompanying drawings, in which—

Figure 1 is a plan view of a buckle in connection with two straps; Fig. 2, a longitudinal sectional view of the same; Fig. 3, a perspective view of one of the members detached from the strap, and Fig. 4 a similar view of the other member.

Referring now more particularly to the accompanying drawings, 1 designates the base member, comprising a plate having a transversely-extending slot 2 near one end to receive the strap 3, which passes loosely there-through and having its opposite end bent at right angles thereto and then to extend substantially parallel therewith, forming a recess or groove 4.

5 designates the movable clamping member, comprising a plate having parallel transversely-extending slots 6 6, through which the strap 3 is passed. The two members are thus movably held together by the strap 3, which is attached to member 5 by being passed through the slots 6 6, as stated, said strap being then passed through slot 2 of member 1. Member 5 is positioned upon the face of

member 1, having the recess thereon, and the end edge of member 5, which is provided with serrations or teeth 7, is adapted to extend into this recess when in clamping position, as illustrated in Fig. 2. Said member 1 may be termed a "hook" member, as the bending of the end thereof to form a recess forms what may be termed a "hook" 9, in which the strap 4 is clamped by the serrated edge of member 5 and which also prevents lateral movement of said member 5.

In operation the two members are connected by the strap 3, as before stated, and the strap 4 or other article to be attached is placed in the recess or hook of member 1 and the serrated end of member 5 inserted in said recess. Tension then being applied to the straps, member 5 is forced into said recess, tightly clamping the strap 4. This clamping movement of member 5 is effected through the medium of the manner in which the strap 3 is arranged, said strap passing loosely through member 1 at a point forward of its attachment to member 5, so that a pull on said strap serves to move the latter member forwardly into the recess or hook.

It will be seen that the member 5 may be readily adjusted upon the strap 3 and that said member may be readily removed from the recess of member 1 to release the strap 4 or other article. It will be seen also that the device may be used in many connections—as, for instance, it would make a very convenient construction of garment-supporter, it being capable of easy attachment and when attached will securely hold the article to which it is attached.

Having now fully described my invention, what I claim as new, and desire to secure by Letters Patent of the United States, is—

The combination with a plate having one end turned backward to form a transversely-extending groove and formed near its opposite end with a transversely-extending slot, and a clamping-plate having a lower serrated edge to engage in said groove and formed with two parallel, transversely-extending slots, of a strap extending through said par-

allel slots of the clamping-plate and over the
upper edge of said clamping-plate and through
the slot in the first-named plate whereby the
serrated edge of the clamping-plate is caused
5 to clamp a strap or other article in said groove
of said first-named plate.

In testimony whereof I have hereunto af-

fixed my signature in the presence of two wit-
nesses.

ROBERT C. POOL.

Witnesses:

T. A. COLEMAN,

J. R. CHEEK.