


No. 745,866.

PATENTED DEC. 1, 1903.

E. H. B. LAING.  
COMBINED BANDOLEER AND WAIST BELT RIFLE CARRIER.

APPLICATION FILED FEB. 14, 1903.

NO MODEL.



Witnesses  
H. Van der Kolk  
Geo. P. Lawrence

Inventor  
E. H. B. Laing  
by H. Van der Kolk  
Attorney



# UNITED STATES PATENT OFFICE.

EDWIN HENRY BERTRAM LAING, OF LONDON, ENGLAND, ASSIGNOR OF  
ONE-EIGHTH TO GEORGE WARRIE CLARKE, OF LONDON, ENGLAND.

## COMBINED BANDOLEER AND WAIST-BELT RIFLE-CARRIER.

SPECIFICATION forming part of Letters Patent No. 745,866, dated December 1, 1903.

Application filed February 14, 1903. Serial No. 143,356. (No model.)

*To all whom it may concern:*

Be it known that I, EDWIN HENRY BERTRAM LAING, a subject of the King of Great Britain and Ireland, and a resident of London, Eng-  
land, have invented a certain new and useful  
5 Combined Bandoleer and Waist-Belt Rifle-Carrier, (for which I have filed applications for patents in Transvaal, No. 448, dated July 15, 1902; in Cape Colony, dated August 8,  
10 1902; in Natal, dated August 15, 1902, and in Great Britain, No. 17,578, dated August 11, 1902;) and I do hereby declare the following to be a full, clear, and exact description of the same.

15 This invention relates to a combined rifle-carrying bandoleer and waist-belt suitable for military and civil use whether mounted or on foot.

The device has been designed with the ob-  
20 jects of avoiding the inconveniences incidental to the use of the ordinary rifle-slings (with which the magazine-trigger guard and other projecting parts of the rifle are liable to un-  
25 duly wear the clothes and to chafe the wearer) and rifle-buckets when mounted (with which the horse is liable to be chafed) and of distributing the weight of the rifle over the person and enabling the rifle to be more speedily brought into action.

30 On the accompanying drawings, Figure 1 represents the improved device extended in the flat. Figs. 2 and 3 represent front and back views of the device in use, and Fig. 4 is a detail view.

35 In the device there is attached to a waist-belt *a*, provided with fastening-strap and buckle parts *a'*, a front bandoleer *b*, provided with pockets or pouches *b'* for carrying am-  
40 munition and with fastening-straps *b<sup>2</sup>* at its free end, and a back rifle-carrying band *c*, provided with a socket *c'*, adapted to receive and embrace the barrel of a rifle, and with fasten-  
45 ing-buckles *c<sup>2</sup>* at its free end, the bandoleer and the rifle-carrying band being so located relatively to the waist-belt and to each other that (*vide* Figs. 2 and 3) on the waist-belt be-  
50 ing secured around the body and the bandoleer passed up across the body and the rifle-carrying band passed up across the back the bandoleer and band can be secured together over the shoulder at a part convenient of ac-

cess to the wearer and with the belt bandoleer and band closely fitting to the body.

In alinement with the direction of the rifle-carrying band the belt is provided with an  
55 upturned angularly-disposed hook *c<sup>3</sup>*, adapted to support the stock of the rifle. To this end the grip portion of the rifle-stock is fitted with a sliding loop *d*, having a loose end *d'*, through which the rifle-stock is passed and  
60 by which it is securely embraced, and a loose end *d<sup>2</sup>*, securing a ring *d<sup>3</sup>*, adapted to be supported by the hook *c<sup>3</sup>*. The hook is preferably made as a spring-hook or is so shaped as to securely embrace the ring when placed  
65 in it and to require the employment of some little force to remove the ring from the hook in order to prevent the rifle from becoming detached in ordinary use. In alinement with  
70 the direction of the rifle-carrying band the belt is also provided with a hip-guard *c<sup>4</sup>*, against which the magazine-trigger guard and other projecting parts *d<sup>1</sup>* of the rifle are adapted to lie flatwise when the device is in use.  
75 The socket *c'*, hook *c<sup>3</sup>*, and hip-guard *c<sup>4</sup>* are thus so located that when the device is in use (with the barrel of the rifle passed upward through the socket and the stock of the rifle hung from the hook) the rifle will hang flat-  
80 wise against the rifle-carrying band and hip-guard, with no part of it lying against the clothing of the wearer. The belt may also be provided with a bayonet-scabbard, holster,  
85 or other sheath *e* for side-arms and with pouches or pockets for ammunition like to those carried by the bandoleer.

A second bandoleer with a back-strap may be applied to the belt, so as to cross the other.

Among the advantages incidental to the de-  
90 vice are its simplicity, comfort, and the speed with which it enables the rifle to be brought into action in any position. For a mounted  
95 man it gives the free use of both hands, giving him complete control over his horse, permitting him to mount and to dismount quickly and without encumbrance, enabling him to  
100 bring his rifle into use at any pace the horse may be going at, and in the case of his being thrown and his horse bolting he has remaining with him the means of defending himself, and in the event of his being armed with a sword, lance, or other equipment the device



allows of the free use of such weapon. For infantry on active service it is a comfortable means of carrying a rifle, the angle at which the rifle is hung distributing the weight  
5 equally over the body and causing a perfect balance, and, as is also the case with the mounted user, the clothing is protected at all parts where friction of the rifle parts would be likely to unduly wear the same, and chaf-  
10 ing by the rifle is avoided.

To put on the device, the left hand is used to guide the rifle-barrel into the socket  $c'$ , while the rifle loop-ring  $d^3$  is dropped by the right hand into the hook  $c^3$ . To remove the  
15 device, the loop  $d^2$  is held firmly in the right hand, while the thumb is pressed on the hook, and with a slight upward movement the ring is removed from the back, when the weight of the rifle will carry it out of the socket,  
20 whereupon the rifle is brought into position with a quick swing around.

What I claim as my invention, and desire to secure by Letters Patent, is—

A combined bandoleer and waist-belt adapt-

ed to carry a rifle and consisting of a waist- 25  
belt to which a front bandoleer and a back-  
band are attached in such positions that when  
the belt is secured around the body the band-  
doleer and back-band can be passed around  
crosswise of the body and secured together 30  
over the shoulder, the belt having a hip-  
guard and a hook adapted to receive a ring  
strapped to the stock of a rifle, and the back-  
band having a socket adapted to embrace the  
barrel of a rifle, so as, jointly with the hook, 35  
to support the rifle flatwise against the back-  
band belt and hip-guard in a position en-  
abling it to be removed by raising the rifle-  
stock ring from the belt-hook and withdraw-  
ing the rifle-barrel from the back-band socket, 40  
as set forth.

In testimony whereof I have signed this specification in the presence of two subscribing witnesses.

EDWIN HENRY BERTRAM LAING.

Witnesses:

ST. GEORGE CLAUD CAMPBELL LAING,  
BERNARD LEO DEVANY.