
G. M. URIE & A. A. MARKAM. TELEPHONE TABLET ATTACHMENT. APPLICATION FILED FEB. 16, 1903.



United States Patent Office.

GEORGE M. URIE AND ANDREW A. MARKAM, OF KANSAS CITY, MISSOURI.

TELEPHONE TABLET ATTACHMENT.

SPECIFICATION forming part of Letters Patent No. 745,978, dated December 1, 1903.

Original application filed August 15, 1902, Serial No. 119,759. Divided and this application filed February 16, 1903. Serial No. 143,675. (No model.)

To all whom it may concern:

Be it known that we, GEORGE M. URIE and ANDREW A. MARKAM, citizens of the United States of America, residing in Kansas City, in 5 the county of Jackson and State of Missouri, have invented a new and useful Improvement in Telephone Tablet Attachments, of which the following is a specification, reference being had therein to the drawings accompany-10 ing the same and forming a part thereof.

Our invention relates to improvements in

telephone tablet attachments.

This application is divisional of an application for Letters Patent filed by us on Au-15 gust 15, 1902, having Serial No. 119,759. In said prior application we have shown and described different mechanism, including the mechanism described and claimed in this present application, by means of which a tablet 20 could be adjusted to different positions upon a support provided with means for attachment to the frame of a telephone.

The object of the present invention is to provide means by which the tablet may be ad-25 justed to different angles upon the support and also to different vertical positions thereon. Our invention provides, further, interlocking means by which the tablet is firmly held upon the support in the position in which 30 it may be adjusted. It provides, further, certain novel means by which the support may be mounted upon a telephone-frame. Other features of novelty are hereinafter fully de-

scribed and claimed.

35 In the accompanying drawings, which illustrate our invention, Figure 1 is a perspective view showing our tablet attachment mounted upon a telephone-frame adapted to be secured upon the wall. Fig. 2 is a horizontal sec-40 tional view taken on the dotted line a b of Fig. 4. Fig. 3 is a vertical sectional view of the bracket and parts employed to clamp the | frame. At the left end of the said top as viewed telephone-frame, the clamping mechanism being of the form shown in Fig. 1. Fig. 4 is a 45 side elevation view of the bracket and the modified form of clamping mechanism used for securing the device to a desk-telephone frame. In this view the bracket is shown partly in vertical section. Fig. 5 is a plan

view of the parts shown in Figs. 2 and 4. 50 Fig. 6 is an elevation view of the bracket looking at the side provided with the interlocking means.

Similar characters of reference indicate

similar parts.

1 indicates the tablet, which may be of any desired shape, preferably rectangular, and provided on its under side with two arms 2, between which is secured a horizontal shaft 3, upon which is mounted a roll of paper 4. 60 Near the upper end of the tablet is provided a transverse slot 5, and near the lower end is provided a similar slot 6 parallel therewith. Upon the tablet is mounted a transverse tension-strip 7, the ends of which engage the 65 sides of the tablet. The particular construction of the tablet and roll supporting mechanism being fully described in the aforesaid prior application and not being herein claimed, it is not deemed necessary to further describe 70 the said mechanism. The paper is drawn through the slots 5 and 6 and under the tension member 7. An angular bracket 8, provided with a horizontal portion and a vertical portion, is secured by the horizontal por- 75 tion to the under side of the tablet 1. The vertical portion of the bracket is provided with two holes, extending horizontally therethrough, one above the other. Radially extending from each of said holes, on the left 80 side of the bracket as viewed in Fig. 2, are a series of grooves adapted to engage with projections on one of the clamping members, to be described later. Said grooves are indicated by the numeral 9, the holes in the ver- 85 tical portion of the bracket being indicated

by 10. In the form of our invention shown in Figs. 1 and 2, 11 indicates a horizontal bolt, mounted upon the top 12 of the wall-telephone 90 in said Figs. 1 and 3 is provided one of the clamping members 13, the lower side of which is provided with a lip 14, adapted to engage the under side of the top 12. Above the said 95 lip is provided a transverse hole in which is secured one end of the rod or bolt 11, the other end of which extends through a hori-

zontal hole provided in the other clamping member 15, which is also provided at its under side with an inwardly-extending lip 16, adapted to engage the under side of the top 12. 5 The bolt 11 extends through one of the holes in the bracket and is provided at the right end with screw-threads, on which end is fitted a nut 17, adapted to tightly clamp the bracket against the member 15. The mem-

so ber 15 is provided with two projections 18, adapted to enter two of the grooves 9 for preventing turning of the bracket on the bolt 11 after it has been adjusted to the proper position thereon. By loosening the nut 17 the

15 bracket may be turned to the position desired and then secured in such position by tightening the nut 17. If the tablet is desired in the upper position, the bolt 11 is mounted in the lower hole 10, and in the upper hole 10 when 20 it is desired to have the tablet in the lower

position.

In the device to be used with desk-telephones the members 13 and 15 are provided each with a concave curved portion adapted to 25 embrace the standard of the telephone. The two members are placed side by side and are secured together by a horizontal bolt 19, which is disposed in holes provided therefor in the said members. One end of the bolt 19 is 30 screw-threaded and provided with a nut 20, adapted to bear upon the adjacent member. The member 15 is provided with a projection 21, adapted to enter a groove 22 in the opposite member for preventing movement of the 35 clamping members with respect to each other. The member 15 in the form shown in Figs.

2 and 4 is provided with a horizontal screwthreaded extension 23, adapted to be inserted in one of the holes 10 of the bracket. The 40 adjustment of the bracket on the said projection is secured in a manner similar to that described with reference to the form shown in Figs. 1 and 3.

It will thus be seen that our invention may 45 be applied to the frames of wall or desk telephones with equal facility and proper vertical and circumferential adjustment of the bracket 8 upon the supporting mechanism attained. Our invention may be variously 50 modified without departing from its spirit.

Having thus described our invention, what we claim, and desire to secure by Letters Pat-

ent, is—

1. In a telephone tablet attachment, the 55 combination with a support provided with means for attachment to the frame of a telephone, of a tablet adjustable to different angles and vertically upon said support, and means for supporting a roll of paper upon the 60 tablet.

2. In a telephone tablet attachment, the combination with a support provided with means for attachment to the frame of a telephone, of a tablet adjustable to different an-65 gles and vertically upon the said support, and means for supporting a roll of paper from

the tablet, the tablet being also provided with means by which paper drawn from the roll of paper may rest upon and be clamped to the tablet.

3. In a telephone tablet attachment the combination with a support provided with means for attachment to the frame of a telephone, of a bracket vertically and circumferentially adjustable on the support, a tablet 75 mounted upon said bracket, and means for supporting a roll of paper upon the tablet.

4. In a telephone tablet attachment, the combination with two clamping members, of means for securing the same to a telephone- 80 frame, a tablet, means for vertically and circumferentially adjusting the tablet upon one of said members, and means for supporting a

roll of paper upon the tablet.

5. In a telephone tablet attachment, the 85 combination with two clamping members, of means for securing the same to a telephoneframe, a bracket adjustable with reference to one of said members to different positions and provided with interlocking means for engag- 90 ing said member, a tablet mounted on said bracket, and means for supporting a roll of paper upon said tablet.

6. In a telephone tablet attachment, the combination with two clamping members, of 95 a bolt for drawing the two members toward each other, a tablet vertically and circumferentially adjustable with reference to one of said members, and means for supporting a

roll of paper upon said tablet.

7. In a telephone tablet attachment, the combination with two clamping members, of a bolt for drawing the two members toward each other, a bracket adjustable to different positions with reference to and provided with 105 means for interlocking with one of said members, a tablet mounted upon said bracket, and means for supporting a roll of paper upon said tablet.

8. In a telephone tablet attachment, the 110 combination with two clamping members of means for drawing the same toward each other, a bracket adjustable vertically and at different angles with reference to one of said members, means for locking the bracket in po- 115 sition after such adjustment, a tablet mounted upon said bracket, and means for supporting a roll of paper upon said tablet.

9. The combination in a telephone tablet attachment with a support provided with 120 means for attachment to the frame of a telephone, of a bracket provided with two transverse holes disposed one above the other and through which the bracket is engaged by the said support at different times when the 125 bracket is in different vertical positions, the bracket being provided with means for adjustment at different angles when placed in either of the different vertical positions, and a tablet mounted upon the bracket.

10. The combination with a bracket, of a tablet mounted thereon, means for supporting

100

130

a roll of paper upon the tablet, a support provided with means for attachment to the frame of a telephone, the bracket being vertically adjustable upon the said support to different positions thereon and also adjustable to different angles when placed in either of said positions, the bracket and support being provided with interlocking means for retaining the bracket in adjustment in either position.

In testimony whereof we have signed our ronames to this specification in presence of two subscribing witnesses.

GEORGE M. URIE. ANDREW A. MARKAM.

Witnesses:

WARREN D. HOUSE, HENRY F. ROSE.