


No. 746,301.

PATENTED DEC. 8, 1903.

W. J. DICK.
HAT AND COAT RACK FOR BEDSTEADS.
APPLICATION FILED APR. 17, 1903.

NO MODEL.



Witnesses
Chas. A. Davies.
Ada V. Bates

Inventor
William J. Dick
by Chas. A. Bates
Attorney.

UNITED STATES PATENT OFFICE.

WILLIAM JOSEPH DICK, OF BAYONNE, NEW JERSEY.

HAT AND COAT RACK FOR BEDSTEADS.

SPECIFICATION forming part of Letters Patent No. 746,301, dated December 8, 1903.

Application filed April 17, 1903. Serial No. 153,107. (No model.)

To all whom it may concern:

Be it known that I, WILLIAM J. DICK, a citizen of the United States, residing at Bayonne, in the county of Hudson and State of New Jersey, have invented certain new and useful Improvements in Hat and Coat Racks for Bedsteads; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same.

My invention relates to improvements in hat and coat racks of that kind or style particularly designed for attachment to the head-post of iron and brass bedsteads and similar vertical standards.

The invention embodies a vertical standard provided with laterally-extending means for holding and securing it in position, hangers for the articles, and an adjustable stand or support to receive an article, all as will be hereinafter fully specified and the novelty thereof distinctly pointed out and definitely claimed.

I have fully and clearly illustrated my improvements in the annexed drawings, forming a part of this specification, and wherein—

Figure 1 is a perspective view of a bedstead of a well-known type, wherein my invention is shown in connection therewith. Fig. 2 is a perspective view of the complete device. Fig. 3 is a detail view of the stand attachment, partly in section, to show the manner of attaching the stand to the supporting-arm. Fig. 4 is a detail view, partly in vertical section, showing the manner of connecting the upper supporting-arm to the bed-post.

In the drawings similar parts appearing in the several illustrations are designated by similar reference notations, and, reference being had to the drawings, A designates a standard made of any suitable material and of such length as will suit it for the uses intended. Adjacent to the lower end of the standard is formed an arm 1, projecting laterally at right angles to the standard and formed on its outer end with a bifurcation 2, adapted to set about and take in the ver-

tical support, as the bedpost, and thus sustain the standard in vertical position.

Adjacent to the upper end of the standard A is an arm 3, projected horizontally and in vertical alinement to the arm 1 and formed with an eye 4 on its free end, which eye is adapted to rest on the upper end of the bedpost and have the threaded stem of the post-knob pass therethrough, so that when the arm is arranged in the required position and the knob is screwed down the arm will be clamped tight between the base of the knob and the end of the post, substantially as indicated in Fig. 4 of the drawings. At the lower end of the standard are formed hooks 5, on which may be hung such articles as may be desired, and at the upper end portion the standard is bent outward, as shown, and formed or provided with a vertically-extended hat-support 6, below which are provided suitable garment-hooks 7, all of which supports are for well-known purposes.

8 designates an arm formed with a sleeve 9, slidably arranged on the standard and held in any position thereon by means of a set-screw 10, let through the sleeve and bearing with its inner end against the standard. The outer portion of the arm 8 is directed vertically, as shown, and at its upper end is screw-threaded to take in a threaded socket-piece 11, fixed centrally to the under face of a table or stand piece 12, whereon may be placed such articles as may be desired.

To connect the device in position, the knob of the bedpost is removed, then the standard is disposed in relation to the post with the arm 3 resting on the upper end of the bedpost and the bifurcation 2 straddling the post below, then the post-knob is screwed down to clamp the arm to the post, and the device is fixed in position. The arm 8 may be adjusted to the desired height and the device is ready for the uses intended and designed.

Having thus described my invention, what I claim is—

A device for the purposes described, comprising a standard, a lower arm projecting laterally from the standard and forked at its

outer end, an upper arm extending from the
standard in vertical alinement with the lower
arm and formed with an eye in its free end,
coat and hat hooks at the upper end portion
5 of the standard, an arm slidably mounted on
the standard, and a table carried by the arm,
substantially as described.

In testimony whereof I affix my signature
in presence of two witnesses.

WILLIAM JOSEPH DICK.

Witnesses:

HYMAN LAZARUS,
JAMES F. MCCABE.