
G. B. STAPLES.

TILE.

APPLICATION FILED SEPT. 12, 1903.

NO MODEL



Attest: Amianleton Elev Leed

George F. Staples.
The George For Staples.
The George For Staples.

Attis

United States Patent Office.

GEORGE B. STAPLES, OF PHILADELPHIA, PENNSYLVANIA.

TILE

SPECIFICATION forming part of Letters Patent No. 746,399, dated December 8, 1903.

Application filed September 12, 1903. Serial No. 172,950. (No model.)

To all whom it may concern:

Be it known that I, GEORGE B. STAPLES, a citizen of the United States, residing at Philadelphia, Pennsylvania, have invented certain new and useful Improvements in Tiles, of which the following is a specification.

My invention relates to tiles for making floors and walls, and particularly to that class in which the tiles are provided with inter10 locking tongues, by which they are held together.

I do not wish to limit myself to any particular material composing the tile, as artificial stone may be used or a material having more or less yielding quality.

The invention consists in the features and combination and arrangement of parts hereinafter described, and particularly pointed out in the claim.

In the accompanying drawing I show a pair of tiles slightly separated, said tiles having the interlocking tongues thereon.

The tiles may be of any desired shape, and in the accompanying drawing I have shown the rectangular form simply as a representative one.

The interlocking tongues are shown at 1, and these consist of projections extending from the edges of the tiles, said projections 30 being at the lower portion of the edge of said side of the tile and reaching up in its thickness only part way of said side edge, which I have marked 2. The projection has beveled edges along its sides, and at the outer end 35 said projection has an upwardly-extending lip 3, which is also beveled upwardly with inclined sides at 4 and with an inclined outer face at 5, while the rear or inner face 6 of said projection extends more nearly vertical or at 40 right angles to the upper face of the said tongue or projection. Lip 3 extends only part way of the height of the said edge 2, and this lip is adapted to engage a socket 7, extending vertically from the under face of the tile and 45 forming a continuation of the recess 8, formed on the under side of the tile and opening through to the edge thereof, as shown at 9. The walls of the recess and of the socket 7 are arranged to conform to the sides and 50 faces of the projection 1 and lip 3, so that when the tongue is in the recess the lower

face of the tongue is substantially flush with the lower face of the tile. The vertical edges 6 and 6' of the lip 3 and socket 7 engaging with each other will hold the tile against 55 separating movement. It will be seen that the interlocking connection between the tiles is entirely hidden, and it is arranged so that when in engagement the said edges of the tiles will fit closely together and no joint, excepting that formed by these edges, will appear between the tiles.

By my arrangement the tiles may be readily interlocked with each other, owing to the beveled construction of the projection and the 65 walls of the socket and recess, and, further, it will be noticed that the desired results is accomplished with a projection which is comparatively short in its extent laterally from the side edge of the tile, as it is only neces- 70 sary to have the projection extend only a slight distance from the side edge of the tile and then to have the projection furnished with the upwardly-extending lip. This construction affords compactness at the interlock-75 ing connection, and consequently strengthens the same, a feature particularly desirable where tiles of yielding material are employed.

Of course each tile is provided both with 80 projections and recesses, so as to interlock with the adjoining tile.

A tile having a projection extending from the lower part of its side edge, said projection 85 having beveled side edges and a lip at the outer end of the said projection, said lip extending only part way of the height of the side edge of the tile and having a beveled front face and said tile having a recess and 90 socket to receive the projection and lip of an adjoining tile, the interlocking connection being hidden when the tiles are together and the sole visible joint between the tiles being that where their side edges meet, substan-95 tially as described.

In testimony whereof I affix my signature in presence of two witnesses.

GEORGE B. STAPLES.

Witnesses:
HENRY A. INGRAM,
JNO. F. REARDON.