

No. 746,584.

PATENTED DEC. 8, 1903.

D. SCHALK.

COMBINED BED AND COUCH.

APPLICATION FILED APR. 1, 1903.

NO MODEL.

2 SHEETS—SHEET 1.




FIG. 1.




FIG. 2.




FIG. 4.

Witnesses

Harry L. Amer.
Herbert D. Lawson.

David Schalk.

By Victor J. Evans

Attorney

No. 746,584.

PATENTED DEC. 8, 1903.

D. SCHALK.

COMBINED BED AND COUCH.

APPLICATION FILED APR. 1, 1903.

NO MODEL.

2 SHEETS—SHEET 2.

FIG. 3.




FIG. 5.





FIG. 6.



Inventor

David Schalk.

By Victor J. Evans.

Attorney

Witnesses

Harry L. Amer.
Herbert D. Lawson.

UNITED STATES PATENT OFFICE.

DAVID SCHALK, OF HAMILTON, OHIO.

COMBINED BED AND COUCH.

SPECIFICATION forming part of Letters Patent No. 746,584, dated December 8, 1903.

Application filed April 1, 1903. Serial No. 150,649. (No model.)

To all whom it may concern:

Be it known that I, DAVID SCHALK, a citizen of the United States, residing at Hamilton, in the county of Butler and State of Ohio, have invented new and useful Improvements 5 in a Combined Bed and Couch, of which the following is a specification.

My invention relates to new and useful improvements in combined beds and couches; 10 and its object is to provide a simple device which may be quickly and conveniently converted from a couch into a bed, or vice versa, and which is provided with a compartment for containing articles of clothing, &c.

15 A further object is to employ a closure for the front of the couch, which is attached in a novel manner to the bottom thereof, whereby said closure can be moved to a position under the couch when the same is converted into 20 a bed.

With the above and other objects in view the invention consists in the novel construction and combination of parts hereinafter more fully described and claimed, and illustrated 25 in the accompanying drawings, showing the preferred form of my invention, and in which—

Figure 1 is a side elevation of the couch. Fig. 2 is a vertical longitudinal section there- 30 through. Fig. 3 is a plan view showing the parts arranged for use as a bed and with the compartment open. Fig. 4 is a transverse section through the couch and showing in elevation the means for securing the front clo- 35 sure to the bottom of the device. Fig. 5 is a rear elevation of a portion of said closure and showing the engaging hook of the fastening means, and Fig. 6 is a detail view of a guide for said hook.

40 Referring to the figures by numerals of reference, 1 is the body of the device, which may be constructed of any suitable material and is open at one side and the top. To the side of the ends of this body is hinged a similar section 2, which is open at one side and the bottom thereof. A compartment 3 is formed upon one end of the main body 1 and extends upward therefrom a suitable distance to permit the hinged cover 4 thereof to extend up- 45 ward at an incline from the top 5 of section 2. This lid 4, as well as the top 5, is uphol- 50 stered.

Parallel cleats 6 are arranged upon the bottom of the body 1 and extend transversely thereof, and to these cleats are secured inwardly-extending metal strips 7, the ends of which are turned inward, as shown at 8. Arranged upon each strip 7 is a hook 9, which is formed at one end of and extends laterally from a rod 10, secured to the inner surface of 60 a closure 11, which extends over the open sides of the body 1 and section 2 and is adapted to be secured to the top of said section 2 in any suitable manner, as by means of a fastener 12. This closure and the sides of the com- 65 partment 3 are upholstered, and it is therefore obvious that the device normally presents every appearance of a couch.

Supporting strips 13 are arranged upon the bottom and top, respectively, of body 1 and 70 section 2, at the ends thereof, and to them are secured strips of, preferably, wire fabric 14, which are connected at the edges thereof adjoining the connected edges of the body 1 and section 2, and strips 14 may also be sup- 75 ported by suitably-arranged coiled springs 15.

When it is desired to convert the couch into a bed, the fastener 12 is unhooked and closure 11 swung outward and then moved longitudinally under the couch, thereby caus- 80 ing the hooks 9 to slide upon the strip 7. Section 2 is then swung outward into the position shown in Fig. 3, and legs 16, which are secured in any suitable manner to the rear edge of section 2, are swung outward in po- 85 sition to support said section. When the de- vice is folded to form a couch, the mattress and bedclothing are folded between the fab- ric strips 14.

It will be understood that clothing or other 90 articles may be placed within the compartment 3, and therefore be readily accessible.

I attach importance to the use of the hooked rods 10 for supporting the closure 11 and to the guide employed for said hooks, as by 95 means of this arrangement said closure can be readily moved out of the way, and yet held in such position as to be guided back to its proper place when it is desired to close the bed.

In the foregoing description I have shown the preferred form of my invention; but I do not limit myself thereto, as I am aware that modifications may be made therein without

departing from the spirit or sacrificing any of the advantages thereof, and I therefore reserve the right to make such changes as fairly fall within the scope of my invention.

5 Having thus described the invention, what is claimed as new is—

In a device of the character described, the combination with a body having a receptacle at one end thereof; of a section hinged to the body and adapted to extend thereover, spring-supported fabric secured within both the body and the section hinged thereto, a closure for the sides of said body and section,

means for securing the closure in such position, rods fastened to the inner surface of the closure, laterally - extending hooks integral with the rods, transversely-extending cleats upon the bottom of the body, and laterally-projecting strips secured to the cleats and engaged by, and adapted to guide, the hooks. 15 20

In testimony whereof I affix my signature in presence of two witnesses.

DAVID SCHALK.

Witnesses:

JOS. L. GARVER,
J. A. JONES.