

No. 751,313.

PATENTED FEB. 2, 1904.

J. O. N. LINDHOLM.  
SAFETY LOCK FOR SACKS, BAGS, &c.  
APPLICATION FILED NOV. 21, 1902.

NO MODEL.

FIG. 1.





FIG. 2.

WITNESSES

*H. F. Doyle*

*J. S. Powers,*

INVENTOR

*J. O. N. Lindholm*

BY

*W. B. Smith*  
Attorney

No. 751,313.

Patented February 2, 1904.

# UNITED STATES PATENT OFFICE.

JOHAN OLOF NATHANAEL LINDHOLM, OF STOCKHOLM, SWEDEN.

## SAFETY-LOCK FOR SACKS, BAGS, &c.

SPECIFICATION forming part of Letters Patent No. 751,313, dated February 2, 1904.

Application filed November 21, 1902. Serial No. 132,239. (No model.)

*To all whom it may concern:*

Be it known that I, JOHAN OLOF NATHANAEL LINDHOLM, merchant, a subject of the King of Sweden and Norway, residing at Stockholm, in the Kingdom of Sweden, have invented certain new and useful Improvements in Safety-Locks for Sacks, Bags, and Such Like; and I do declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same.

This invention relates to a safety lock for sacks, bags, and the like.

The invention is illustrated in the several figures of the annexed drawings, in which—  
Figure 1 is a front elevation, and Fig. 2 a plan view thereof.

The belt (designated at 1) is doubled intermediate its ends, the doubled end forming a loop which receives the clasp 4, the belt being attached by means of a rivet 2 to the sack 3, the ends of the belt being then passed through the clasp in the usual manner, so that the tongue 5 of the clasp may be received within the usual belt-hole. The clasp 4 and

the tongue 5 are provided with apertures 6 7, respectively, through which apertures the cord 8 is passed, the free ends of the cord being embedded within the securing means, here shown as being of a lead disk 9.

Having thus fully described my invention, what I claim as new, and desire to secure by Letters Patent, is—

In combination with a sack, a belt encircling the same, a buckle provided on one end of said belt and having a tongue adapted to project through openings provided in the other end of said belt, said buckle having its frame provided with an opening, said tongue having an opening alining with the opening in the buckle, a wire passing through the openings of the said buckle and tongue, means for securing the ends of said wire together, substantially as described.

In testimony whereof I affix my signature in presence of two witnesses.

JOHAN OLOF NATHANAEL LINDHOLM.

Witnesses:

H. HÅKANSON,

THOR FREDBORG.