
W. W. CARPENTER.

APPARATUS FOR MAKING HAIR BRUSHES.

APPLICATION FILED JUNE 11, 1903.

NO MODEL.



United States Patent Office.

WALTER W. CARPENTER, OF BROOKLYN, NEW YORK.

APPARATUS FOR MAKING HAIR-BRUSHES.

SPECIFICATION forming part of Letters Patent No. 753,234, dated March 1, 1904.

Application filed June 11, 1903. Serial No. 160,960. (No model.)

To all whom it may concern:

Be it known that I, Walter W. Carpenter, a citizen of the United States, residing at Brooklyn, in the county of Kings and State of New York, have invented certain new and useful Improvements in Apparatus for Making Hair-Brushes, of which the following is a specification, such as will enable those skilled in the art to which it appertains to make and use the same.

The object of this invention is to provide an improved apparatus for use in the manufacture of hair-brushes; and the invention is fully disclosed in the following specification, of which the accompanying drawings form a part, in which the separate parts of my improvement are designated by suitable reference characters in each of the views, and in

which—

Figure 1 is a plan view of a mold-block which I employ; Fig. 2, a similar view of a supplemental plate used in connection with said block; Fig. 3, a transverse section of said plate and block, the plate being placed over the block; Fig. 4, a face or front view of a brush-back which I employ; Fig. 5, a transverse section on the line 5 5 of Fig. 4; Fig. 6, a transverse section through the mold-block and supplemental plate and showing one step of the process of making a brush; Fig. 7, a view similar to Fig. 6, showing another step of the process of making a brush; and Fig. 8, a transverse section of the complete brush.

In the practice of my invention I provide a mold-block a, the top surface of which is provided with a raised beveled portion a^2 , in which is formed a receptacle a^3 , the bottom of which is gradually curved upwardly from the 40 center thereof toward the surrounding edges thereof, and said block a is also provided with a plurality of bores or passages a^4 , which extend therethrough and through which in the manufacture of a brush the tufts b of bristles or other 45 brush material are passed. I also provide a supplemental plate c, which is provided with an opening c^2 , similar in form to the raised portion a^2 of the mold-block a, and around this opening c^2 is a raised flange c^3 , the inner 50 walls of which are beveled outwardly and up-

wardly and outwardly and downwardly, as clearly shown in Fig. 3, the outward and downward bevel corresponding with the bevel or incline of the raised portion a^2 of the moldblock a, and said supplemental plate c is adapt- 55 ed to be placed on the block a, as shown in Figs. 6 and 7, and in this position of the block a and plate c the upwardly and outwardly directed bevel of the central opening c^2 of the plate c corresponds with the bevel or incline 60 of the bottom of the receptacle a in the raised portion a^2 of the block a. I also provide a brush-back d, the face portion of which is provided with a plurality of holes or recesses d^2 , any desired number of which may be em- 65 ployed, and said brush-back is also provided with a handle d^3 .

In the process of making a brush the tufts b of bristles or other brush material are passed upwardly through the block a, as clearly in- 7° dicated in Figs. 6 and 7. The receptacle a^3 in the block a is then filled with liquid or plastic cement e, in which the tufts b are embedded. The receptacle a^3 is filled rounding full of the cement, and the brush-back d is pressed 75 downwardly thereon, as shown in Fig. 7, and in this operation the cement enters the holes or recesses d^2 in the brush-back, and after the cement has set or become hard the plate c is removed from the block a and with it the 80 brush-back, the cemente, which adheres thereto, and the tufts b, which are secured in said cement, after which the brush, including the back d, the cement e, and the tufts b, are removed from the plate c. The plate c serves 85 in this operation to hold the edge portions of the cement in place and to prevent the breaking off thereof and to give a finished appearance to the brush.

The back of the brush-back d is rounded or 90 tapered in cross-section, and the front thereof, including the cement e, is similarly formed, the cement extending to the side and end edges of the brush-back in a gradual curve, as clearly indicated in Fig. 8, and a firm, strong, and 95 substantial brush is thus formed.

Having fully described my invention, what I claim as new, and desire to secure by Letters Patent, is—

The herein-described apparatus for making 100

hair-brushes, comprising a mold-block the top
of which is provided with a raised portion of
the shape which it is desired to give the body
of the brush, said raised portion being provided with a receptacle the bottom of which
is beveled outwardly and upwardly from the
central portion thereof to the edges thereof,
said block being also provided with bores or
passages which communicate with said receptacle and through which tufts of brush material are adapted to be passed, a plate adapted
to be placed on said block and provided with
a central opening which corresponds with the
raised portion on said block and which is
adapted to inclose the same, the top walls of

said opening being beveled outwardly and upwardly, so as to form an enlargement of the receptacle in the mold-block, said receptacle being adapted to receive liquid cement, and a brush-back provided in the face thereof with 20 holes or recesses, substantially as shown and described.

In testimony that I claim the foregoing as my invention I have signed my name, in presence of the subscribing witnesses, this 10th day 25 of June, 1903.

WALTER W. CARPENTER.

Witnesses:

F. A. Stewart, C. E. Mulreany: