

BEST AVAILABLE COPY

No. 763,605.

PATENTED JUNE 28, 1904.

D. HEPP.
TOOL HOLDER.

APPLICATION FILED JULY 17, 1903.

NO MODEL.

2 SHEETS—SHEET 1.




Fig. 1.

Witnesses

C. H. Walker
Geo. E. Tew




Fig. 2.

Inventor

Daniel Hepp

By

Milo B. Stevens & Co.

Attorneys

No. 763,605.

BEST AVAILABLE COPY


PATENTED JUNE 28, 1904.

D. HEPP.
TOOL HOLDER.

APPLICATION FILED JULY 17, 1903.

NO MODEL.

2 SHEETS—SHEET 2.



Inventor

Daniel Hepp

ਭੈਯ

Milo B. Stevens & Co
Attorneys

Witnesses

C. H. Walker?
Geo. E. Tew.

UNITED STATES PATENT

DANIEL HEPP, OF CHICAGO, ILLINOIS.

TOOL-HOLDER.

SPECIFICATION forming part of Letters Patent No. 763,605, dated June 28, 1904.

Application filed July 17, 1903. Serial No. 166,040. (No model.)

To all whom it may concern:

Be it known that I, DANIEL HEPP, a citizen of the United States, residing at Chicago, in the county of Cook and State of Illinois, have
 5 invented new and useful Improvements in Tool-Holders, of which the following is a specification.

This invention relates particularly to tools for scraping, sandpapering, rubbing, and finishing
 10 woodwork and to holders therefor; but it may be used for all purposes wherein it is necessary or desirable to work a reciprocating tool upon the surface of a piece of material, especially a plane surface. It may thus
 15 be conveniently used to scrape or polish stone, metal, hides, and the like.

The invention embodies the use of a holder for a tool of the kind stated in connection with a fluid-pressure motor, such as a pneu-
 20 matic engine, connected to the holder to give the motion thereto.

The holder is characterized by an adjustment which permits variable pressure or depth of cut on the surface being worked by the
 25 use of a carriage mounted on rollers in which the holder is movable with respect to the surface of the work.

Another feature of the invention is the use of the exhaust from the engine to carry off
 30 the scrapings and dust. This is effected by a cover over the tool more or less air-tight and a dust-tube leading from the cover.

The machine is adapted for bench use or for scraping floors and the like, conveniently
 35 by the addition of a long handle.

In the accompanying drawings, Figure 1 is a top plan view of the device. Fig. 2 is a vertical longitudinal section. Fig. 3 is a vertical cross-section on the line 3 3 of Fig. 2.
 40 Fig. 4 is a horizontal section on the line 4 4 of Fig. 3.

Referring specifically to the drawings, the carriage comprises a yoked frame 6 at each end, at the lower ends of the arms of which
 45 are bearings 6^a for the shafts of the rollers 7. Side slats 8 are joined to the frames by screws at 9. The screw-holes are slightly enlarged to permit a movement of the frames, to be hereinafter explained. The lower edges of

the side slats run in easy contact with the sur- 50
 face of the work.

The upper ends of the frames 6 are held between the ears 10, projecting upwardly from a block 11, by bolts 12, said bolts acting as
 55 pivots to permit a slight rock or movement of the frames 6 thereon. The block 11 carries the tool and motor, and this block is raised or lowered to vary the pressure on or cut in the surface of the work by means of the gears 13, which mesh with each other and with
 60 teeth produced on the end of the frames 6, as shown at 14. The motion is slight, as will be understood, and the gears rock slightly on their shafts in bearings in the ears 10. The outer ends of the shafts of the gears carry
 65 cranks 15, which project upwardly and have their upper ends connected by a spring 16 in tension, the tendency of which is to turn the gears, and consequently the frames 6 on their
 70 pivots 12, to the extent permitted by the enlarged screw-holes at 9, whereby, the rollers 7 being lowered the tool and its block are correspondingly raised.

One of the pivot-bolts 12 is extended on one side, as indicated at 12^a, and has fixed thereto
 75 a handle 17, which is oppositely disposed to a fixed handle 18, projecting laterally from the casting or block 11. Now if the handles be grasped and pressed together it will have the effect of slightly turning the pivots 12 and
 80 the frames 6, fast thereto, thereby raising the rollers and depressing the tool accordingly to give greater pressure for a polishing-tool or a deeper cut for an abrading-tool. The handles 17 and 18 thus serve to regulate the pres-
 85 sure and also to control the movements of the whole device.

The block 11 is bored, as at 11^a, to form the barrel for a piston or plunger of a reciprocating engine, as indicated at 19, the engine itself
 90 being indicated at 20. This engine may be of any suitable or approved kind, conveniently one such as is used in pneumatic tools having a handle and a latch therein controlling the pressure-inlet valve. The block 11 is also re-
 95 cessed or grooved, as at 11^b, to form a space for the reciprocation of the clamp 21, which is fixed and fastened on the plunger by the

end
piece or plate
The clamp 21
to the socket-piece by
extending through the ears thereof,
and a limited rocking movement is thus per-
mitted. If a rigid tool be desired, it may be
produced by tightening the lock-bolt 26, which
extends through the ears 23 and through a
10 rearward extension 21^a on the clamp.

The socket-piece 24 has a dovetail mortise
on its face to receive the corresponding tenon
27, fixed to the back of a tool, which in the
drawings I have shown as a polishing or sand-
15 ing block 28. This is shown as having a
grooved edge to receive and clamp the sand-
paper or polishing cloth 29 by means of a
hoop-clamp 30.

In connection with a sanding or rubbing
20 block a scraping-tool 31 is shown carried by
the tool-holder. The scraping-blade 31 is held
in the holder 32 by a slotted wedge 33 and its
bolt 34. The scraper can be set at an angle
upon bolts 34^a, by which it is pivoted or hinged
25 to lugs 35, projecting from the socket-piece 24
at each side thereof, as shown in Fig. 4. The
scraper may thus be rocked on the hinges to
the desired adjustment, which is fixed by the
lock-bolt 36, which is carried by the lug 37,
30 projecting from the back side of the scraper-
holder and extending through a slot 38 in an
ear 39 on the socket-piece 24.

At 40 a tin cover is indicated connected to
the upper edges of the slats 8 and to the out-
35 side of the block 11. The barrel of the en-
gine extends through this cover, and the ex-
haust from the engine enters within the cover,
as indicated at 41, at the rear end of the de-
vice. At the front the cover is tapped by an
40 exhaust-tube 42. The force of the exhaust
from the engine is thus utilized to blow the
dust and the like from the surface of the work
and out through the dust-pipe to any desired
outlet.

45 Although the invention is shown in connec-
tion with a scraping and polishing tool, it is
not limited thereto. Instead of the scraping
and polishing block any kind of tool desired
may be substituted by attachment to a tenon,
50 such as 27. Thus a polisher, a brush, a cupped
cutter or scraper, a groover, planer, or other
tool may be used. For use on a floor the han-
dle may be lengthened, and for certain kinds
of work it may be advisable or necessary to
55 remove the rollers and allow the weight and
pressure to be supported entirely by the tool.

In operation the reciprocation of the plun-
ger of the engine causes a corresponding move-
ment of the entire tool carried by the holder,
60 which may be directed and guided on the work
by the handle of the engine, and the pressure
of the tool on the surface of the work is con-
trolled and regulated by the handles 17 and

18, as above described. The flexible supply-
pipes commonly used in pneumatic tools will 65
allow the holder to be moved about as de-
sired.

The invention is not limited to the exact
construction shown and described nor other-
wise than is indicated in the following claims. 70

What I claim as new, and desire to secure
by Letters Patent, is—

1. The combination with a carriage adapted
to move over the surface of a piece of work,
of an engine having a reciprocating plunger 75
supported on the carriage, and a tool-socket
secured to the plunger.

2. The combination with a carriage adapted
to move over the surface of a piece of work,
of a reciprocating plunger on the carriage, ad- 80
justable to vary its distance from the said sur-
face, and a tool-holder attached to the plunger.

3. The combination with a carriage adapted
to move over a surface, of an engine-driven
tool-holder reciprocable on the carriage and 85
adjustable therein to vary its distance from
said surface.

4. The combination with an engine-barrel,
and a carriage on which it is supported substan-
tially parallel to the surface on which the car- 90
riage is movable, of a plunger working in the
barrel, and a tool-holder clamped to the plun-
ger and extending perpendicularly thereto,
to hold a tool against said surface.

5. The combination with a carriage, of a 95
fluid-driven engine thereon having a plunger
reciprocating substantially parallel to the base
of the carriage, and a tool-holder carried by
the plunger and extending therefrom toward
said base. 100

6. The combination with a carriage adapted
to travel upon the surface of a piece of work,
and a fluid-operated reciprocating tool-holder
therein carrying a tool acting under the base
of the carriage, of means to relatively adjust 105
the carriage and holder to vary the elevation
of the tool with respect to the base of the car-
riage.

7. The combination with an engine-barrel
and its reciprocating plunger, and a perpen- 110
dicularly-extending tool-holder clamped to the
plunger, of a wheeled frame carrying the bar-
rel and adjustable perpendicularly with re-
spect thereto to vary the distance of the plun-
ger with respect to the wheel-base. 115

8. The combination with a block bored to
form the barrel of a fluid-driven engine, hav-
ing a reciprocating plunger in the barrel,
and a tool-holder secured to the plunger, of
wheeled frames pivotally joined to the block 120
and means to turn the frames on their pivots
to raise or lower the wheels.

9. The combination with wheeled frames
pivoted and geared together at the top, of a
reciprocating tool-holder suspended from the 125
frames between the wheels, and means to turn

the frames on their pivots, to vary the distance of the tool-holder from the plane of the wheel-base.

10. The combination with a fluid-driven reciprocating plunger, of a laterally-extending clamp on the plunger and a tool-socket pivotally connected to the clamp and adjustable angularly with respect to the plunger.

11. The combination, an engine-barrel, a reciprocating plunger therein, a tool-socket carried by the plunger, carriage-frames pivoted to the barrel and having rollers at their lower ends, a spring connected to the frames tending to turn the frames and lower the rollers, and a handle connected to the frames and acting in opposition to the spring to raise the rollers.

12. In a tool-holder, in combination, a carriage, a tool-socket carried thereby, a scraper-clamp secured to the socket and adjustable thereon, and means to reciprocate the socket.

13. The combination with a tool and a fluid-driven engine connected thereto, to operate the same, of a cover over the tool and forming a close joint with the work, means to conduct the exhaust from the engine into the cover, and a dust-outlet from the cover.

In testimony whereof I have signed my name to this specification in the presence of two subscribing witnesses.

DANIEL HEPP.

Witnesses:

EWALD W. DIERSEY,
PAUL SCHAEPLI.