

No. 766,913.


PATENTED AUG. 9, 1904.

D. K. STONE.  
BADGE.


APPLICATION FILED MAY 27, 1904.

NO MODEL.


*Fig. 1.*




*Fig. 2.*



*Fig. 3.*



*Fig. 4.*



Witnesses  
*Leff Williams*  
*M. E. Moore*

Inventor  
*David K. Stone*  
By *Cha. N. Fowler*  
Attorney

# UNITED STATES PATENT OFFICE.

DAVID K. STONE, OF BLOOMINGDALE, MICHIGAN.

## BADGE.

SPECIFICATION forming part of Letters Patent No. 766,913, dated August 9, 1904.

Application filed May 27, 1904. Serial No. 210,050. (No model.)

*To all whom it may concern:*

Be it known that I, DAVID K. STONE, a citizen of the United States, residing at Bloom-  
ingdale, in the county of Van Buren and State  
5 of Michigan, have invented certain new and  
useful Improvements in Badges; and I do here-  
by declare that the following is a full, clear,  
and exact description of the same, reference  
being had to the annexed drawings, making a  
10 part of this specification, and to the letters of  
reference marked thereon.

The object of the present invention is to  
provide a badge that may be used for cam-  
paign purposes that will be ornamental and  
15 of novel construction and may be used for  
other purposes in which a badge of this char-  
acter may be found useful.

The invention consists in a badge construct-  
ed substantially as shown in the drawings and  
20 hereinafter described and claimed.

Figure 1 of the drawings is a front eleva-  
tion of a badge constructed in accordance with  
my invention. Fig. 2 is a sectional elevation  
thereof. Fig. 3 is a perspective view with  
25 the back removed to show the interior con-  
struction, the portrait-slide being shown in an  
elevated or raised position in dotted lines.  
Fig. 4 is a perspective view of the flanged end  
of the slide.

30 In the accompanying drawings, A repre-  
sents a suitable casing of any desirable mate-  
rial and of any preferred shape and provided  
with means for connecting it to the apparel of  
the wearer, a pin *a* being shown in the pres-  
ent instance, but any suitable means may be  
35 substituted for this purpose.

The casing A is formed hollow and has slots  
*b c* at its upper and lower ends, respectively,  
and, if desired, the front of the casing may  
40 contain a portrait or suitable lettering, as  
found most preferable, this being left entirely  
to the judgment of the manufacturer, depend-  
ing upon the use to which the badge is to be  
applied.

45 The casing A is formed hollow and has near  
its upper end a horizontal bar *d* with its ends  
fastened to the side walls of the casing, as  
shown in Fig. 3 of the drawings, and passing

around this bar is a suitably-colored ribbon  
B of sufficient length to extend down below 50  
the lower end of the casing, as shown in the  
drawings. That end of the ribbon B lying  
within the casing A is secured to the neck *e* of  
a portrait-slide C, which slide may contain  
thereon any particular portrait desired, such 55  
as a political candidate when the badge is  
used for campaign purposes.

The lower edge of the neck *e* is bent up  
against the edge of the ribbon, which forms  
a clamping-flange *e'* to hold the ribbon se- 60  
curely to the extended neck, and said neck is  
formed with stop-flanges *f*, extending out  
horizontally therefrom, and through the me-  
dium of the cross-bar *d* the upward move-  
ment of the portrait-slide will be limited, the 65  
bar serving the double function of a hanger  
for the ribbon and a stop to limit the move-  
ment of the slide through the medium of the  
stop-flanges *f*.

Pulling down upon the ribbon B will cause 70  
the portrait-slide to be elevated to the posi-  
tion shown in the drawings, and by pressing  
down upon the slide it is returned to the cas-  
ing and concealed therein.

Having now fully described my invention, 75  
what I claim as new, and desire to secure by  
Letters Patent, is—

A badge comprising a hollow casing having  
slots across its upper and lower end and a  
cross-bar near its upper end, and a portrait- 80  
slide located in the casing and having a de-  
pending neck and horizontally-extending  
stop-flanges operating in connection with the  
cross-bar to limit the upward movement of  
the slide, and a ribbon having one end con- 85  
nected to the neck of the slide and passing up  
and over the cross-bar and extending below  
the casing, substantially as and for the pur-  
pose set forth.

In testimony whereof I affix my signature in 90  
presence of two witnesses.

DAVID K. STONE.

Witnesses:

E. A. HAVEN,  
E. G. COOLEY.