





No. 768,339.

PATENTED AUG. 23, 1904.

H. F. NORTON.  
TROUSERS HANGER.

APPLICATION FILED MAR. 16, 1904.

NO MODEL.



Witnesses  
Ernest Pulsford.  
*Ernest Pulsford*

Inventor  
H. F. Norton.  
By his Attorneys  
*Baldwin, Davidson & Wright*



# UNITED STATES PATENT OFFICE.

HAROLD F. NORTON, OF NEWPORT NEWS, VIRGINIA.

## TROUSERS-HANGER.

SPECIFICATION forming part of Letters Patent No. 768,339, dated August 23, 1904.

Application filed March 16, 1904. Serial No. 198,331. (No model.)

*To all whom it may concern:*

Be it known that I, HAROLD F. NORTON, a citizen of the United States, residing at Newport News, in the county of Warwick and State of Virginia, have invented certain new and useful Improvements in Trousers-Hangers, of which the following is a specification.

This invention relates to trousers-hangers of the kind in which two clamp members are applied to the lower ends of the legs of the trousers and held in engagement therewith by a spring and in which one of the clamp members is provided with a hook or eye by means of which the clamp with the trousers attached may be suspended. Experience has shown that when trousers are flattened out, creased, and attached to clamps of this kind and the clamp is suspended so as to cause the trousers to hang freely therefrom the shape of the trousers may be preserved for a long time without pressing.

The object of my invention is to provide trousers-hangers of this general class which shall be strong and durable, may be cheaply made, and quickly applied and released and which shall securely hold the trousers without in any way injuring them.

In the accompanying drawings, Figure 1 is a perspective view of my improved hanger applied to a pair of trousers. Fig. 2 is a perspective view of the hanger with the clamp members open. Figs. 3 and 4 are detail views showing how the rubber band employed is attached to the cross-bar or handle which it carries.

There are two clamp members A and B, which are preferably made of wood finished smooth, but unpainted or varnished. Each member is preferably formed, as shown on its inner side, with a wide groove *a* to accommodate the seams of the trousers in order that the members may firmly engage the goods on opposite sides of the seams. The member A is formed at one end with a slot C, which is crossed by a wooden peg D, and at its opposite end is formed with a slot E. The front face of the member A, adjacent the slot E, is preferably recessed at *e* to receive the cross-bar or handle K, hereinafter referred to. The member B is formed at one end with a recess

G, crossed by a wooden peg H, and at its opposite end the member B is formed with a recess I.

J indicates an ordinary commercial rubber band or elastic loop, which is attached to the member A by the peg D and extends through the opening in the member B, formed by the recess G and closed by the peg H. In this way the members A and B are hinged together by the band J. Preferably the width of the recess G is approximately the same as that of the band J or a little less, so that the band will fit tightly therein. The band J carries on its outer free end a cross-bar or handle K, which is preferably attached, in the manner indicated in Figs. 3 and 4, by means of a wire clip L. As indicated, the band is inserted through a loop *l* in the clip, and then the cross-bar K is passed through the eyes *l'* of the clip and through the looped portion *j* of the band. Then the band is drawn back tightly in the manner indicated in Fig. 4. When assembled, the parts will appear as shown in Fig. 2, and when in this position the trousers may be applied to the clamp member A. Then the clamp member B may be folded over upon the trousers, and the band may be stretched and passed around the outer side of the member B, as indicated in Fig. 1, through the recesses I and E, and then the cross-bar or handle K may be seated in the recess *e*. At this time the parts will appear as shown in Fig. 1, and the clamp members will firmly engage the trousers. One of the clamp members may be provided with a suitable hanger M, which is preferably a hook, as shown.

By employing a rubber band of good quality the hanger may be used for a long time without repair; but should the band be broken or wear out it can easily be replaced, as such bands may be easily procured. As there are so few parts and as these parts are all inexpensive the hanger may be made very cheaply. There are no loose parts to get lost. There is no complicated mechanism, and therefore the hanger can be easily applied to or removed from the trousers. As there are practically no metallic parts and as the clamp members are unvarnished or unpainted there is no liability of the trousers being stained or



in any way injured. The clamp members are broad and flat, and no creases are formed in the trousers except where they belong. By providing recesses to accommodate the seams  
5 the clamp is made to engage the trousers at the edges of the legs, and thus preserve the proper creases. As indicated in Fig. 2, the clamp members may be laid wide open to receive the trousers and then may be easily  
10 closed and secured. A uniform and constant pressure is exerted on the trousers while they are suspended, and therefore there is no danger of their slipping from engagement with the hanger. I preferably employ a rubber  
15 band, because this may be easily procured and it is easily applied. It is essential that an elastic connection should be provided, but this connection instead of being in the form of a band, as shown, might of course be in the  
20 form of a tape of single thickness; but I do not recommend this. It would be inferior to the band, and yet the use of such a tape would be within the scope of my invention broadly stated.

25 I claim as my invention—

1. A trousers-hanger comprising two clamp members, a strip of elastic material flexibly connecting them at one end, and a cross-bar or handle carried by said elastic material and  
30 adapted to be detachably connected with the end of the clamp opposite the end thereof where the clamp members are flexibly connected.

2. A trousers-hanger comprising two clamp  
35 members, a rubber band or elastic loop flexibly connecting them at one end and a cross-bar or handle carried by said loop and adapted to be detachably connected with the end of the clamp opposite the end thereof where the  
40 clamp members are flexibly connected.

3. A trousers-hanger comprising two clamp members, a rubber band flexibly connecting them at one end and which extends longitudinally along the outside of one of the members and across the ends of both members,  
45 and a cross-bar or handle carried by the band and adapted to engage the clamp.

4. A trousers-hanger comprising two clamp members each of which has recesses at opposite ends, a rubber band attached to one member  
50 at one end extending through an adjacent recess in the other member and longitudinally along the outside of said member across the other recessed ends of both members, and a cross-bar or handle carried by the end of the  
55 band engaging the clamp.

5. A trousers-hanger comprising two clamp members each of which is recessed at opposite ends, a rubber band extending through all of said recesses and longitudinally along the out-  
60 side of one of the clamp members, a peg securing the band to one of the members, a cross-bar or handle carried by the band and engaging the same member to which the band is attached and a peg on the other member  
65 confining the band in one of the recesses through which it extends.

6. A trousers-hanger comprising two clamp members, a rubber band or elastic loop flexibly connecting them at one end, a cross-bar  
70 or handle carried by said loop and adapted to be detachably connected with the clamp, and a wire clip for attaching the cross-bar to the rubber band.

In testimony whereof I have hereunto sub-  
scribed my name.

HAROLD F. NORTON.

Witnesses:

J. E. HUNTER,

H. H. APPLENHETE.