No. 774,929.


PATENTED NOV. 15, 1904.

W. M. BASHLIN.

PROTECTING DIAPHRAGM FOR TELEPHONE TRANSMITTERS.

APPLICATION FILED OCT. 28, 1903.

NO MODEL,



Witnesses R. a. Batrles. M. C. Sullman

Toilliam MBushlin
4 NT Lines
Attorney

United States Patent Office.

WILLIAM M. BASHLIN, OF WARREN, PENNSYLVANIA.

PROTECTING-DIAPHRAGM FOR TELEPHONE-TRANSMITTERS.

SPECIFICATION forming part of Letters Patent No. 774,929, dated November 15, 1904.

Application filed October 28, 1903. Serial No. 178,953. (No model.)

To all whom it may concern:

Be it known that I, WILLIAM M. BASHLIN, a citizen of the United States, residing at Warren, in the county of Warren and State of Pennsylvania, have invented new and useful Improvements in Protecting-Diaphragms for Telephone-Transmitters, of which the following is a specification.

This invention relates to protecting-diaphragms for telephone-transmitters; and it consists in certain improvements in the construction thereof, as will be hereinafter fully described, and pointed out in the claims.

The invention is illustrated in the accom-

15 panying drawings as follows.

Figure 1 shows a side elevation of a telephone-transmitter, part of the mouthpiece being broken away to better show construction; Fig. 2, a plan view of the attaching-ring.

A marks the telephone-transmitter; A', the mouthpiece. A diaphragm C is secured over the opening in the mouthpiece by a ring B. The ring B is provided with lugs b, which are bent inwardly for engaging the edge of the provided with a screw b'. The ring also has its inner edge crimped in at b', so as to draw the diaphragm C' tight. The diaphragm C may be made from any suitable material, so

as to make a light sensitive film. It prevents 30 the lodgment of disease-germs in the mouth-piece and may be frequently renewed, so as to keep it in a sanitary condition. It also protects the parts forming the active elements of the telephone-transmitter, especially from 35 the moisture of the breath.

What I claim as new is-

1. In combination with a telephone-transmitter having a mouthpiece; a removable protecting-diaphragm arranged over the opening 40 in the mouthpiece and means for stretching and clamping the protecting-diaphragm about the edge of the mouthpiece.

2. In combination with a telephone-transmitter having a mouthpiece; a ring engaging 45 the edge of the mouthpiece and forming a means for securing the diaphragm on the mouthpiece, said ring being provided with an attaching-screw b; and the diaphragm removably secured to the transmitter by said 50 ring.

In testimony whereof I have hereunto set my hand in the presence of two subscribing witnesses.

WILLIAM M. BASHLIN.

Witnesses:

D. U. ARIED,

C. E. BORDWELL.