


C. J. SUTTER. BABY CARRIER. APPLICATION FILED SEPT. 23, 1904.







WITNESSES

J. D. Larrelu Fastemart INVENTOR

BY Charles J. Sutter

Edgar Tall & Co.

PHOTO-LITHIGRAPHED BY SACHETT & MILHELMS LITHO, E PTO, CO. NEW YORK.

United States Patent Office.

CHARLES J. SUTTER, OF WEST HOBOKEN, NEW JERSEY.

BABY-CARRIER.

SPECIFICATION forming part of Letters Patent No. 781,033, dated January 31, 1905.

Application filed September 23, 1904. Serial No. 225,609.

To all whom it may concern:

Be it known that I, Charles J. Sutter, a citizen of the United States, residing at West Hoboken, in the county of Hudson and State of New Jersey, have invented certain new and useful Improvements in Baby-Carriers, of which the following is a specification, such as will enable those skilled in the art to which it appertains to make and use the same.

The object of this invention is to provide an improved device for carrying a baby and which is adapted to be connected with a belt or other device at a woman's waist and also to be held in a horizontal position by a belt passing over one shoulder and on which a child may be seated and conveniently carried; and with this and other objects in view the invention consists in a device of the class specified, constructed as hereinafter described and claimed.

The invention is fully disclosed in the following specification, of which the accompanying drawings form a part, in which the separate parts of my improvement are designated by suitable reference characters in each of the views, in which—

Figure 1 is a front view of my improved child or baby carrying device and indicating the method of its operation or use; Fig. 2, a plan view of the seat portion of the device, and Fig. 3 a cross-section on the line 3 3 of Fig. 2.

In the drawings forming part of this specification I have indicated at a the figure of a 35 woman, and in the practice of my invention I provide a seat b, which in the form of construction shown consists of a frame b2, upholstered, as shown at b^3 , the frame being filled in with hair or other upholstering material, to which is held in place by top and bottom sheets b^4 , secured to the frame b^2 and composed of leather, canvas, or any suitable material. In Fig. 2 the back of the seat is shown at b^5 and the front thereof at b, and the opposite 15 sides of the seat are curved inwardly, as shown at b^7 , and one side of the seat is provided with hooks c, which open downwardly and which are connected with the seat b2, so as to turn thereon at c^2 . The opposite side of the seat o is provided with rings, eyes, or other attaching devices d, two of which are shown, with | which are connected a strap or straps e, this connection being preferably made by means of snap-hooks.

In practice the hooks c are connected with 55 a belt f, which is secured around the waist, and the strap or straps e are passed over the shoulder opposite the seat b, as clearly shown in Fig. 1, and the baby or child to be carried is placed on the seat b, and in this position 60 the strap or straps e serve to hold the child in position on the seat b, and one arm of the party carrying the child may also be used for the same purpose. This, as will be understood, leaves one arm free, and both arms may 65 also be used at times and under certain circumstances for any desired purpose, the child remaining seated, as will be readily understood. When desired or necessary, the hooks c may be reversed and the seat turned over 70 and used on the opposite side for the purpose of resting the party carrying the child or changing the strain caused thereby.

My invention is not limited to any particular form or construction of seat, and changes 75 in and modifications of the construction herein described may be made without departing from the spirit of my invention or sacrificing its advantages.

Having fully described my invention, what 80 I claim as new, and desire to secure by Letters Patent, is—

1. A seat-support for use in carrying a child, said seat-support being provided at one side with hooks adapted to engage a belt at one 85 side of the waist of the carrier, and at the opposite side with a strap adapted to be passed over the opposite shoulder of the carrier, substantially as shown and described.

2. A seat provided at one side with hooks 90 which open downwardly and at the opposite side with a strap or straps, said hooks being reversible, substantially as shown and described.

In testimony that I claim the foregoing as 95 my invention I have signed my name, in presence of the subscribing witnesses, this 22d day of September, 1904.

CHARLES J. SUTTER.

Witnesses:

F. A. STEWART,

C. J. KLEIN.