





No. 786,678.

PATENTED APR. 4, 1905.

C. M. RAWLINS.
DENTAL FLOSS HOLDER.
APPLICATION FILED SEPT. 1, 1904.



Witnesses

C. Munter
L. O. Hilton

Inventor

Clifton M. Rawlins.

by *H. R. Wilson*
Attorney

UNITED STATES PATENT OFFICE.

CLIFTON M. RAWLINS, OF CLEVELAND, OHIO.

DENTAL-FLOSS HOLDER.

SPECIFICATION forming part of Letters Patent No. 786,678, dated April 4, 1905.

Application filed September 1, 1904. Serial No. 223,045.

To all whom it may concern:

Be it known that I, CLIFTON M. RAWLINS, a citizen of the United States, residing at Cleveland, in the county of Cuyahoga and State of Ohio, have invented certain new and useful Improvements in Dental-Floss Holders; and I do declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same.

My invention is an improved dental-floss holder adapted for use in holding the dental floss taut when the same is employed and for conveniently containing a quantity of dental floss on a bobbin and also adapted to be folded and compactly disposed when not in use, so that it may be readily carried in the pocket.

My invention consists in the construction, combination, and arrangement of devices hereinafter described and claimed.

In the accompanying drawings, Figure 1 is a perspective view of a dental-floss holder embodying my improvements, showing the same with its spring-frame extended and the floss disposed in operative position. Fig. 2 is a longitudinal sectional view of the same. Fig. 3 is an elevation of the same, showing the frame folded and closed against the body of the holder; and Fig. 4 is a transverse sectional view of the same, taken on the plane indicated by the line *a a* of Fig. 3.

The body 1 of my improved dental-floss holder is of tubular cylindrical form and of suitable size to contain a bobbin 2, on which is wound a quantity of dental floss. In one side of the tubular body is a longitudinal slot 3, through which the floss extends, and one end of the tubular body is open and is provided with a cap or closure 4, the same fitting against a shoulder 5, with which the body is provided, and the body or cap or closure having a coengaging shoulder or lug 6 and notch 7 to lock the cap against rotation on the body. The outer end 8 of the cap or closure projects beyond its head 9 and forms a projecting annular flange, which has openings 10 in opposite sides, one of the said openings registering with a longitudinal groove 11 in the outer side of the cap or closure.

I employ a spring-frame 12 to support a

portion of the floss and hold the same taut while being used. This spring-frame is made from a single piece of spring-wire and is preferably of the form shown in the drawings, having a right-angled portion 13 at its inner 55 end passed through the openings 10 in the cap and pivotally connecting the spring-frame to the cap, and an arm 14 at the terminal end of the said transverse portion 13 to enter the groove 11 of the cap and provided at its outer 60 end with a transverse arm 15, which terminates in an outwardly-directed hook 16. The length of the intermediate portion of the said spring-frame and of its transverse end portions 13 15 is such that the spring-frame may 65 be folded compactly against the body portion of the holder in order to compactly dispose the device when not in use. When in use, the floss is wrapped around the arm 14 and is stretched between the said arm and the hook 70 16 and wrapped around the latter, said arm and said hook serving, owing to the tension of the spring-frame, to hold that portion of the floss which is between said arm and hook taut and adapt it for use on the teeth of the 75 patient, as will be understood. When the frame is in its extended position, the arm 14 engages the groove 11 of the cap or closure, said arm and groove coacting to hold the frame in extended position. 80

On one side of the cylindrical body is a cutting device 17, which is employed for cutting the floss.

From the foregoing description, taken in connection with the accompanying drawings, 85 the construction, operation, and advantages of the invention will be readily understood without requiring a more extended explanation.

Various changes in the form, proportion, 90 and the minor details of construction may be resorted to without departing from the principle or sacrificing any of the advantages of this invention.

Having thus described my invention, what 95 I claim as new, and desire to secure by Letters Patent, is—

1. A dental-floss holder comprising a body portion having a detachable cap at one end, and a frame to hold the floss in an extended 100

position with respect to the body portion, said frame being pivotally connected to and carried by the cap and adapted to be folded against the body, and a bobbin in the body, 5 retained therein by the detachable cap.

2. A dental-floss holder comprising a body portion adapted to contain a quantity of dental floss and being open at one end and provided with an opening in one side for the passage of 10 the floss, a cap or closure to close the said open end of the body, and a device pivotally connected to and carried by the cap or closure to

hold a portion of the floss taut in an extended position with respect to the body, said pivoted device being foldable upon the body, and having means to engage the end thereof opposite the said cap or closure.

In testimony whereof I have hereunto set my hand in presence of two subscribing witnesses.

CLIFTON M. RAWLINS.

Witnesses:

CLAYTON R. BALDWIN,
J. SHARP MAXWELL.