




No. 790,200.

PATENTED MAY 16, 1905.

R. G. W. FOSTER.  
DEVICE FOR SUPPORTING PAINT PAILS.  
APPLICATION FILED AUG. 10, 1904.



WITNESSES

E. O. Miller  
Chas. C. DeFurbaugh.

INVENTOR

R. G. W. Foster  
By *Chas. C. DeFurbaugh* atty.



# UNITED STATES PATENT OFFICE.

ROBERT G. W. FOSTER, OF TOLEDO, OHIO.

## DEVICE FOR SUPPORTING PAINT-PAILS.

SPECIFICATION forming part of Letters Patent No. 790,200, dated May 16, 1905.

Application filed August 10, 1904. Serial No. 220,189.

*To all whom it may concern:*

Be it known that I, ROBERT G. W. FOSTER, of Toledo, county of Lucas, and State of Ohio, have invented certain new and useful Improve-  
5 ments in Devices for Supporting Paint-Pails; and I do hereby declare that the following is a full, clear, and exact description of the invention, which will enable others skilled in the art to which it appertains to make and use  
10 the same, reference being had to the accompanying drawings, and to the figures of reference marked thereon, which form part of this specification.

My invention has reference to a device for  
15 supporting paint-pails upon ladders, scaffolds, &c.

In painting buildings it is the usual practice to suspend the pail containing paint from a ladder by means of a wire bent in the form  
20 of a double hook, one of the hooks being adapted to engage the bail-handle of the pail and the other engaging the round of the ladder. Where a paint-pail is suspended in this manner, the bail-handle assumes a position in  
25 a vertical plane immediately above the open top of the pail and necessarily presents an obstruction to the passage of the brush into the pail. The operation of dipping the brush is further hampered by the presence immediately  
30 above the open top of the pail of the ladder-round from which the pail is suspended. By the employment of my improved device the paint-pail is rigidly supported in position, the open top of the pail being entirely free from  
35 obstruction and the usual tendency of the pail to swing back and forth being entirely eliminated.

To this end my invention comprises a clamp for the attachment of the device to a ladder  
40 or other support, a member formed to embrace the pail-body, and means for engaging the handle of the pail.

In carrying out my invention I employ the novel combination and the arrangement of the  
45 parts hereinafter shown, described, and claimed.

In the accompanying drawings, Figure 1 is an elevation illustrating my improved device in position upon a ladder and showing a paint-

pail supported thereby. Fig. 2 is a side elevation of the same, the position of the pail with relation to the device being shown in dotted outline. Fig. 3 is a plan view of the bent wire member adapted to embrace the pail.

Referring to the details as shown in Figs. 1 and 2, the device comprises a screw-clamp  
55 1 for the attachment of the device to a ladder, a downwardly-extending member 2 upon the clamp-jaw, curved or formed to embrace the pail-body and extending approximately half-  
60 way around the same, and an upwardly-extending projection 3 upon the clamp-jaw adapted to engage the handle of the pail. The member 2 and the projection 3 may be constructed from a single piece of sheet metal stamped  
65 out in proper shape and secured to the clamp-jaw in any suitable manner. As illustrated, however, I prefer to construct these parts out of wire, employing a single piece of proper  
70 length and bending the same to provide a curved portion 4 of the shape of the body of the pail. Then by bending the wire angularly at 5 I provide inclined curved portions 6,  
75 meeting each other at 7, being at this point passed through and projecting above parallel perforations 8, (indicated in dotted lines,) provided in the jaw of the screw-clamp, said perforation being preferably spaced apart and the wire ends shouldered, as at 9, after their  
80 insertion to prevent their withdrawal.

The manner of supporting the paint-pail by means of my improved device is shown in Figs. 1 and 2, the same being firmly held in place and the usual tendency to swing back and forth being entirely eliminated. It will  
85 be observed that the top of the pail is entirely free from obstruction, the handle of the pail being firmly secured in lowered position.

As illustrated the device is arranged for use  
90 upon ladders, the clamp assuming a horizontal position to permit its attachment to the elongated side pieces of the ladder. Where it is intended to employ the device upon scaffolds, the position of the clamp relative to the mem-  
95 ber 2 would be altered to cause the clamp to assume a vertical position to clamp the horizontal pieces of the scaffold.



From the foregoing description the novelty, utility, and many advantages of my device should be apparent.

Having described my invention, what I claim, and desire to secure by Letters Patent, is—

1. In a device for supporting paint-pails, a clamp provided with a member, curved to conform to the shape of the pail-body, and having means for engaging the pail-handle, substantially as described.

2. In a device for supporting paint-pails, a clamp provided on one of its jaws with a member formed to embrace a pail-body, and having an upwardly-extending projection on said jaw for engaging the pail-handle, substantially as described.

3. In a device for supporting paint-pails, a clamp, and a wire member, secured to the clamp, having a portion thereof formed to embrace a pail-body and having the ends thereof extended upwardly above the clamp to provide means for engaging the pail-handle, substantially as described.

4. In a device for supporting paint-pails, a clamp, and a substantially triangular-shaped

wire member having the angular portions thereof bent to embrace the body of a pail and having the ends of the wire forming said member inserted through the clamp-jaw and projecting in parallel relation above the same to provide engaging means for the handle, substantially as described.

5. In a device for supporting paint-pails, a clamp, having a screw-threaded stem operating through one of its jaws, and having a pair of perforations in the other jaw, a wire member having the curved portion 4 to embrace the pail-body, the inclined portions 6 meeting at their upper ends, and the ends thereof inserted through the perforations in the clamp-jaw, said ends being provided with a shouldered offset to prevent their withdrawal after insertion, substantially as described.

In testimony that I claim the foregoing as my own I affix my signature in presence of two witnesses.

ROBERT G. W. FOSTER.

Witnesses:

CARL H. KELLER,  
W. G. THURSTIN.