


No. 791,379.

PATENTED MAY 30, 1905.

W. TERRY.
BAG HOLDER.

APPLICATION FILED AUG. 10, 1904.



WITNESSES:

John T. Schrott,
Ella Mac Cormick.

INVENTOR

William Terry.

BY

Fred Goettlich & Co.
ATTORNEYS

UNITED STATES PATENT OFFICE.

WILLIAM TERRY, OF PEARL CITY, ILLINOIS.

BAG-HOLDER.

SPECIFICATION forming part of Letters Patent No. 791,379, dated May 30, 1905.

Application filed August 10, 1904. Serial No. 220,217.

To all whom it may concern:

Be it known that I, WILLIAM TERRY, residing at Pearl City, in the county of Stephenson and State of Illinois, have invented certain new and useful Improvements in Bag-Holders, of which the following is a specification.

This invention relates to certain new and useful improvements in bag-holders; and it has for its object to provide means for holding the mouth of the bag in a distended position until filled and then for conveniently releasing it from the holder to permit the end of the bag to be closed.

Generically, my invention includes a stand having a vertical supporting member to which the bag-holder member is adjustably secured, and the said bag-holder in its generic nature includes a pair of laterally-movable arms adapted to be received by the bag-neck and means for either extending or drawing together said arms and maintaining them in such extended or drawn-together position.

With other objects in view, which will be hereinafter apparent, the invention includes certain novel construction, arrangement, and combination of parts, all of which will be first described in detail and then be specifically pointed out in the appended claims, reference being had to the accompanying drawings, in which—

Figure 1 is a perspective view of my invention as applied for use. Fig. 2 is a front elevation thereof, the bag being broken away. Fig. 3 is a vertical cross-section on the line 3 3 of Fig. 2. Fig. 4 is a horizontal section on the line 4 4 of Fig. 2.

Referring now to the accompanying drawings, in which like numerals of reference indicate like parts in all of the figures, the support or standard 1 is mounted upon a base 2, to which the receiving-platform 3 is secured, and the said support is suitably braced by brace-rods 4 4, as shown.

5 designates the mechanism for holding the bag 10 with its mouth distended, and this mechanism includes the U-shaped bracket 6, the front leg 6^a of which has a vertical slot 6^b, while the rear leg 6^c has an inwardly-curved portion or bend 6^d. The cross-arm 7, fixedly secured to the lower end of the

rear leg 6^c of the bracket 6, has fixedly-held clips or rings 8 8 at each end, which rings 8 8 serve as guides for the crossed bag-engaging arms 9 9, which have their ends 9^a 9^a passing through said rings 8 8 to lie parallel with each other and the cross-arms 7.

9^b 9^b designate the bag-engaging ends of the arms 9 9, which may be of a U shape in horizontal section or may be circular in form, if desired, depending upon the nature of the opening desired in the bag end, and the said arms 9 9 may be provided with pins 10^x 10^x for engaging the bag, if found desirable.

11 designates a lever which includes a handle portion 11^a and a link 11^b, formed integral therewith, which at the end 11^c is pivotally secured to one of the arms 9 near the bag-engaging end 9^b.

12 designates a second link member, one end of which, 12^a, is pivotally joined with the other arm 9 at its end 9^b, and at its other end, 12^b, the link 11^b is pivotally joined to the lever member 11, where the handle portion 11^a and the link portion 11^b are connected, and the said pivotal connection 13 for the links 11^b and 12 also passes through the slots 6^b and is movable vertically therein.

14 designates a bolt which passes through the rear leg 6^c near its top and through the slot 1^a of the support 1 to receive a wing-nut 14^a, whereby the bracket 6 can be adjusted up and down with respect to the support 1. The bracket 6 also has a projection or leg 6^x, which enters the slot 1^a to prevent turning of the bracket on the axial line of the bolt 14 during the bag opening and closing action.

The links 11^b and 12 are so shaped that when the parts are in position shown in dotted lines in Fig. 2 they will lie in a vertical plane in the arc of the same circle, and when the parts are in the position shown in full lines in Fig. 2 the pivot-bolt 13 will lie in the horizontal plane below that containing the pivotal connection of the links with the arms 9 9 and lock the parts to the bag-opening position.

As an auxiliary means for locking the parts to their bag-opening position and to allow the use of my invention in connection with bags of various sizes I provide the front leg

6^a of the U-shaped bracket 6 with a rack portion 6^z, with which the pawl 11^z, fulcrumed on the link portion 11^b, coöperates, as clearly shown in the drawings.

5 So far as described the operation of my invention will be best explained as follows: The operator raises the handle-lever to the position shown in dotted lines in Fig. 2 and then places the neck of the bag around the
10 arms 9 9, after which he lowers the handle-lever until the parts are in the position shown in full lines in Fig. 2, when the arms 9 9 will be distended and firmly hold the bag with the mouth open. The pivot-bolt which slides
15 in the vertical slot of the bracket will be forced down to the extreme lower portion of the said slot, and by reason of the peculiar shape of the link members the arms 9 9 will be held to their extended position regardless
20 of the pressure applied thereto at their ends, since any force applied to the end of the arms 9 9 to close them together will only serve to tend to force the pivot-bolt, which moves up and down in the slot of the bracket, to its
25 lowermost position. When smaller bags are used, the parts will be locked in their bag-opening position by the rack and pawl devices 6^z 11^z, before referred to.

From the foregoing description it will be
30 seen that I provide a very simple and effective construction of bag-holding means which will readily and effectively serve its intended purposes. As soon as the bag has become filled it is only necessary to again raise the hand-lever
35 to the position shown in dotted lines in Fig. 2, when the bag will be released.

From the foregoing description, taken in connection with the accompanying drawings, it is thought the advantages, construction,
40 and complete operation of my invention will be readily understood by those skilled in the art to which it appertains, and I desire it understood that slight changes in the detailed arrangement of parts may be made without
45 departing from the invention or the scope of the appended claims.

Having thus described my invention, what I claim, and desire to secure by Letters Patent, is—

50 1. A device of the character stated, comprising in combination with a base, a platform and a standard secured thereto, of a bag-holding and mouth-extending mechanism vertically adjustably held upon said standard and in-
55 cluding a U-shaped bracket, a laterally-extending guide member secured to said U-shaped bracket, bag-engaging arms held in said laterally-extending guide means for expanding and contracting the arms laterally with re-
60 spect to each other.

2. A device of the character stated, comprising in combination with a base, a platform and a standard secured thereto, of a bag-holding and mouth-extending mechanism vertically
65 adjustably held upon said standard and in-

cluding a U-shaped bracket, a laterally-extending guide member secured to said U-shaped bracket, bag-engaging arms held in said laterally-extending guide, means for expanding or contracting the arms laterally
70 with respect to each other, said means including a lever member pivotally secured at one end to one of said arms, and a link member pivotally secured at one end to the other arm and at its other end to the lever member. 75

3. A device of the character stated, comprising in combination with a base, a platform and a standard secured thereto, of a bag-holding and mouth-extending mechanism vertically
80 adjustably held upon said standard and including a U-shaped bracket, a laterally-extending guide member secured to said U-shaped bracket, bag-engaging arms held in said laterally-extending guide means for extending or contracting the arms laterally with
85 respect to each other, said means including a lever member and a link member, the lever member being pivotally secured at one end to one of said bag-engaging arms, said link member being pivotally secured at one end to the
90 other bag-engaging arm, and said link member and said lever member being pivotally secured to each other and to the U-shaped bracket, substantially as shown.

4. A device of the character stated, comprising in combination with a base, a platform and a standard secured thereto, of a bag-holding and mouth-extending mechanism vertically
95 adjustably held upon said standard and including a U-shaped bracket, a laterally-extending guide member secured to said U-shaped bracket, bag-engaging arms held in said laterally-extending guide, means for extending and contracting the arms laterally
100 with respect to each other, said means including a lever member and a link member the lever member being pivotally secured at one end to one of said bag-engaging arms, said link member being pivotally secured at one end to the other bag-engaging arms, and said
105 link member and said lever member being pivotally secured to each other and to the bracket member, said pivotal connection of the link and lever members passing through and being vertically movable in a slot in the
110 bracket member, substantially as shown and for the purposes specified. 115

5. A device of the character stated, comprising in combination with a base, a platform and a standard secured thereto, said standard being
120 vertically slotted near its upper end, a bag-holding mechanism comprising a U-shaped bracket, a bolt passing through said U-shaped bracket and said slotted portion of the standard, a wing-nut coöperating with said bolt to
125 hold said U-shaped bracket to said standard, said U-shaped bracket including a transverse bearing-arm having rings at each end, said bracket member also including a vertically-slotted portion, a pair of bag-engaging arms 130

coöperating with said transverse portion of the bracket member and passing through the transverse bracket member rings, a curved link pivotally secured at one end to one of said bag-engaging arms, a lever member including a curved link portion pivotally secured at one end to the other bag-engaging arm, a pivot-bolt passing through said slotted portion of the bracket member through said lever member and the other end of the first-mentioned link member to pivotally join the link and lever members with each other and with the bracket portion, said bag-engaging arms, said lever and said link members being so arranged that when the lever member is forced downward the bag-engaging arms will be extended, and the pivot-bolt passing through the link, the lever and the slotted portion of the bracket will be forced to its lowermost position to lock the members in their bag-engaging arm-extended position, substantially as shown and described.

6. A device of the character stated, comprising in combination with a base, a platform and a standard secured thereto, of a bag-holding and mouth-extending mechanism vertically adjustably held upon said standard and including a U-shaped bracket, a laterally-extending guide member secured to said U-shaped bracket, bag-engaging arms held in said laterally-extending guide, means for extending or contracting the arms laterally with respect to each other, said means including a lever member and a link member, the lever member being pivotally secured at one end to one of said bag-engaging arms, said link member being pivotally secured at one end to the other bag-engaging arm, and said link member and said lever member being pivotally secured to each other and to the bracket member, means for locking said bag-engaging arms to their extended position.

7. A device of the character stated, compris-

ing in combination with a base, a platform and a standard secured thereto, of a bag-holding 45 and mouth-extending mechanism vertically adjustably held upon said standard and including a U-shaped bracket, a laterally-extending guide member secured to said U-shaped bracket, bag-engaging arms held in 50 said laterally-extending guide, means for expanding or contracting the arms laterally with respect to each other, said means including a lever member pivotally secured at one end to one of said arms, and a link member pivot- 55 ally secured at one end to the other arm and at its other end to the lever member, means for locking said bag-engaging arms to their extended position.

8. A device of the character stated, compris- 60 ing in combination with a base, a platform and a standard secured thereto, of a bag-holding mechanism vertically adjustably held upon said standard and including a U-shaped bracket, a laterally-extending guide member 65 secured to said U-shaped bracket, bag-engaging arms held in said laterally-extending guide member, means for extending and contracting the arms laterally with respect to each other, said means comprising a lever member 70 and a link member, the lever member being pivotally secured at one end to one of said bag-engaging arms, said link member being pivotally secured at one end to the other bag-engaging arm, the said link member and said 75 lever member being pivotally secured to each other and to the bracket member, said bracket member having a rack portion, a pawl secured to the lever member for engaging with said rack portion to lock the bag-engaging arms 80 to their extended positions substantially as shown and for the purposes described.

WILLIAM TERRY.

Witnesses:

ORIE W. DOW,
J. F. MISHLER.