





No. 797,088.

PATENTED AUG. 15, 1905.

F. A. TOBLER.  
COMBINATION PASTRY KNIFE.  
APPLICATION FILED APR. 4, 1904.



Witnesses:  
Charles M. Wiggan  
Jessie V. Ryan

Inventor:  
Frederick A. Tobler



# UNITED STATES PATENT OFFICE.

FREDERICK A. TOBLER, OF LOS ANGELES, CALIFORNIA.

## COMBINATION PASTRY-KNIFE.

No. 797,088.

Specification of Letters Patent.

Patented Aug. 15, 1905.

Application filed April 4, 1904. Serial No. 201,589.

*To all whom it may concern:*

Be it known that I, FREDERICK A. TOBLER, a citizen of the United States of America, residing at Los Angeles, in the county of Los Angeles and State of California, have invented new and useful Improvements in Combination Pastry-Knives; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same.

My invention relates to improvements in combination pastry-knives of the class used in crimping and reaming pies, trimming cakes, &c., and has for its object, first, to provide an instrument for crimping and reaming pies simultaneously; second, to provide a spur for puncturing and lettering the face-crust of pies, thus eliminating the need for a separate instrument; third, to afford effective means for rasping the dried and burned edges from cakes and otherwise plumbing them up preparatory to glazing or frosting, which means may also be utilized as a common grater; fourth, to provide a device of this description, combined in one compact instrument, adapted to convenient and effective use for the purposes named.

A practical embodiment of my invention is represented in the accompanying drawings, in which—

Figure 1 represents a side elevation of the device in vertical section constructed according to my invention. Fig. 2 represents a plan view of the same. Fig. 3 designates a broken elevation of the reaming-wheel. Fig. 4 represents a vertical section of the reaming-wheel as it may be constructed, with the cup J and the flange K formed separately and united by means of solder.

Like letters of reference refer to like parts throughout the several views.

A represents a longitudinal grating-plate substantially mounted upon a plurality of parallel ribs, said ribs contacting at B and describing a plurality of twists, then bulging laterally, forming a handle C C, when they again contact and describe another series of twists, a portion of which are turned abruptly vertical, one wire ending in a flatwise coil D, the other in a vertical bearing or boss E.

F designates a wheel or shell rotatably mounted upon the boss E, said wheel com-

prising a disk G and an integral transverse fluted portion H and an integral concave flange I, or, if preferable, this wheel may be assembled after the manner shown in Fig. 4, with the cup J and the flange K formed separately and united by means of solder. The wheel F is retained upon its axis by means of a small circular piece of tin soldered upon the apex of the boss E so as not to interfere with the free rotation of said wheel, but to hold it securely against coil D.

L designates a spur formed laterally and on a plane with the grater A, said spur comprising an acute bend made in the left parallel rib preparatory to passing at right angle on a line with said grater.

The reaming-wheel is mounted vertically, so as to be out of the way when the grater is in service, which has its operating-surface oppositely disposed to said wheel.

From the foregoing description it is obvious that by drawing the wheel around the rim of a pie the flutings thereon will impress a fancy crimp around the edge of the pie, while the concave flange will ream off the excess pastry. It is also apparent that by drawing the grating-plate spherically about a layer or other cake the burned and irregular edges will respond to the action of the rasp. It is further seen that the grating-plate is not alone confined to be useful in plumbing cakes, but by its formation is serviceable as a common grater.

Having described my invention, what I claim as new, and desire to secure by Letters Patent, is—

1. In a combination pastry-knife, comprising a longitudinally-disposed grating plane mounted upon a plurality of parallel ribs, a wheel laterally and rotatably mounted upon a prolongation of said ribs, and an interposing handle; all substantially as specified.

2. In a new article of manufacture, the combination of a longitudinal grating plane with a pair of parallel ribs, said ribs comprising a handle, and terminating, one in an upwardly-disposed flatwise coil, the other in a vertical bearing or boss, and a wheel rotatably mounted upon said boss, said wheel comprising a disk, and an integral transverse fluted portion, and an integral concave flange, and means for retaining said wheel upon its axis; all substantially as shown and described.

3. In a device of the class described, the combination of a grater with a plurality of ribs, a lateral spur on a plane with said grater, and a handle, a wheel vertically and rotatably mounted adjacent to said handle, said wheel comprising a transverse fluted portion and an integral concave flange, and means for retain-

ing said wheel; all substantially as and for the purpose specified.

FREDERICK A. TOBLER.

Witnesses:

MORRIS BRODY,

ARTHUR G. HULETT.