

No. 815,618.

PATENTED MAR. 20, 1906.

W. MUESER.  
MATERIALS OF CONSTRUCTION.

APPLICATION FILED APR. 20, 1905.

Fig: 1.




Fig: 2.




Fig: 3.




Fig: 4.




Fig: 5.




Fig: 6.




Fig: 7.





Fig: 8.



Witnesses  
Herman Meyer  
S. J. Cox

William Mueser Inventor  
By his Attorney William R. Baird



# UNITED STATES PATENT OFFICE.

WILLIAM MUESER, OF NEW YORK, N. Y.

## MATERIALS OF CONSTRUCTION.

No. 815,618.

Specification of Letters Patent.

Patented March 20, 1906.

Application filed April 20, 1905. Serial No. 256,579.

*To all whom it may concern:*

Be it known that I, WILLIAM MUESER, a citizen of the United States, residing at New York city, in the county of New York and State of New York, have invented certain new and useful Improvements in Materials of Construction, of which the following is a specification.

My invention relates to concrete-steel construction; and its novelty consists in the construction and adaptation of the parts, as will be more fully hereinafter pointed out.

In an application for Letters Patent of the United States filed by me October 13, 1904, Serial No. 228,342, I have shown and described a form of bar adapted to be embedded in concrete and to form a unitary structure with its concrete envelop, which bar comprises a longitudinal body provided with external spirally-arranged ribs whereby a resistance is afforded to the movement of the bar within the concrete envelop and yet at the same time the cross-sectional area of the bar in a plane at right angles to its longitudinal axis is substantially constant and of uniform character, and therefore the tensile strength of the bar and, what is more important, its elongation under stress is substantially uniform at all points along its length. The subject-matter of this present application comprises sundry modifications of this form of bar and has for its object the production of a bar which while varying somewhat in form and proportions from that described in the application referred to yet possesses the advantages of the bar, while at the same time it has other advantages peculiar to itself and may perhaps be more readily manufactured.

In the drawings, Figure 1 is a longitudinal elevation of a bar embodying my invention, showing the concrete envelop in section in two planes, the outline of the bar being shown dotted where it is concealed. Figs. 2, 3, and 4 are transverse right-angled sections on the planes of the lines 2 2, 3 3, and 4 4 in Fig. 1. Fig. 5 is a longitudinal elevation of the same bar, showing the modification or distortion which occurs in its shape when the two rolls through which it is formed do not exactly register while this operation is taking place; and Figs. 6, 7, and 8 are transverse right-angled sections on the planes of the lines 6 6, 7 7, and 8 8 in Fig. 5.

In the drawings, 20 represents a bar of metal, preferably iron or steel, which has

been rolled or otherwise fashioned into the forms shown. It comprises a longitudinal body 21 of symmetrical form and provided with external ribs 22, 23, 24, 25, 26, and 27, variously disposed around and projecting from the body 21. The body 21 is shown in the illustrations as a long cylinder; but it may as well have any polygonal shape in cross-section so long as its transverse sectional area is uniform at all points. The external ribs 22 to 27 are preferably made integral with the body of the bar. Their size contrasted with the body of the bar may be varied to suit different circumstances of use; but about the proportions shown in the drawings are usual and convenient. In cross-section each one of these ribs above the body of the bar resembles somewhat the shape of an ordinary tooth of toothed gearing. The ribs are each arranged symmetrically with reference to the longitudinal axis of the bar.

Referring specifically to Figs. 1 to 4, 22 and 23 are ribs spirally arranged around the body of the bar, wound in opposite directions, intersecting each other at regular intervals. Coincident with one-half of these points of intersection and arranged on diametrically opposite sides of the body 21 are two longitudinal ribs 24 24, which are substantially parallel with the central longitudinal axis of the bar. It will be seen that by this arrangement spaces roughly triangular in shape are left above the body 21 and between the ribs 22, 23, and 24, and other spaces roughly diamond-shaped are left between the ribs 22 and 23. These spaces are adapted to receive and do receive the concrete and assist in holding the bar and its envelop together after they are once in place.

The bar made as described has substantially the same cross-sectional area in all planes at right angles to its longitudinal axis. Theoretically at the angles formed by the intersection of any pair of spiral ribs this cross-sectional area would be slightly less than elsewhere, and in order to compensate for such decrease in area the angle of intersection is rounded out slightly and a little more metal is left at that point, so as to make the sectional area of the bar at that point uniform with that at the other points along its length. Another matter to be noted is that all oblique sections of the bar are greater in area than the transverse right-angled section, and consequently this area of uniform section represents the minimum strength of



the bar. It cannot twist and cannot pull out of the concrete, and the longitudinal ribs prevent it from rotating. How the cross-sectional area remains uniform is seen from an examination of Figs. 2, 3, and 4. In Fig. 2 it is seen that the ribs 22, 24, and 23 all coalesce to form at that point one projecting body. In Fig. 3 they are all shown as separated; but their combined area is the same, of course, as it was in Fig. 2. In Fig. 4 the ribs 23 and 22 are coalesced, while the ribs 24 are separate, in each of these figures their area being identical.

In Figs. 5, 6, 7, and 8 there is shown a modified form of the bar illustrated in the preceding figures. It happens in rolling the bar that sometimes the two rolls employed are not registered with sufficient care and the upper half of the bar is not in precise symmetrical relation with the lower half of the bar. In Fig. 5 this is shown in slightly-exaggerated form in order to make the situation clear. This non-registration of the rolls is apt to occur, and it has occurred frequently in every rolling-mill and is a difficulty which ironmasters have long sought to overcome, but have not overcome except at an expense entirely disproportionate to the result sought to be obtained. When a bar of my improved form, however, is employed, it makes no difference whether the rolls register or not, because the cross-sectional area of the bar at all points will be found to be the same, even although such registration does not take place. How this occurs is fully illustrated in Figs. 6, 7, and 8, showing cross-sections of the bar illustrated in Fig. 5. By these sections it will be seen that while the ribs 22, 23, and 24 are not at any place symmetrically arranged around the periphery of the intersecting circular, yet nevertheless their combined area is above the body of the bar, and consequently the cross-sectional area of the entire bar at all of these points is at all times the same.

Having in view the principles governing the construction of this form of concrete bar—namely, that the body of the bar shall be of symmetrical form and that the external ribs shall be symmetrically placed about such form—it will be relatively easy for those skilled in the art to which the invention relates to make other modifications in the form of the bar while still practicing the principles of the invention.

What I claim as new is—

1. A bar adapted to be used as a core to be embedded in concrete comprising a regularly-formed central body provided with external projecting ribs extending a substantial part of the length of the body, one of said ribs being substantially parallel with the longitudinal axis of the body, another rib extending diagonally around the body in one direction and another rib extending diagonally

around the body in the opposite direction and intersecting the other ribs.

2. A bar adapted to be used as a core to be embedded in concrete comprising a regularly-formed central body provided with external projecting ribs extending a substantial part of the length of the body, one of said ribs being substantially parallel with the longitudinal axis of the body, another rib extending diagonally around the body in one direction and a plurality of ribs extending diagonally around the body in the opposite direction and intersecting the other ribs.

3. A bar adapted to be used as a core to be embedded in concrete comprising a regularly-formed central body provided with external projecting ribs extending a substantial part of the length of the body, one of said ribs being substantially parallel with the longitudinal axis of the body, a plurality of ribs extending diagonally around the body in one direction and a plurality of ribs extending diagonally around the body in the opposite direction and intersecting the other ribs.

4. A bar adapted to be used as a core to be embedded in concrete comprising a regularly-formed central body provided with external projecting ribs extending a substantial part of the length of the body, a plurality of said ribs being substantially parallel with the longitudinal axis of the body, another rib extending diagonally around the body in one direction and another rib extending diagonally around the body in the opposite direction and intersecting the other ribs.

5. A bar adapted to be used as a core to be embedded in concrete comprising a regularly-formed central body provided with external projecting ribs extending a substantial part of the length of the body, a plurality of said ribs being substantially parallel with the longitudinal axis of the body, another rib extending diagonally around the body in one direction and a plurality of ribs extending diagonally around the body in the opposite direction and intersecting the other ribs.

6. A bar adapted to be used as a core to be embedded in concrete comprising a regularly-formed central body provided with external projecting ribs extending a substantial part of the length of the body, a plurality of ribs being substantially parallel with the longitudinal axis of the body, a plurality of ribs extending diagonally around the body in one direction and a plurality of ribs extending diagonally around the body in the opposite direction and intersecting the other ribs.

7. A bar adapted to be used as a core to be embedded in concrete comprising a regularly-formed central body provided with external projecting ribs extending a substantial part of the length of the body, one of said ribs being substantially parallel with the longitudinal axis of the body, and others of said ribs extending diagonally around the body



and intersecting each other and the longitudinal rib, the transverse section at the intersections of the ribs being increased to produce along the whole bar a uniform section  
5 throughout its length.

8. A bar adapted to be used as a core to be embedded in concrete comprising a regularly-formed central body provided with external projecting ribs extending a substantial  
10 part of the length of the body, a plurality of said ribs being substantially parallel with the longitudinal axis of the body, and others of

said ribs extending diagonally around the body and intersecting each other and the longitudinal ribs, the transverse section of the  
15 ribs being increased to produce along the whole bar a uniform section throughout its length.

In testimony whereof I affix my signature in presence of two witnesses.

WILLIAM MUESER.

Witnesses:

SAMUEL W. PRATT,  
WILLIAM R. BAIRD.