
No. 821,208.


PATENTED MAY 22, 1906.

F. VOSS.

BEER GLASS TRAY.

APPLICATION FILED NOV. 9, 1905.





William Schuk.

Friedrich Voss by his attorney Aunser Briene

## INITED STATES PATENT OFFICE.

FRIEDRICH VOSS, OF BURG, IN DITHMARSCHEN, GERMANY.

## BEER-GLASS TRAY.

No. 821,208.

Specification of Letters Patent.

Patented May 22, 1906.

Application filed November 9, 1905. Serial No. 286,458.

To all whom it may concern:

Be it known that I, FRIEDRICH Voss, a citizen of the German Empire, and a resident of Burg, in Dithmarschen, Province of Sleswick-Holstein, Germany, have invented certain new and useful Improvements in Beer-Glass Trays, of which the following is a specification.

This invention relates to a beer-glass tray which absorbs the drippings and conveys the same to a receiving-trough, so that cleanliness is insured.

In the accompanying drawings, Figure 1 is a plan, partly broken away, of my improved beer-glass tray. Fig. 2 is a cross-section on line AB, Fig. 1; and Fig. 3, a side elevation.

The letter a indicates a base-plate composed of a raised central section  $a^2$ , a downwardly-extending upright flange a', and an 20 upwardly-curved rim b. Thus there is formed between the parts a' and b an annular trough which surrounds the central raised section a<sup>2</sup> of the plate. The top of raised section  $a^2$  is provided with radial grooves f, com-25 municating with alined grooves f' of flange a'. The parts  $a^2 a'$  are covered by an absorbent cloth c, held to the plate a by means of a ring d, surrounding flange a'. In order to securely connect the parts, the ring d is pro-30 vided with an inwardly-extending bead d' opposite a corresponding recess of flange a'. Perforations o in ring  $\bar{d}$  permit the escape of the liquid, which trickles through the cloth and passes along the grooves ff' through the 35 openings o into the trough. If the cloth is

to be renewed, it may be readily detached by first removing the ring.

What I claim is—

1. In a beer-glass tray, a plate having a raised grooved section, an upright flange extending from the edge of said raised section to the bottom of the plate, and a rim surrounding said plate, combined with a cloth covering the raised section and the upright flange, and means for securing the cloth to 45 said flange, substantially as specified.

2. In a beer-glass tray, a plate having a raised grooved section, a grooved upright flange extending from the edge of said raised section to the bottom of the plate, and a rim surrounding said plate, combined with a cloth covering the raised section and the grooved flange, and a ring that engages the cloth and surrounds the grooved flange, substantially as specified.

3. In a beer-glass tray, a plate having a raised grooved section, a grooved upright flange extending from the edge of said raised section to the bottom of the plate, and a rim surrounding said plate, combined with a cloth 60 covering the raised section and the grooved flange, and a perforated ring that engages the cloth and surrounds the grooved flange, substantially as specified.

Signed by me at Hamburg, Germany, this 65 24th day of October, 1905.
FRIEDRICH VOSS.

Witnesses:

FRIEDRICH J. POTHS, OTTO W. HELLMRICH.