

No. 834,070.

PATENTED OCT. 23, 1906.

J. E. NUTTER.
ROCKING CHAIR.

APPLICATION FILED OCT. 16, 1905.

Fig. 1.





Fig. 2.



WITNESSES:

M. C. Abbott
E. E. Ellis

INVENTOR

John E. Nutter

BY

Munnis
ATTORNEYS

UNITED STATES PATENT OFFICE.

JOHN E. NUTTER, OF FERRIS, TEXAS.

ROCKING-CHAIR.

No. 834,070.

Specification of Letters Patent.

Patented Oct. 23, 1906.

Application filed October 16, 1905. Serial No. 282,981.

To all whom it may concern:

Be it known that I, JOHN E. NUTTER, a citizen of the United States, and a resident of Ferris, in the county of Ellis and State of Texas, have invented a new and Improved Rocking-Chair, of which the following is a full, clear, and exact description.

This invention relates to chairs; and it consists, substantially, in the details of construction and combinations of parts hereinafter more particularly described, and pointed out in the claims.

The invention has reference more especially to rocking-chairs; and one of the principal objects thereof is to provide a chair of this kind of an embodiment to overcome numerous disadvantages and objections encountered in the use of many other structures of the kind hitherto devised.

A further object is to provide a structure of the character specified which is simple in its embodiment and comparatively inexpensive to manufacture, besides being effective and reliable for its purposes and possessing the capacity for long and repeated service.

The above and additional objects are attained by means substantially such as are illustrated in the accompanying drawings, in which—

Figure 1 is a part-sectional side elevation of my improved rocking-chair on the line 1 1 of Fig. 2, the upper part of the back of the chair being broken off; and Fig. 2 is a transverse sectional view on the line 2 2 of Fig. 1.

Before proceeding with a more detailed description it may be stated that in the form of my improvements herein shown I employ a base for my improved rocking-chair of special construction, working upon which are specially-constructed rockers, between which and the seat of the chair are disposed special cushioning devices for the seat, and while I have herein represented my improvements in a certain preferred form it will be understood that I do not limit myself thereto in precise detail, since immaterial changes therein may be made coming within the scope of my invention.

Reference being had to the drawings by the designating characters thereon, 1 represents my improved rocking-chair in entirety, the same comprising parallel base members 2, disposed a suitable distance apart and preferably provided at the ends thereof with feet 3 for supporting said members a suitable height from the floor. These base members

are preferably provided on the upper surfaces thereof with wear-plates 4, upon which are mounted the rockers 5, which are herein shown as being substantially semicircular in form and which may be constructed of any suitable material. The curved edges of said rockers are provided with inturned flanges 6, constituting the operative members of the rockers, and which flanges are directly seated upon the said wear-plates 4. The upper or straight edges of the rockers, which are normally horizontally disposed, are also provided with inturned flanges or members 7, preferably of equal width with the said flanges or members 6, and the rockers are formed with corresponding sets of reversely-disposed arcuate slots 8, through each of which extends a headed pin or bolt 9, which is supported in suitable alining openings therefor in the upper ends of an outer vertical plate 10 and an inner vertical plate 11, the former being straight for its full length and lying directly adjacent to the outer face of the appropriate rocker with which the same is associated and the latter being straight for a portion of its height and bent inwardly and upwardly at 12 with the upper extremity 13 thereof lying in close proximity to the inner face of the said appropriate rocker, each duplicate set of said plates 10 and 11 being secured to one of the base members 2 of the structure in any suitable way, as by means of bolts 14 and nuts 15 thereon. It will thus be seen that when motion is imparted to the rockers 5 in the ordinary way the same will be evenly guided in their movements upon the wear-plates 4, and attention is called to the fact that the base members 2 are preferably connected together by suitable brace-rods 16, extending between the same at or near the ends thereof. Secured to the upper surfaces of the flanges 7 of the rockers by means of bolts 17 and nuts 18 thereon are strips 19 of any suitable material, (preferably wood,) the upper surfaces of which are flat and on which are suitable springs 20, which are secured in place in any suitable way, as by means of the same bolts 17 and nuts 18 by which the said strips 19 are secured to the said flanges or members 7 of the rockers.

The springs 20 are preferably herein shown as of bowed form with the ends thereof free or disconnected from each other, as at 21 in Fig. 1, the end portions of each of the said springs being secured to the under side of one of the side members 22 of the seat 23 of the

chair, said seat being herein shown as constructed of said side members 22 and intersecting front and rear members 24 and 25, respectively. The seat may be provided with
 5 any suitable form of cushion 26, if desired, a similar cushion 27 being provided for the back 28 of the chair also, if desired, and side arms 29 may be employed extending toward the front edge of the seat from the said back
 10 28 and supported in position by suitable ornamental posts 30. The seat 24 is further mounted at the rear thereof upon the inwardly-extending upper end portions 31 of duplicate reversely-disposed transverse
 15 springs 32, the lower end portions of which are preferably seated in notches therefor in the upper surfaces of the hereinbefore-mentioned strips 19 flushly with such surfaces and secured in place by the rearmost sets of
 20 the hereinbefore-mentioned bolts 17 and nuts 18 employed for securing in place the hereinbefore-mentioned springs 20, while the said upper end portions of the springs 32 are secured to the under side of the member 25 of
 25 the seat 23 by means of screws 33 or in any other suitable way.

To furnish rigidity to the structure above the base thereof, it is preferable also to connect the rockers together by means other
 30 than such as have been already referred to, and, as shown herein, the strips 19 are connected together by any desired number of transversely-extending rods 34, it being apparent that in this way the parts will all be
 35 held in the desired relationship to each other for enabling the rocking-chair to be used for all the ordinary purposes of such a structure. The movable portions of the structure are easy working and practically noiseless in op-
 40 eration, while they are capable of being readily taken apart for any purpose desired and again put together. The structure is also comparatively light, yet strong and stable for its purposes, all of which, it is thought, will be
 45 fully understood from the foregoing description.

Having thus described my invention, I

claim as new and desire to secure by Letters Patent—

1. A rocking-chair comprising a base com- 50
 posed of separated side members having flat upper faces provided with wear-plates, rockers comprising substantially semicircular plates having flanged peripheries, the curved
 55 edges of the rockers resting upon the wear-plates, each of said rockers being provided with a pair of oppositely-arranged arcuate slots, oppositely-arranged pairs of plates secured to the side members adjacent to the center thereof, bolts traversing the upper 60
 ends of the plates and the arcuate slots, and a seat connected with the rockers.

2. A rocking-chair comprising a base, composed of separated side members having flat upper faces, rockers comprising substantially 65
 semicircular plates having flanged peripheries, the curved edges of the rockers resting upon the side members, each of said rockers being provided with a pair of oppositely-arranged arcuate slots, oppositely-arranged 70
 pairs of plates secured to the side members adjacent to the centers thereof, bolts traversing the upper ends of the plates and the arcuate slots, and a seat connected with the rockers. 75

3. A rocking-chair comprising a base composed of separated side members having flat upper faces, rockers comprising substantially semicircular plates having flanged peripheries, the curved edges of the rockers resting 80
 upon the side members, a seat connected with the rockers, side plates secured to the respective side members of the base and a connection between the side plates and the rockers whereby to permit the movement of the rock- 85
 ers upon the side members of the base.

In testimony whereof I have signed my name to this specification in the presence of two subscribing witnesses.

JOHN E. NUTTER.

Witnesses:

HIREM LEMPY,
 CHARLEY S. NUTTER.