
J. L. BRYAN.

ATTACHMENT FOR PLATFORM SCALES.

APPLICATION FILED MAR. 2, 1906.



UNITED STATES PATENT OFFICE.

JAMES L. BRYAN, OF HOT SPRINGS, ARKANSAS.

ATTACHMENT FOR PLATFORM-SCALES.

No. 834,258.

Specification of Letters Patent.

Patented Oct. 30, 1906.

Application filed March 2, 1906. Serial No. 303,930.

To all whom it may concern:

Be it known that I, James L. Bryan, a citizen of the United States, residing at Hot Springs, in the county of Garland and State 5 of Arkansas, have invented a new and useful attachment for platform-scales to indicate to salesmen the amount of overweight of any article placed upon the said scales, of which

the following is a specification.

This invention is an improvement in platform and counter scales generally having a graduated beam or lever provided with sliding or adjustable weights; and the object of this invention is to enable the amount 15 weighed to be determined with the utmost exactness and the loss due to the overweight usually made on such scales, owing to the extent of vibration allowed the beam, to be obviated by providing a device which will show 20 exactly how many ounces overweight is on the scale when the beam lifts, thus enabling | the operator to remove the surplus until the exact weight of material is on the scale.

The invention will be fully understood 25 from the following description, and illustration in the accompanying drawings, which form part of this specification and which illustrate one practical form of the invention applied to a well-known kind of scale-beam.

3º In said drawings, Figure 1 is a side elevation of part of a scale, showing the scalebeam and the overweight-indicating device. Fig. 2 is a similar view showing the overweight-indicating device in section. Fig. 3 35 is a perspective view of the overweight devices. Fig. 4 is a perspective view of the overweight-indicating slide. Fig. 5 is an en-

larged section on line 5 5, Fig. 2.

In the drawings, 1 designates the frame of 40 an ordinary scale, of any suitable construction, having a standard 1a, to which is pivoted the beam 2, which is shown as a double beam, of ordinary construction, having adjustable weights 2^a 2^b thereon and provided with a weight-suspending device 3a on its free outer end, while its inner end is provided with counterpoises and connected to the scalelevers in the usual manner. (Not shown.)

The free end 3 of the beam is ordinarily | 50 guided in a slotted member 4, which may be constructed as illustrated in the drawings, and has a slot 4ª in its upper end above the

end3 of the beam and transverse to the opening in the part 4, through which the end 3 passes, and in this slot 4ª is guided the lower 55 end of an overweight-indicating slide 5, which may be of any suitable construction, but, as shown, has a T-shaped lower end, the arms of the T extending through the slots 4ª and bent, as at 5^a, so as to prevent lateral 60 displacement of the indicator-slide, and the stem of the slide projects or is adapted to project above the end of part 4 and may be guided between screws or pins 4b, attached to the upper end of part 4, as shown, the essen- 65 tial feature of the construction being the provision of a freely-movable indicator above the beam and in position to be actuated thereby when the beam rises. The slot 4ª terminates slightly above the top of part 3 70 when the beam is in its lowest position, with part 3 resting upon member 4, so that the slide will not be affected until the beam rises above the proper point for showing exact weight. Then as the end 3 rises above the ex- 75 act point it raises the indicator-slide and brings into view an index 6 thereon, which index is formed of transverse scores, numbered consecutively from top to bottom, so that as the slide rises the amounts of over- 80 weight can be read in ounces by the numbers appearing on the index-scale.

Figs. 1 and 2 show the beam at exactweight position. Fig. 3 shows the beam with one ounce overweight, indicated by the 85 scale-numeral appearing above the top of

member 4.

The simplicity and utility of the invention is obvious, and I do not care to be restricted to the precise form and construction of parts 90 shown, as it can be modified to suit different styles of scales.

Having thus described my invention, I ciaim---

1. The combination with a scale-beam, a 95 member having a slot through which the free end of the beam extends; and a guide-slot for an indicator-slide; with an overweight-indicator slide playing in said guide-slot in said member above the scale-beam and adapted to 100 be raised by excessive movement of the scalebeam, substantially as described.

2. In combination with a scale-beam, a member arranged adjacent the beam and having a guide-slot for an indicator-slide above the beam; with an indicator-slide loosely confined in said slot, and adapted to be raised by excessive upward movement of the beam, said slide being provided with an index-scale, for the purpose and substantially as described.

In testimony whereof I have signed my name to this specification in the presence of two subscribing witnesses.

JAMES L. BRYAN.

Witnesses:

GEO. G. LATTA, F. McKeogh.