



No. 836,745.

PATENTED NOV. 27, 1906.

M. J. FERREN.  
FURNACE ATTACHMENT.  
APPLICATION FILED JAN. 3, 1906.



Witnesses:  
*Jesse Hutchinson.*  
*Gertrude Roderick*

Inventor:  
*Myron J. Ferren*  
By *Hall & Kufner* Attorneys:

# UNITED STATES PATENT OFFICE.

MYRON J. FERREN, OF WASHINGTON, DISTRICT OF COLUMBIA.

## FURNACE ATTACHMENT.

No. 836,745.

Specification of Letters Patent.

Patented Nov. 27, 1906.

Application filed January 3, 1906. Serial No. 294,343.

*To all whom it may concern:*

Be it known that I, MYRON J. FERREN, a citizen of the United States, residing in the city of Washington, in the District of Columbia, have invented certain new and useful Improvements in Furnace Attachments, of which the following is a specification.

My invention relates to attachments for furnaces, more particularly the ordinary furnace used in heating systems installed in dwellings; and its object is to provide a device intended to be placed in coöperative connection with a furnace when ashes are to be drawn from the ash-pit thereof for causing any fumes, gases, dust, or the like which may tend to rise and intermingle with the surrounding atmosphere as the ashes are drawn and deposited in a receiving-receptacle, as a pan or scuttle, to pass into the path of the draft caused by the smoke-flue of the furnace—as, for instance, by passing into the fire-box of the furnace.

The invention includes an attachment which is particularly simple in construction and which is preferably normally disconnected from the furnace and is connected up therewith at the time ashes are to be removed from the ash-pit.

To this end the invention includes the combination and arrangement of parts to be hereinafter described, and particularly pointed out in the claims.

The invention is susceptible of varying embodiments; but for the purpose of fully disclosing the same it is deemed necessary to illustrate and describe only a single exemplification thereof.

In the accompanying drawings, Figure 1 shows the attachment in coöperative relation to a furnace, but a fragment on the latter being shown conventionally. Fig. 2 is a perspective view of the attachment.

In the accompanying drawings a fragment of a hot-air furnace is shown conventionally and is designated by A, and one embodiment of my attachment is shown in coöperative relation thereto at B.

The illustrated embodiment of the attachment comprises a substantially rectangular casing or body *a*, provided with a lateral discharge-opening *b* and with substantially aligning openings *c d* in its front and rear walls, respectively. The opening *b* is located at the

end of an offset portion or laterally-extending branch *e*, which is preferably of such size and contour as to snugly fit the walls of the fire-door opening of the furnace. The openings *c d* are located in such relation to the branch *e* that when the latter is in place in the opening *f* such opening *c d* will register with the door-opening *g* of the ash-pit.

The pan or like receptacle *h*, into which the ashes shoveled from the ash-pit is deposited, rests within the lower part of the attachment or occupies a position beneath the flue formed by the body *a*, so that the gases, dust, and the like arising by shoveling the ashes from the ash-pit into the receptacle will pass up through said flue into the fire-chamber of the stove and out through the ordinary smoke-flue. It will be understood, of course, that the damper on the smoke-flue will be opened to the full extent before the ashes are drawn to insure a good draft through the attachment.

The construction and operation of the invention will be fully understood from the foregoing description, and it will be appreciated that varying changes may be made from the illustrated form of the invention without departing from the spirit and scope thereof.

I claim—

1. The combination with a furnace having a door-opening leading into the fire-chamber, and a second door-opening beneath the first leading into the ash-pit, of a portable casing having a passage-way leading from its upper portion designed to register with the fire-door opening and discharge therein and having additional openings in its lower portion in its front and rear walls designed to register with the ash-pit opening, substantially as described.

2. A furnace attachment comprising a light portable casing normally out of connection with the furnace and intended to be placed into coöperative relation therewith when ashes are to be drawn from the ash-pit of the furnace, said casing having an offset portion at its upper end, designed to fit within the door-opening of the fire-chamber of the furnace and having openings in its front and rear walls registering with the door-opening leading into the ash-pit of the furnace whereby a receptacle may be placed in front of the furnace within the casing and ashes withdrawn from the ash-pit and dumped there-



into and whereby the dust and fumes arising from the ashes so withdrawn will pass upwardly through said casing into the fire-chamber of the furnace, substantially as described.

5. In testimony whereof I have hereunto signed my name, in the presence of two at-

testing witnesses, at Washington, District of Columbia, this 30th day of December, 1905.

MYRON J. FERREN.

Witnesses:

HENRY E. COOPER,  
GERTRUDE RODERICK.