



No. 840,282.

PATENTED JAN. 1, 1907.

B. ADAMOWICZ.
CURTAIN POLE.

APPLICATION FILED JULY 12, 1904. RENEWED JULY 21, 1906.



Witnesses:
H B Hallock.

Inventor:
Benedict Adamowicz

By *W. P. Williams*
Att'y.

UNITED STATES PATENT OFFICE.

BENEDICT ADAMOWICZ, OF PHILADELPHIA, PENNSYLVANIA.

CURTAIN-POLE.

No. 840,282.

Specification of Letters Patent

Patented Jan. 1, 1907.

Application filed July 12, 1904. Renewed July 21, 1906. Serial No. 327,111.

To all whom it may concern:

Be it known that I, BENEDICT ADAMOWICZ, a subject of the Czar of Russia, residing at Philadelphia, county of Philadelphia, and State of Pennsylvania, have invented a certain new and useful Improvement in Curtain-Poles, of which the following is a specification.

My invention relates to a new and useful improvement in curtain-poles, and has for its object to provide a new and improved curtain-pole by which a curtain may be suspended from said pole without passing over the pole and without pinning the curtain, and said curtain will be held securely in place, but may be easily removed from the pole at any time desired, and a further object of my invention is to provide improved hangers for said pole, said hangers being so constructed that they may be placed in contact with the pole at any point desired.

With these ends in view this invention consists in the details of construction and combination of elements hereinafter set forth and then specifically designated by the claim.

In order that those skilled in the art to which this invention appertains may understand how to make and use the same, the construction and operation will now be described in detail, referring to the accompanying drawings, forming a part of this specification, in which—

Figure 1 is a cross-section through my improved pole; Fig. 2, a perspective view of the pole, showing the manner of securing the curtain thereto.

My improved curtain-pole, in fact, consists of two poles, one inside of the other.

In the drawings, A represents the pole proper, which may be suspended by securing at each end or by means of the hangers B. This pole is provided with an opening C, formed longitudinally therethrough. A longitudinal slot D, narrower than the opening C, extends from said opening to the interior of the pole, through the lower side thereof. E is a small pole or rod smaller than the opening C, but larger in diameter than the width of the slot D. The curtain is adapted to be placed around the pole or rod D, and then the rod, with the curtain thereon, is slipped into the opening C, the curtain hanging downward through the slot D, and the friction between

the pole E and the plate A will prevent the curtain from slipping, and the more the curtain is pulled upon the greater will be the friction generated between the two poles, binding the curtain in between them. Therefore by this means the curtain can be adjusted very easily and will be held in place securely after being once adjusted and may be easily removed at any time desired, and by doing away entirely with pins or other fastenings the curtain is not mutilated at all.

The hanger B entirely surrounds the pole A except for a short distance at the lower end and the two ends of the surrounding portion of the hanger terminating each side of the slot D. Therefore said hangers can be secured at any point desired and will not interfere with the hanging of the curtain. The hanger B is formed of a single piece of wire bent upon itself midway its length to form a split loop adapted to embrace the pole. The free portions of the wire are twisted around themselves near their ends and terminate in diverging portions provided with eyes, by means of which the hanger is secured in position. A hanger constructed in this manner permits the pole to be sprung into position, and thereby obviates the labor and delay of sliding the pole into position, as is customary in devices of this character.

Of course I do not wish to be limited to the exact construction here shown, as slight modifications could be made without departing from the spirit of my invention.

Having thus fully described my invention, what I claim as new and useful is—

In combination with a pole provided with a longitudinal opening formed therethrough connected with the exterior of a pole by a longitudinal slot, and a smaller pole around which the curtain is placed lying within the opening of the larger pole; a hanger for the said larger pole, said hanger comprising a single piece of wire bent upon itself to form a split ring, the free portions of the wire being twisted one around the other and terminating in eyes, as and for the purpose set forth.

In testimony whereof I have hereunto affixed my signature in the presence of two subscribing witnesses.

BENEDICT ADAMOWICZ.

Witnesses:

HERMAN F. VOSS,
ADOLF C. VOSS.