

No. 840,735.

PATENTED JAN. 8, 1907.

F. H. ARNOLD.
SAFETY RAZOR.

APPLICATION FILED SEPT. 16, 1906.

Fig. 1




Fig. 2




Fig. 3





Fig. 4



Fred. H. Arnold Inventor

Witnesses

Chas. A. Davis

J. O. Kelly

By

E. J. Kelly

Attorney

UNITED STATES PATENT OFFICE.

FREDERICK H. ARNOLD, OF READING, PENNSYLVANIA.

SAFETY-RAZOR.

No. 840,735.

Specification of Letters Patent.

Patented Jan. 8, 1907.

Application filed September 15, 1906. Serial No. 334,785.

To all whom it may concern:

Be it known that I, FREDERICK H. ARNOLD, a citizen of the United States, residing at Reading, in the county of Berks and State of Pennsylvania, have invented certain new and useful Improvements in Safety-Razors, of which the following is a specification.

This invention relates to improvements in safety-razors of the class in which the blade is arranged to lie on the same plane and in line with the handle.

The object of the present invention is to provide a razor of simple and cheap construction, having but few parts, and capable of being used with either hand, provision being made for cutting from both sides of the guard-plate.

The invention consists of a single-piece holder comprising a handle and guard and a slotted double-edge blade capable of being quickly and accurately placed in position.

The invention is more fully described in the following specification and clearly illustrated in the accompanying drawings, in which—

Figure 1 is a plan view, and Fig. 2 a side view, of my razor. Fig. 3 is a detail view of the blade, and Fig. 4 is a detail in section of the clamping device.

The entire holder comprises a handle 1 and a guard 2, formed integral therewith and having the usual teeth 3. The guard is formed with the usual positioning-pins 3^a, one near either end, and it has loosely mounted in its center a pin 4, which passes through the plate. This pin projects beyond the upper face of the guard and carries a curved spring 5 and a thumb-piece 6 at its top. The ends of the spring bear upon the upper face of the guard, and both the spring and thumb-piece are of the same width.

The numeral 7 designates the blade, which is of thin metal and formed with a central elongated slot 8 and a small perforation near either end. The slot 8 is slightly greater in width and length than the thumb-piece and spring. The blade is placed in position on the guard, the thumb-piece and spring passing easily through the slot 8. The pins 3^a will engage the perforations in the blade, thus insuring its being properly placed, and the thumb-piece 6 is turned slightly, carrying with it the spring 5, which rides up onto the upper face of the blade and securely holds it against the face of the guard. To insure its easy engagement, the inner wall of the slot 8 is tapered, as shown at 8^a, to permit the ends of the spring to ride up onto the surface more easily. It is evident that the blade may be reversed on the guard, if desired.

Having thus fully described my invention, what I claim, and desire to secure by Letters Patent, is—

In a safety-razor a holder having a guard formed with positioning-pins, a pin loosely mounted in the center thereof, a spring secured to and moving with said pin, a thumb-piece secured to the upper end of said pin in combination with a blade of thin metal having two cutting edges and a central elongated slot adapted to engage said spring and perforations adapted to engage said positioning-pins.

In testimony whereof I have signed my name to this specification in the presence of two subscribing witnesses.

FREDERICK H. ARNOLD.

Witnesses:

M. C. KREIDER,
ED. A. KELLY.