




No. 844,226.

PATENTED FEB. 12, 1907.

J. C. WRIGHT.  
FAUCET.

APPLICATION FILED JAN. 8, 1906.



WITNESSES

*T. L. Krock*  
*Rea P. Wright*

INVENTOR

*J. C. Wright,*

By *O. Mearns & Brock*  
*Attys.*



# UNITED STATES PATENT OFFICE.

JAMES C. WRIGHT, OF COLORADO SPRINGS, COLORADO, ASSIGNOR OF ONE-HALF TO JAMES C. RAWLINGS, OF COLORADO SPRINGS, COLORADO.

## FAUCET.

No. 844,226.

Specification of Letters Patent.

Patented Feb. 12, 1907.

Application filed January 8, 1906. Serial No. 295,106.

*To all whom it may concern:*

Be it known that I, JAMES C. WRIGHT, a citizen of the United States, residing at Colorado Springs, in the county of El Paso and State of Colorado, have invented a new and useful Improvement in Faucets, of which the following is a specification.

My invention relates to certain new and useful improvements in faucets, and has for its object to provide a faucet that is especially adapted to be used in dispensing any heavy or thick liquids, such as molasses.

Another object of my invention is to provide a faucet which is very simple and cheap in construction and one which is very effective in use.

A further object of my invention is to provide a faucet with a weighing attachment, so that the vessel adapted to receive the liquid can be placed on a platform and the faucet opened and closed automatically when the required amount is secured in the vessel.

Another object of my invention is to provide certain new and improved tripper means in connection with the turning plug and scale, so that when the required amount of liquid has been secured in the vessel it will be automatically cut off.

With these objects in view the invention consists of the novel features of construction and combination and arrangement of parts, hereinafter fully described, and pointed out in the claims.

In the drawings forming a part of this specification, Figure 1 is a perspective view of the faucet; showing it attached to a barrel. Fig. 2 is a longitudinal section of the same. Fig. 3 is a detail view of the turning plug and handle.

Referring to the drawings, A indicates the tube or body portion of the faucet, adapted to be secured in the barrel B and is provided with a transverse opening A', in which a turning plug C, provided with a passage C', is mounted. One end of the plug is provided with a handle C<sup>2</sup> carrying a coil-spring C<sup>3</sup> at one end, the other end of which is connected to the faucet. A pin A<sup>2</sup> is arranged on the faucet adjacent the opening A' and is adapted to form a stop for the handle to prevent it from turning too far. The other end of the plug C is provided with a reduced threaded portion, on which a cam-washer C<sup>4</sup> is secured by a nut. The other end of the

body portion of the faucet is provided with an upwardly-extending portion A<sup>3</sup>, provided with outwardly-extending lugs A<sup>4</sup>, A<sup>5</sup>, and A<sup>6</sup>. The lugs A<sup>5</sup> and A<sup>6</sup> are provided with openings through which a bar D, carrying a cross-bar E, is adapted to work. An opening D' is formed in the upper end of the bar D, through which a link D<sup>2</sup> is adapted to be connected. The other end of the link is connected to the end of a scale-beam F, provided with projecting pins F', over which a hanger F<sup>2</sup> is adapted to fit, supported by a hook carried by the lug A<sup>4</sup>. The bar F is provided with an ordinary weight F<sup>3</sup>. A platform G is supported below the bar E by bars G', upon which the vessels are adapted to be placed. A pawl H is pivotally mounted on the side of the body of the faucet and is adapted to be held in engagement with the notch of the cam-washer C<sup>4</sup> by a coil-spring H'. The upper end of the pawl is provided with a notch adapted to be engaged by a pin D<sup>3</sup>, carried by the bar D, and throw the pawl out of engagement with the plug, allowing the spring connecting to the handle to close the same.

The operation is as follows: A vessel is placed on the platform and the weight adjusted on the beam to the amount desired. The plug is then turned by the handle until the notch of the washer is engaged by the pawl, which will allow the liquid to pass out until the required amount has been received in the vessel, which will trip the pawl and allow the spring connected to the handle to close the same.

Having thus fully described my invention, what I claim as new, and desire to secure by Letters Patent, is—

1. The combination with a faucet, provided with a scale-beam, of a bar carried by said beam supporting a platform, a latch pivoted to said faucet, means carried by the turning plug of the faucet adapted to be engaged by said latch and a pin carried by the platform-supporting bar adapted to engage said latch, for the purpose described.

2. The combination with a faucet provided with a spring-actuated turning plug, of a weighing-scale carried by said faucet, and tripping means pivoted to the faucet adapted to be engaged by the scale, for the purpose described.

3. The combination with a faucet, pro-



vided with a spring-actuated turning plug carrying a notched washer, of a weighing-scale carried by said faucet, and a pawl held in engagement with the notched washer of the plug adapted to be engaged by the scale, 5 for the purpose described.

4. The combination with a faucet provided with a spring-actuated turning plug carrying a notched washer, of a spring-actuated pawl pivoted to said faucet adapted to 10 engage the notch in said washer, a scale-beam mounted on said faucet carrying a bar supporting a platform and means connected to the bar for engaging said pawl, for the purpose described. 15

5. The combination with a faucet provided with a spring-actuated turning plug carrying a notched washer, of a spring-actuated pawl pivoted to said faucet adapted to 20 engage the notch-washer, an upwardly-extending portion formed on the outer end of the faucet, a bar slidably mounted on said

portion, a platform connected to said bar, a scale-beam mounted on the upper end of said portion and connected to said bar, a weight 25 carried by said beam, and a pin carried by said bar, adapted to engage said pawl, for the purpose described.

6. The combination with a faucet, provided with a turning plug, of a notched 30 washer secured on one end of said plug, an arm secured on the other end of said plug, a spring connecting the lower end of said arm to said faucet carrying a bar, a scale-beam mounted on said faucet, supporting a 35 platform, a spring-actuated pawl pivoted to said faucet adapted to engage said washer and a pin carried by the bar adapted to engage said pawl, for the purpose described.

JAMES C. WRIGHT.

Witnesses:

F. E. KOHLER,

FRANK J. WATERS