
A. WAGNER.
HOOK FOR GARMENTS.
APPLICATION FILED JULY 24, 1906.



UNITED STATES PATENT OFFICI

ALBERT WAGNER, OF ELKHORN, PENNSYLVANIA.

HOOK FOR GARMENTS.

No. 844,428,

Specification of Letters Patent.

Patented Feb. 19, 1907.

Application filed July 24, 1908. Serial No. 327,519.

To all whom it may concern:

Be it known that I, ALBERT WAGNER, a citizen of the United States of America, residing at Elkhorn, in the county of Allegheny and State of Pennsylvania, have invented certain new and useful Improvements in Hooks for Garments, of which the following is a specification, reference being had therein to the accompanying drawings.

This invention relates to a combined trousers-hook and belt-support; and its object is to provide a simple and effective device for retaining a trousers-belt in position.

The invention consists of a trousers-hook 15 provided with a projecting perforated lug adapted to receive a buckle-tongue, and the construction of the improvement will be more fully described hereinafter in connection with the accompanying drawings, which

30 form a part of this specification, and its novel features will be defined in the appended claims.

In the drawings, Figure 1 is a perspective view of the improved belt-support shown in 25 connection with a belt and pair of trousers. Fig. 2 is a perspective view of the same detached, showing its outer side; and Fig. 3 is a similar view showing the reverse side of the device.

The improvement comprises a metallic plate having a body portion 1, adapted to be secured to a trousers-waistband, as shown, by means of perforated lugs 2, a hook 3, and an outwardly-bent lug 4, formed with an open-'5 ing 5.

It will be observed that the improvement, which consists of the perforated lug 4, adds nothing to the cost of the trousers-hook, as said lug is merely the cut-away portion of the

hook which is ordinarily severed from the 40 blank. I retain this cut-away portion, perforate it, and bend it outward to present it in rosition to receive the tongue 6 of the belt-buckle 7.

The utility of the improvement is illus- 45 trated in Fig. 1. After the belt 8 is passed through the retaining-straps 9 of the trousers the buckle-tongue 6 is inserted into the open-. ing in the lug 4, after which the tongue is, passed through one of the holes in the belt, 50 as shown. Thus the belt is supported in proper rosition and prevented from dropping down or working up above the waistband.

The device is simple and inexpensive and, as above explained, may be readily stamped 55 out of sheet metal.

What I claim, and desire to secure by Letters Patent, is-

1. A trousers-hook having an integral outwardly-projecting perforated lug to receive a 60 buckle-tongue.

2. A combination trousers-hook and beltsupport comprising a body portion adapted to be attached to a waistband, an inwardlybent hook, and an outwardly-bent perforated 65 lug.

3. A combination trousers-hook and beltsupport, comprising a body portion, an inwardly-bent hook, and a perforated lug formed by cutting a portion of the metal of 70 the hock and bending it outward in position to be engaged by the tongue of a belt-buckle.

In testimony whereof I affix my signature in the presence of two witnesses. ALBERT WAGNER.

Witnesses:

MAX H. SROLOVITZ, E. E. Potter.