

No. 844,679.

PATENTED FEB. 19, 1907.

J. D. KARLE.  
GARMENT CLASP.  
APPLICATION FILED APR. 19, 1906.

Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.





Fig. 7.



WITNESSES

H. A. Lamb.  
M. T. Longden

INVENTOR

J. D. Karle

BY

*J. D. Karle*  
ATTORNEY



# UNITED STATES PATENT OFFICE.

JOHN D. KARLE, OF BRIDGEPORT, CONNECTICUT.

## GARMENT-CLASP.

No. 844,679.

Specification of Letters Patent.

Patented Feb. 19, 1907.

Application filed April 19, 1906. Serial No. 312,590.

*To all whom it may concern:*

Be it known that I, JOHN D. KARLE, a citizen of the United States, residing at Bridgeport, in the county of Fairfield and State of Connecticut, have invented certain new and useful Improvements in Garment-Clasps; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same.

My invention relates to garment-clasps, and consists in certain arrangements of parts and combinations of parts, such as will be hereinafter fully explained and then particularly pointed out in the claims which conclude this application.

In the accompanying drawings, Figure 1 is a side elevation of my improved clasp with the clamping-loop open, and Fig. 2 a vertical longitudinal section thereof; Fig. 3, a side elevation of said clasp with the clamping-loop closed, and Fig. 4 a central vertical longitudinal section thereof; Fig. 5, a plan view of the clasp with the clamping-loop open; Fig. 6, a detail perspective view of the clamping-loop equipped with a rubber covering; and Fig. 7 a view similar to Fig. 4, but showing a modification of my improvement in which the clamping-lever is thrown rearwardly to effect the closing of the clamping-loop.

Similar numbers of reference denote like parts in the several figures of the drawing.

1 is a base-plate supporting at its outer extremity a stud 2, which may be made of any suitable material, preferably rubber, and which is secured to the base-plate in any ordinary manner.

3 is a cross-pin whose ends are secured within ears 4, that project upwardly from the rear portion of the plate 1, and 5 is the clamping-loop, which is made of wire and has depressed portions 6 near its rear end, which portions extend beneath the pin 3, the forward extremity of this loop being enlarged to form a circular portion 7, capable of fitting snugly over the stud 2. The extreme rear ends of the loop 5 immediately beyond the pin 3 are bent at right angles toward each other at 8, as shown more particularly at Fig. 6, and these ends are passed freely within the heel portion of a cam 9, so that the latter has a free swinging action around said ends as a pivotal point, said cam being provided with a lever 10.

11 is a sheet-metal spring having a de-

pressed portion 12, which fits snugly beneath the pin 3, intermediate of the sides of the clamping-loop 5, the forward extremity of this spring resting upon the plate 1, while the rear extremity of said spring is reduced in width and rests upon the ends 8 of the clamping-loop between the sides of the cam 9, the function of this spring being to normally elevate the clamping-loop, so that the portion 7 is elevated above the stud 2 for the insertion of the fabric to be clamped when the lever 10 is thrown rearwardly, as shown at Figs. 1, 2, and 5. Neither the clamping-loop 5 or the spring 11 has actual connection with the means employed for confining these elements in position, and therefore there can be no cramping or buckling of these elements, since they are, so to speak, loosely confined to the plate 1, in contradistinction to all other garment-clasps in which the similar elements either actually surround a pivotal point or are otherwise directly connected to the base-plate. It will be obvious, therefore, that the loop 5 can be elevated or lowered with a rocking movement.

The operation of my improvement is as follows: The garment is placed over the stud 2 and the handle of the cam-lever swung forward to the position shown at Figs. 3 and 4, thereby securely clamping the garment between said stud and the forward end of the loop 5.

In the event that the loop 5 is provided with a rubber covering 13, as shown at Fig. 6, it will be clear that the garment will be held between rubber surfaces, and this is very desirable in devices of this description, although I do not limit myself to the provision of rubber.

It will be observed that neither the clamping-loop nor the spring element is actually pivoted, although they are pivotally confined, and this effectually prevents the cramping of these parts and gives them greater efficiency in the performance of their functions. Furthermore, it will be clear that the cross-pin 3 is practically a continuation of the ears 4, in that the two are rigidly connected together, so as to form a tie-bar or sort of bail for the purpose of confining the loop to the plate.

Referring to the modification shown at Fig. 7 of the drawings, it will be noted that the forward end of the cam 9 is pivoted around the rear ends of the loop 5, whereby when the clamping-lever is thrown rear-



wardly the rear ends of the clamping-loop will be elevated, thereby causing the forward portion of the clamping-lever to assume its closed or clamping position. I therefore do  
 5 not wish to be limited to the pivoting of either the heel or front ends of the cam around the rear ends of the loop 5, since both of these constructions are fully within my invention. This construction (shown at  
 10 Fig. 7) is particularly well adapted for a woman's use on a stocking-supporter, since the end of the lever 10 presents no projection on which a woman's clothing could catch, and this is not true of the construc-  
 15 tion shown in the other figures of the drawings, as will be apparent from Figs. 3 and 4, where the bent-up end of the lever 10 does actually present a hook-like projection which would be very apt to catch in a woman's  
 20 clothing. The construction shown in Figs. 1 to 5, inclusive, would probably be preferred as a clasp on the end of a hose-supporter for a man.

Having thus described my invention, what  
 25 I claim as new, and desire to secure by Letters Patent, is—

1. In a garment-clasp, the combination of the base-plate supporting a stud at its forward end and a cross-pin near its rear end,  
 30 the clamping-loop pivotally confined beneath said cross-pin and having its rear ends bent toward each other, the cam-lever around said rear ends, and the spring element whereby said loop is normally elevated.

35 2. In a garment-clasp, the combination of a base-plate carrying a stud at its outer end and provided near its rear end with upwardly-projecting ears, the cross-pin having its ends secured within these ears, the clamping-loop  
 40 having depressed portions near its rear end which fit snugly beneath said pin, the cam-lever pivoted to the rear end of said loop, and the sheet-metal spring having a depressed portion which fits beneath said pin interme-  
 45 diate of the sides of said loop and whose forward extremity rests upon said plate while its rear extremity bears against the rear end of said loop.

50 3. In a garment-clasp, the combination of the base-plate supporting at its front end a stud and having ears which project upwardly on opposite sides of its rear portion, the pin

having its ends secured within said ears, the clamping-loop having its front portion con-  
 formed to said stud and provided with de- 55 pressed portions near its rear end which portions fit snugly beneath said pin and having its rear ends bent toward each other at right angles, the cam-lever pivoted around  
 60 said ends, and the sheet-metal spring having a depressed portion which fits beneath said pin intermediate of the sides of said loop, the forward end of said spring resting against the base-plate while the rear end bears upon the  
 65 rear bent ends of said loop.

4. In a garment-clasp, the combination of the base-plate supporting a stud at its forward end, the clamping-loop pivotally con-  
 fined to said plate beneath a cross-piece which is supported by said plate near its rear 70 end, the cam-lever carried by the rear end of the clamping-loop immediately above said plate, and the spring element whereby said loop is normally elevated.

5. In a garment-clasp, the combination of 75 a base-plate supporting at its forward end a stud, a clamping-loop loosely confined to said plate and capable of a free rocking movement, means carried by said plate for preventing displacement of said loop, the cam- 80 lever pivoted to the rear end of said loop immediately above said plate, and a spring bearing against said loop whereby the forward end of the latter is normally elevated.

6. In a garment-clasp, the combination of 85 a base-plate carrying a stud at its outer end, the clamping-loop having depressed portions near its rear end, means carried by said plate and extending immediately above said depressed portions of the loop whereby the 90 latter is confined to said plate and is capable of a rocking movement, the cam-lever pivoted to the rear end of said loop immediately above said plate, and the spring element bearing against said clamping-loop to cause 95 the latter to normally assume an elevated position.

In testimony whereof I affix my signature in presence of two witnesses.

JOHN D. KARLE.

Witnesses:

F. W. SMITH, Jr.,  
 M. T. LONGDEN.