

E. A. WILCOX. DISPLAY CABINET. APPLICATION FILED JULY 16, 1900.

2 SHEETS-SHEET 1.



E. A. WILCOX. DISPLAY CABINET. APPLICATION FILED JULY 16, 1906.



UNITED STATES PATENT OFFICE.

ELIJAH ABBOTT WILCOX, OF NEW YORK, N. Y.

DISPLAY-CABINET.

No. 857,265.

Specification of Letters Patent.

Patented June 18, 1907.

Application filed July 16, 1906. Serial No. 326,510.

To all whom it may concern:

Be it known that I, Elijah Abbott Wilcox, a citizen of the United States, residing at New York city, county and State of New York, have invented certain new and useful Improvements in Display-Cabinets, of which the following is a specification.

My invention consists in a display cabinet, comprising a casing which may be opened and closed and a series of pivoted display frames, together with other parts, all of which will be specifically enumerated in the

specification.

The object of my invention is to provide
a display cabinet wherein various types of
merchandise may be readily shown, the display frames being easily removed or interchanged to replace or change the merchandise displayed, the cabinet as a whole providing means for protecting the merchandise
from dust, moisture, etc.

The accompanying drawings will serve to

illustrate my invention.

Figure 1 is a front elevation. Fig. 2 is a horizontal section through Fig. 1. Fig. 3 is a vertical section through Fig. 1. Fig. 4 is a horizontal section through Fig. 1 showing the cabinet open. Fig. 5, is a modification showing a double cabinet. Fig. 6 is a horizontal section through Fig. 5. Fig. 7 and 8 are respectively views of the top and bottom supporting means for the frames.

Similar figures indicate like parts.

In the drawings: 1 indicates the front or movable section of the cabinet and 2 the back or fixed section. The movable section 1 is made up of a front 1, sides 4, 5, base 6, and top 7, and the fixed section 2, of a back 8, sides 9, 10, base 11 and top 12. The fixed and movable sections are hinged together at 3, and arranged over the tops 7, 12, is a series of electric lights, 13, 14, respectively arranged in staggered relation, each light registering with a space between two lights upon the other section.

In the rear and above the lines of lights 13, 14, are two reflecting surfaces, 15, 16, which operate to reflect upon the merchandise attached to the display frames, within the fixed and movable sections. At one side and at the top are bracket supports, 17, upon which are arranged pivoted stud pins, 18, Fig. 7, and in the fixed and movable sections at the bottom at one side are brackets, 19,

55 carrying fixed stud pins 21.

Carried in the brackets are the display frames

20, which may be of any construction, preferably a rectangular metal frame, 22, having a flexible center, 23, upon which the goods to be displayed may be pinned or otherwise fas- 60 tened. The upper and inner edge of the frame is bent, as shown in Fig. 7, to form a socket, 24, to receive the stud 18, and the lower end of the frame is provided with an extension, 25, which is provided with an extension, 25, which is provided with an 65 aperture to fit over the stud pin 21. Any other means of supporting the swinging frames may be employed.

26 represents a pivoted strap for holding the cabinet open. Any suitable device may 70

be employed.

Secured to the outer edge of the movable section of the cabinet is a depending arm, 27, on the lower end of which is a caster, 28. This arm and caster serve to support and 75 guide the movable section, when rotated inward or outward. Located in the bottom of the cabinet is a drawer 29, which drawer may be dispensed with.

In Figs. 5 and 6, the construction of the 80 parts is the same as that described, except that the cabinet is double instead of single.

Having thus described my invention, I claim:

1. A display cabinet comprising a fixed 35 section and a movable section, supporting brackets in each section, the supporting faces of said brackets being disposed at substantially right angles to each other when the cabinet is closed, and a series of display 90 frames carried by said brackets, whereby when the sections are opened at right angles the inner ends of the frames will be substantially in line.

2. A display cabinet divided vertically 95 into a movable front section and a back section, the said sections being hinged to each other along the dividing line of one side, and a plurality of swinging vertically disposed display frames pivotally mounted within 100 said cabinet so that they may be placed parallel to either section, a part of said frames being attached to each section, means for supporting the front section of said cabinet when open, and a folding stop attached to 105 each section of the cabinet and which determines the point to which the movable front section may be moved from the back section.

3. A display cabinet divided vertically into a movable front section and a back section, the said sections being hinged to each other along the dividing line of one side, and

a plurality of swinging vertically disposed display frames pivotally mounted within said cabinet, a part of said frames being attached on a diagonal line across each section, and a folding stop attached to each section of the cabinet and which determines the point to which the movable front section may be moved from the back section, whereby the sections may stop automatically with the inner ends of the frames in line.

4. A display cabinet divided vertically into two sections hinged to each other at the division line of one side, lines of lights upon the top of each section, and reflectors adapted to throw light into the interior of said cabi-

net when open.

5. A display cabinet divided vertically into two sections, hinged to each other at the division line of one side, lines of light upon the top of each section, and two reflecting devices therefor, which operate to throw light

6. A display cabinet divided vertically into two sections, hinged to each other at the division line of one side, a plurality of vertically disposed display frames attached to each portion of one side, and lines of lights upon the top of each section, and two reflecting devices therefor, which operate to throw light upon the display frames.

7. A display cabinet divided vertically

into a movable front section and a back section, the said sections being hinged to each other along the dividing line of one side, a plurality of swinging vertically disposed dis- 35 play frames pivotally mounted within said cabinet, a part of said frames being attached to each section, a folding stop attached to each section of the cabinet, which determines the point to which the movable front 40 section may be moved from the back section, means for supporting the front section of said cabinet when open, said means consisting of a wheel attached to said movable front section and adapted to run upon the means sup- 45 porting the base of said cabinet, lines of lights upon the top of each section, and two reflecting devices for said lines of light adapted to throw light upon the said display frames.

8. A display cabinet divided vertically 50 into two hinged sections, lighting devices carried by each section, and devices co-operating with said lighting devices to constitute reflectors when the cabinet is open and a closed housing when the cabinet is closed. 55

In testimony whereof, I affix my signature,

in the presence of two witnesses.

ELIJAH ABBOTT WILCOX.

Witnesses:

M. Turner, Frederick A. Blount.