






No. 857,507.

PATENTED JUNE 18, 1907.

H. W. WILSON.
SLEEPING BAG.

APPLICATION FILED NOV. 10, 1906.



WITNESSES
R. C. Abbott
[Signature]

INVENTOR
Herbert W. Wilson
BY [Signature]
ATTORNEYS

UNITED STATES PATENT OFFICE.

HERBERT WALN WILSON, OF SPRINGFIELD, SOUTH DAKOTA.

SLEEPING-BAG.

No. 857,507.

Specification of Letters Patent.

Patented June 18, 1907.

Application filed November 10, 1906. Serial No. 342,802.

To all whom it may concern:

Be it known that I, HERBERT WALN WILSON, a citizen of the United States, and a resident of Springfield, in the county of Bonhomme and State of South Dakota, have invented a new and Improved Sleeping-Bag, of which the following is a full, clear, and exact description.

This invention is an improvement in sleeping bags, more especially designed for children, combined with means for retaining the bag in place on the mattress of the bed and holding the child in the bag in proper position.

The preferred form of bag, as constructed, is open at both ends, with one side thereof at the upper end extended to receive the child's head when in sleeping posture. The bag is split for almost its entire length, where it is detachably connected together with buttons or other devices in order that the child may be readily placed into or removed from the bag, as desired.

Reference is to be had to the accompanying drawings forming a part of this specification, in which similar characters of reference indicate corresponding parts in all the figures.

Figure 1 is a perspective view of a bed with my improved sleeping bag applied thereto, as when in use; Fig. 2 is a longitudinal, central, sectional view through the same; Fig. 3 is an inverted plan of the bag; Fig. 4 is a cross section on the line 4-4 of Fig. 3, looking in the direction of the arrow, and Fig. 5 is a perspective view of a yoke which is used in connection with the bag to hold the child in position therein.

A bag 1, made of any suitable material and slightly longer than the child which it is to contain, is open at both ends, with one side thereof at the upper end extended, forming a flap 2 on which the head of the child when in sleeping posture, rests. The opposite side or top of the bag is split for almost its entire length, where it is provided with buttons or other like devices 3 for detachably connecting this part of the bag together. At each end and at each side are provided on the bottom of the bag reinforcing strips 4, having buttons or other equivalent devices 5 secured thereto for detachably connecting straps 6 for securing the bag in position on the mattress of the bed. These straps, as shown in Fig. 2, pass over the opposite ends of the mat-

tress, and are each connected with the wire springs of the bed by a hook member 7, or other suitable means, thus securely maintaining the bag in fixed position. If desired, straps 8 as shown in Fig. 1, may be connected to the bag and passed transversely of the mattress and secured in like or other suitable manner.

A yoke, shown in perspective in Fig. 5, for holding the child in position in the bag, is composed of shoulder-straps 9 connected to a breast-strap 10, the ends of the latter being brought together and detachably connected at 11. At each side of the breast-strap 10 a strap 12 is attached, both of which pass through the lower open end of the bag and thereafter are adjustably connected to a U-shaped member 13 of metal or other suitable material, embracing one end of the mattress. This adjustable connection of the straps 12 with the member 13 is preferably made by passing the straps through an opening in the member and engaging the free end of the strap by ball and socket buttons 14, shown in Fig. 2.

In use, the bag is secured in the desired position on the mattress where the child is to sleep. The bag is then unbuttoned, as also the ends of the breast-strap 10 detached and the child inserted therein, the arms passing through the shoulder-straps 9. The ends of the breast-strap are thereafter re-engaged and the straps 12 adjusted to bring the child to the proper position in the bag. The split portion of the bag should then be buttoned together, acting to keep the child from becoming uncovered.

Although I have described the invention in detail in order that the construction and operation thereof might be fully understood, the precise embodiment is not material provided the essential characteristics are employed as pointed out in the annexed claims.

Having thus described my invention I claim as new and desire to secure by Letters Patent:

1. The combination of a child's sleeping bag open at both ends, means for securing the bag in position on a mattress, and means passing through one end of the bag for holding the child in position therein.

2. The combination of a child's sleeping bag open at both ends, means for securing the bag in position on a mattress, and means for holding the child in position in the bag.

3. The combination of a child's sleeping bag open at both ends, means for securing the bag in position on a mattress, a yoke for holding the child in position in the bag, and
5 means attached to the yoke passing through one end of the bag for holding the yoke in place.

4. The combination of a child's sleeping bag open at both ends, straps attached to the
10 bag adapted to adjustably secure it upon a mattress, and means passing through one end of the bag for retaining the child in position therein.

5. The combination of a child's sleeping
15 bag open at both ends, and means passing

through one end of the bag for retaining the child in position therein.

6. The combination of a child's sleeping bag open at both ends, means passing through one end of the bag for retaining the child in
20 position therein, and means for adjustably attaching said retaining means.

In testimony whereof I have signed my name to this specification in the presence of two subscribing witnesses.

HERBERT WALN WILSON.

Witnesses:

HANS MILLER,
JOHN HOAGLIN.